



Revision Date 02-Oct-2024

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS
2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous
Products Regulation (HPR)

Version 1

1. Identification

Product identifier

Product Name 1AR FORM A GASKET #1 SEALANT 1.5 OZ.

Other means of identification

Product Code 80007

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex, Inc.
6875 Parkland Blvd.
Solon, Ohio 44139 USA
Telephone: 1-87-Permatex
(866) 732-9502

May Also Be Distributed by:

ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

E-mail address mail@permatex.com

Emergency telephone number

Company Phone Number 866-732-9502

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

24-hour emergency phone number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

2. Hazard(s) identification

Classification

Carcinogenicity

Category 1A

Label elements

Contains CRYSTALLINE SILICA; TITANIUM DIOXIDE; METHYL ISOBUTYL KETONE



Danger

Hazard statements

May cause cancer.

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use personal protective equipment as required.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

Precautionary Statements - Storage

Store locked up.

Precautionary Statements - Disposal

Dispose of contents and container to an approved waste disposal plant.

1.089 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

12.439 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

38.42 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

37 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

27.07 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Other Information

May be harmful if swallowed. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
KAOLIN	1332-58-7	30-60%	-	-
FUMARATED RESIN	65997-04-8	10-30%	-	-
ETHANOL	64-17-5	7-13%	-	-
2-PROPANOL	67-63-0	0.5-1.5%	-	-
TITANIUM DIOXIDE	13463-67-7	0.1-1%	-	-
CRYSTALLINE SILICA	14808-60-7	0.1-1%	-	-
METHANOL	67-56-1	0.1-1%	-	-
METHYL ISOBUTYL KETONE	108-10-1	0.1-1%	-	-

4. First-aid measures

Description of first aid measures

General advice	IF exposed or concerned: Get medical advice/attention.
Inhalation	Remove to fresh air.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin contact	Wash skin with soap and water.
Ingestion	Rinse mouth.

Most important symptoms and effects, both acute and delayed

Symptoms	No information available.
Effects of Exposure	May cause cancer.

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
--------------------	------------------------

5. Fire-fighting measures

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	No information available.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Personal precautions	Ensure adequate ventilation.
Other information	Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Pick up and transfer to properly labeled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
KAOLIN 1332-58-7	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
ETHANOL 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
2-PROPANOL 67-63-0	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
TITANIUM DIOXIDE 13463-67-7	TWA: 0.2 mg/m ³ nanoscale respirable particulate matter TWA: 2.5 mg/m ³ finescale respirable particulate matter	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ CIB 63 fine TWA: 0.3 mg/m ³ CIB 63 ultrafine, including engineered nanoscale
CRYSTALLINE SILICA 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
METHANOL 67-56-1	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) Sk*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm STEL: 75 ppm	TWA: 100 ppm TWA: 410 mg/m ³ (vacated) TWA: 50 ppm	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m ³

		(vacated) TWA: 205 mg/m ³ (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m ³	STEL: 75 ppm STEL: 300 mg/m ³
--	--	---	---

Chemical name	Alberta	British Columbia	Ontario	Quebec
KAOLIN 1332-58-7	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
ETHANOL 64-17-5	TWA: 1000 ppm TWA: 1880 mg/m ³	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm
2-PROPANOL 67-63-0	TWA: 200 ppm TWA: 492 mg/m ³ STEL: 400 ppm STEL: 984 mg/m ³	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³
CRYSTALLINE SILICA 14808-60-7	TWA: 0.025 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.10 mg/m ³	TWA: 0.1 mg/m ³
METHANOL 67-56-1	TWA: 200 ppm TWA: 262 mg/m ³ STEL: 250 ppm STEL: 328 mg/m ³ Sk*	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm TWA: 262 mg/m ³ STEL: 250 ppm STEL: 328 mg/m ³ Skin
METHYL ISOBUTYL KETONE 108-10-1	TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 307 mg/m ³	TWA: 20 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
KAOLIN	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
ETHANOL	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm
2-PROPANOL	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm
TITANIUM DIOXIDE	TWA: 0.2 mg/m ³ TWA: 2.5 mg/m ³	TWA: 10 mg/m ³	TWA: 0.2 mg/m ³ TWA: 2.5 mg/m ³	TWA: 0.2 mg/m ³ TWA: 2.5 mg/m ³
CRYSTALLINE SILICA	TWA: 0.025 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.025 mg/m ³
METHANOL	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm STEL: 250 ppm Sk*
METHYL ISOBUTYL KETONE	TWA: 20 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
KAOLIN	TWA: 2 mg/m ³ STEL: 4 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³ STEL: 4 mg/m ³	TWA: 30 mppcf TWA: 10 mg/m ³ STEL: 20 mg/m ³
ETHANOL	TWA: 1000 ppm STEL: 1250 ppm	STEL: 1000 ppm	TWA: 1000 ppm STEL: 1250 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ STEL: 1000 ppm STEL: 1900 mg/m ³
2-PROPANOL	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³ Sk*
TITANIUM DIOXIDE	TWA: 10 mg/m ³ STEL: 20 mg/m ³	TWA: 0.2 mg/m ³ TWA: 2.5 mg/m ³	TWA: 10 mg/m ³ STEL: 20 mg/m ³	TWA: 30 mppcf TWA: 10 mg/m ³ STEL: 20 mg/m ³
CRYSTALLINE SILICA	TWA: 0.05 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.05 mg/m ³	TWA: 300 particle/mL
METHANOL	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
	STEL: 250 ppm Sk*	STEL: 250 ppm	STEL: 250 ppm Skin	TWA: 260 mg/m ³ STEL: 250 ppm STEL: 310 mg/m ³ Sk*
METHYL ISOBUTYL KETONE	TWA: 50 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm	TWA: 50 ppm STEL: 75 ppm	TWA: 100 ppm TWA: 410 mg/m ³ STEL: 125 ppm STEL: 510 mg/m ³ Sk*

Biological occupational exposure limits

Chemical name	ACGIH
2-PROPANOL 67-63-0	40 mg/L - urine (Acetone) - end of shift at end of workweek
METHANOL 67-56-1	15 mg/L - urine (Methanol) - end of shift
METHYL ISOBUTYL KETONE 108-10-1	1 mg/L - urine (MIBK) - end of shift

Appropriate engineering controls

Engineering controls	Showers Eyewash stations Ventilation systems.
-----------------------------	---

Individual protection measures, such as personal protective equipment

Eye/face protection	Appropriate eye/face protection should be selected and used according to the chemical nature, hazards and use of this product and safety requirements of the local jurisdiction.
Hand protection	Wear suitable gloves.
Skin and body protection	Wear suitable protective clothing.
Respiratory protection	Appropriate respiratory protection should be selected and used according to the chemical nature, hazards and use of this product and safety requirements of the local jurisdiction. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
General hygiene considerations	Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties**Information on basic physical and chemical properties**

Physical state	Paste / Gel Liquid
Appearance	Paste
Color	Red-Brown
Odor	Alcohol
Odor threshold	No information available

Property	Values	Remarks • Method
pH	No data available	Melting point / freezing point No data available
Boiling point / boiling range	82 °C / 179.6 °F	

Flash point	No data available	ASTM D 4359	
Evaporation rate	7.7	Butyl acetate = 1	
Flammability (solid, gas)	No data available	Flammability Limit in Air	
Upper flammability limit:	No data available		
Lower flammability limit:	No data available		
Vapor pressure	33 mmHg @ 68°F		
Vapor density	>1	Air = 1	
Relative density	1.44		
Water solubility	No data available	Partially soluble	
Solubility(ies)	No Data Available	Partition coefficient	No Data Available
Autoignition temperature	No data available	Decomposition temperature	No data available
Kinematic viscosity	No Data Available	Dynamic viscosity	No data available
Other information			
Explosive properties	No information available		
Oxidizing properties	No information available		
Softening point	No information available		
Molecular weight	No information available		
VOC content	13.51		
Density	No information available		
Bulk density	No information available		

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	None known based on information supplied.
Incompatible materials	None known based on information supplied.
Hazardous decomposition products	Carbon oxides. Aldehydes. Carboxylic acids.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available.
Eye contact	Specific test data for the substance or mixture is not available.
Skin contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	No information available.
----------	---------------------------

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	4,933.60 mg/kg
ATEmix (dermal)	6,070.20 mg/kg

ATEmix (inhalation-gas) 99,999.00 ppm
 ATEmix (inhalation-vapor) 1,335.4314 mg/l
 ATEmix (inhalation-dust/mist) 55.50 mg/l

1.089 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
 12.439 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
 38.42 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
 37 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
 27.07 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
KAOLIN 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
FUMARATED RESIN 65997-04-8	> 2000 mg/kg (Rat)	= 2000 mg/kg (Rat)	-
ETHANOL 64-17-5	= 7060 mg/kg (Rat)	-	= 116.9 mg/L (Rat) 4 h = 133.8 mg/L (Rat) 4 h
2-PROPANOL 67-63-0	5050 mg/kg	12800 mg/kg	> 10000 ppm (Rat) 6 h
TITANIUM DIOXIDE 13463-67-7	> 2000 mg/kg (Rat)	-	> 5.09 mg/L (Rat) 4 h
METHANOL 67-56-1	= 6200 mg/kg (Rat)	= 15840 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	2000 - 4000 ppm (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
ETHANOL 64-17-5	A3	Group 1	Known	X
TITANIUM DIOXIDE 13463-67-7	A3	Group 2B	-	X
CRYSTALLINE SILICA 14808-60-7	A2	Group 1	Known	X
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B	-	X

Legend**ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

12. Ecological information

Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
FUMARATED RESIN 65997-04-8	-	LC50: =3.2mg/L (96h, Brachydanio rerio)	-	-
ETHANOL 64-17-5	-	LC50: 12.0 - 16.0mL/L (96h, Oncorhynchus mykiss) LC50: >100mg/L (96h, Pimephales promelas) LC50: 13400 - 15100mg/L (96h, Pimephales promelas)	-	LC50: 9268 - 14221mg/L (48h, Daphnia magna) EC50: =2mg/L (48h, Daphnia magna)
2-PROPANOL 67-63-0	EC50: >1000mg/L (96h, Desmodesmus subspicatus) EC50: >1000mg/L (72h, Desmodesmus subspicatus)	LC50: =9640mg/L (96h, Pimephales promelas) LC50: =11130mg/L (96h, Pimephales promelas) LC50: >1400000µg/L (96h, Lepomis macrochirus)	-	EC50: =13299mg/L (48h, Daphnia magna)
METHANOL 67-56-1	-	LC50: =28200mg/L (96h, Pimephales promelas) LC50: >100mg/L (96h, Pimephales promelas) LC50: 19500 - 20700mg/L (96h, Oncorhynchus mykiss) LC50: 18 - 20mL/L (96h, Oncorhynchus mykiss) LC50: 13500 - 17600mg/L (96h, Lepomis macrochirus)	-	-
METHYL ISOBUTYL KETONE 108-10-1	EC50: =400mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 496 - 514mg/L (96h, Pimephales promelas)	-	EC50: =170mg/L (48h, Daphnia magna)

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
---------------	-----------------------

FUMARATED RESIN 65997-04-8	7
ETHANOL 64-17-5	-0.35
2-PROPANOL 67-63-0	0.05
METHANOL 67-56-1	-0.77
METHYL ISOBUTYL KETONE 108-10-1	1.9

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

US EPA Waste Number Waste designations and classifications should be determined by the end user based on the application for which the product was used.

14. Transport information

DOT Not regulated

TDG Not regulated

MEX Not regulated

IATA Not regulated

IMDG Not regulated

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Complies
ENCS	Not determined

IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies
NZIoC	Complies

Legend:**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances**ENCS** - Japan Existing and New Chemical Substances**IECSC** - China Inventory of Existing Chemical Substances**KECL** - Korean Existing Chemicals Inventory**PICCS** - Philippines Inventory of Chemicals and Chemical Substances**AICS** - Australian Inventory of Chemical Substances**NZIoC** - New Zealand Inventory of Chemicals**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
2-PROPANOL - 67-63-0	1.0
METHYL ISOBUTYL KETONE - 108-10-1	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
METHANOL 67-56-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
METHYL ISOBUTYL KETONE 108-10-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
ETHANOL - 64-17-5	*Developmental (in alcoholic beverages)
TITANIUM DIOXIDE - 13463-67-7	*Carcinogen (airborne, unbound particles of respirable size)
CRYSTALLINE SILICA - 14808-60-7	*Carcinogen
METHANOL - 67-56-1	Developmental
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental

Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage *The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
KAOLIN 1332-58-7	X	X	X
ETHANOL 64-17-5	X	X	X
2-PROPANOL 67-63-0	X	X	X
WATER 7732-18-5	-	-	X
CRYSTALLINE SILICA 14808-60-7	X	X	X
METHYL ISOBUTYL KETONE 108-10-1	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 1 Flammability 0 Instability 0 Special hazards -
HMIS Health hazards * Flammability 0 Physical hazards 0 Personal protection X
 Chronic Hazard Star Legend * = Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet**Legend**

SVHC: Substances of Very High Concern for Authorization:
 PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
 vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
 STOT: Specific Target Organ Toxicity
 ATE: Acute Toxicity Estimate
 LC50: 50% Lethal Concentration
 LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)
 Ceiling Maximum limit value * Skin designation
 + Sensitizers

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
 U.S. Environmental Protection Agency ChemView Database
 European Food Safety Authority (EFSA)
 Environmental Protection Agency
 Acute Exposure Guideline Level(s) (AEGL(s))
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
 U.S. Environmental Protection Agency High Production Volume Chemicals
 Food Research Journal
 Hazardous Substance Database
 International Uniform Chemical Information Database (IUCLID)
 National Institute of Technology and Evaluation (NITE)
 Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
 NIOSH (National Institute for Occupational Safety and Health)
 National Library of Medicine's ChemID Plus (NLM CIP)
 National Library of Medicine's PubMed database (NLM PUBMED)
 U.S. National Toxicology Program (NTP)
 New Zealand's Chemical Classification and Information Database (CCID)
 Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
 Organization for Economic Co-operation and Development High Production Volume Chemicals Program
 Organization for Economic Co-operation and Development Screening Information Data Set
 World Health Organization

Revision Date 02-Oct-2024

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.