Product Number 840

Issuing Date No data available

SAFETY DATA SHEET

Revision Number 2

•

Revision Date 03-11-2015



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Acetone

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Multi-purpose solvent

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier NameSunnyside CorporationSupplier Address225 Carpenter Avenue

Wheeling IL 60090

Supplier Phone Number US Phone:8003238611

Fax:8475419043

 Supplier Email
 sscontact@sunnysidecorp.com

 Emergency telephone number
 Chem Trec 8004249300

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

GHS Label elements, including precautionary statements



Emergency Overview

Signal word

Danger

Hazard Statements

Causes serious eye irritation May cause drowsiness or dizziness Highly flammable liquid and vapor





Appearance Clear

Physical State Liquid

Odor Pungent

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ ventilating/ lighting/ equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

Precautionary Statements - Response

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity



Other information

May be harmful if inhaled

PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical Name	CAS No	Weight-%	Trade Secret
Acetone	67-64-1	60 - 100	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Show this safety data sheet to the doctor in attendance.

Eye Contact If symptoms persist, call a physician. Rinse immediately with plenty of water, also

under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub

affected area.

Skin Contact In the case of skin irritation or allergic reactions see a physician. Wash off

immediately with soap and plenty of water while removing all contaminated clothes

and shoes.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, (trained personnel should) give oxygen.

Ingestion Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water.

Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take

precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Burning sensation. Drowsiness. Dizziness.

Effects

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable Extinguishing Media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Vapors can form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Uniform Fire Code Flammable Liquid: I-B

Irritant: Liquid

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

All equipment used when handling the product must be grounded. Do not touch or walk

through spilled material. Stop leak if you can do it without risk.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental Precautions

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for ContainmentA vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth,

sand or other non-combustible material and transfer to containers.

Methods for cleaning up

Use clean non-sparking tools to collect absorbed material. Soak up with inert absorbent

material. Dike far ahead of liquid spill for later disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

HandlingHandle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Do not eat, drink or smoke when using this product. Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area

equipped with sprinklers. Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials.

Keep in an area equipped with sprinklers.

Incompatible ProductsNone known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL = 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm 10% LEL
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 1800 mg/m ³	TWA: 590 mg/m ³
		(vacated) TWA: 750 ppm	_
		(vacated) STEL: 1000 ppm	
		(vacated) STEL: 2400 mg/m ³	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Tight sealing safety goggles.

Skin and Body ProtectionLong sleeved clothing. Chemical resistant apron. Impervious gloves. Antistatic boots.

Respiratory ProtectionNo protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.



Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

None known

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State Liquid **Appearance** Clear Odor Pungent No information available Color Colorless **Odor Threshold**

Values Remarks/ Method Property None known рΗ Melting / freezing point No data available None known 56 °C / 133 °F Boiling point / boiling range None known -18 C / 0 F Flash Point None known **Evaporation Rate** No data available None known Flammability (solid, gas) N/A None known

Flammability Limit in Air

Upper flammability limit No data available Lower flammability limit 2.5% @ 77 °F 213 mmHg @ 75 °F Vapor pressure Vapor density No data available No **Specific Gravity** data available Water Solubility Soluble in water No Solubility in other solvents data available Partition coefficient: n-octanol/waterNo data available

Autoignition temperature 869 °F

No data available **Decomposition temperature** No data available Kinematic viscosity Dynamic viscosity No data available No data available **Explosive properties** No data available **Oxidizing Properties**

Other Information

Softening Point

VOC Content (%) Exempt **Particle Size**

Particle Size Distribution

No data available

No data available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Caustics, amines, alkanolamines, ammonia, strong oxidizing agents and chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information .

Inhalation Specific test data for the substance or mixture is not available. May cause drownsiness and

dizziness based on components. May cause irritation of respiratory tract.

Eye Contact Specific test data for the substance or mixture is not available. Expected to be an irritant

based on components. May cause redness, itching, and pain. May cause temporary eye

irritation.

Skin Contact Specific test data for the substance or mixture is not available. May cause irritation.

Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	-	-	= 50100 mg/m ³ (Rat) 8 h
67-64-1			, ,

Information on toxicological effects

Symptoms May cause redness and tearing of the eyes.

Delayed and immediate effects as well as chronic effects from short and long-term exposure



Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity Contains no ingredient listed as a carcinogen.

Reproductive Toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Chronic Toxicity No known effect based on information supplied.

Target Organ Effects Eyes. Central Nervous System (CNS). Respiratory system. Skin.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist)

100.20 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Chemical Name	Log Pow
Acetone	-0.24
67-64-1	

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number D001 U002

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone				U002
67-64-1				

California Hazardous Waste Codes 212

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Acetone	Ignitable
67-64-1	

14. TRANSPORT INFORMATION

DOT

UN-No. UN1090 Proper Shipping Name ACETONE

Hazard Class 3
Packing Group II

Description UN1090, ACETONE, 3, II

<u>TDG</u>

UN-No. UN1090 Proper Shipping Name ACETONE

Hazard Class 3
Packing Group |

Description UN1090, ACETONE, 3, II

MEX

UN-No. UN1090 Proper Shipping Name ACETONE

Hazard Class 3 Packing Group II

Description UN1090 ACETONE, 3, II

<u>ICAO</u>

UN-No. UN1090 Proper Shipping Name ACETONE

Hazard Class 3
Packing Group ||

Description UN1090, ACETONE, 3, II

IATA

UN-No. UN1090 Proper Shipping Name ACETONE

Hazard Class 3

Packing Group ||

Description UN1090, ACETONE, 3, II

IMDG/IMO

UN-No. UN1090
Proper Shipping Name ACETONE

Hazard Class 3 Packing Group II

EmS No. F-E, S-D

Description UN1090, ACETONE, 3, II, FP -18C

RID

UN-No. UN1090 Proper Shipping Name UN1090 ACETONE

Hazard Class 3
Packing Group || Classification code F1

Description UN1090 ACETONE, 3, II

<u>ADR</u>

UN-No. UN1090 Proper Shipping Name ACETONE

Hazard Class 3
Packing Group || Classification code F1

Description UN1090 ACETONE, 3, II

ADN

UN-No. UN1090 Proper Shipping Name ACETONE

Hazard Class 3
Packing Group || Classification code F1

Description UN1090 ACETONE, 3, II

Hazard Labels 3 Limited Quantity 1 L Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard No
Fire Hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No



CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Acetone 67-64-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Acetone	Χ	X	X	X	
67-64-1					

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Acetone		Mexico: TWA= 1000 ppm
67-64-1 (60 - 100)		Mexico: TWA= 2400 mg/m ³
		Mexico: STEL= 1260 ppm
		Mexico: STEL= 3000 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

B2 - Flammable liquid D2B - Toxic materials





NFPA Health Hazards 2 Flammability 3 Instability 0 Physical and Chemical Hazards HMIS Health Hazards 2 Flammability 3 Physical Hazard 0 Personal Protection



Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110

1-800-572-6501 15-Sep-2014

Revision Note No information available

Disclaimer

Revision Date

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet



Page 12/12