

7/1/2025: File reviewed, more current MSDS/SDS not available. CAS

Safety Data Sheet

Material Name: ACETYLENE, DISSOLVED

SDS ID: MAT00280

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name ACETYLENE, DISSOLVED **Synonyms** ACETYLENE; ETHYNE; WELDING GAS; ACETYLEN; ETHINE; NARCYLEN; VINYLENE; UN 1001; C2H2; **Chemical Family** Hydrocarbons, aliphatic **Product Use** Industrial and Specialty Gas Applications. **Restrictions on Use** None known. Details of the supplier of the safety data sheet MATHESON TRI-GAS, INC. 909 Lake Carolyn Parkway Suite 1300 Irving, TX 75039 General Information: 1-800-416-2505 Emergency #: 1-800-424-9300 (CHEMTREC) Outside the US: 703-527-3887 (Call collect)

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200. Flammable Gases - Category 1 Gases Under Pressure - Dissolved gas Specific Target Organ Toxicity - Single Exposure - Category 3 (central nervous system.) GHS Label Elements Symbol(s)



Signal Word Danger Hazard Statement(s) Extremely flammable gas. Contains gas under pressure; may explode if heated. May cause drowsiness or dizziness. May displace oxygen and cause rapid suffocation. Precautionary Statement(s) Prevention Keep away from heat/sparks/open flame/hot surfaces - No smoking. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Response



Material Name: ACETYLENE, DISSOLVED

Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so. IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. **Storage** Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other Hazards

Rapid release of compressed gas may cause frostbite. Explosive with or without contact with air.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

| CAS | Component Name | Percent | |
|---------|----------------------|---------|--|
| 74-86-2 | ACETYLENE, DISSOLVED | 100 | |

Section 4 - FIRST AID MEASURES

Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Skin

Wash exposed skin with soap and water.

Eyes

Flush eyes with plenty of water.

Ingestion

If swallowed, get medical attention.

Most Important Symptoms/Effects

Acute

Frostbite, suffocation, Depression of central nervous system

Delayed

No information on significant adverse effects.

Note to Physicians

For inhalation, consider oxygen.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media Suitable Extinguishing Media

carbon dioxide, regular dry chemical, Large fires: Use regular foam or flood with fine water spray.

Unsuitable Extinguishing Media

None known.

Special Hazards Arising from the Chemical

Severe explosion hazard. Vapor/air mixtures are explosive. Electrostatic discharges may be generated by flow or agitation resulting in ignition or explosion. **Hazardous Combustion Products**

Oxides of carbon.

Fire Fighting Measures





Material Name: ACETYLENE, DISSOLVED

SDS ID: MAT00280

Move container from fire area if it can be done without risk. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck: Stop leak if possible without personal risk. Let burn unless leak can be stopped immediately. For smaller tanks or cylinders, extinguish and isolate from other flammables. Evacuation radius: 800 meters (1/2 mile). Do not attempt to extinguish fire unless flow of material can be stopped first. Flood with fine water spray. Cool containers with water spray until well after the fire is out. Apply water from a protected location or from a safe distance. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Evacuate if fire gets out of control or containers are directly exposed to fire. Evacuation radius: 500 meters (1/3 mile). Consider downwind evacuation if material is leaking. Stop flow of gas.

Special Protective Equipment and Precautions for Firefighters

Wear personal protective clothing and equipment such as self-contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Avoid heat, flames, sparks and other sources of ignition. Stop leak if possible without personal risk. Reduce vapors with water spray. Keep unnecessary people away, isolate hazard area and deny entry. Remove sources of ignition. Ventilate closed spaces before entering. Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ (U.S. SARA Section 304).

Environmental Precautions

Avoid release to the environment.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from heat/sparks/open flame/hot surfaces - No smoking. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray.

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight.

Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.

Incompatible Materials

metals, halogens, oxidizing materials, metal carbide, reducing agents, halo carbons

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

| ACETYLENE, DISSOLVED | 74-86-2 | | | |
|----------------------|---|--|--|--|
| ACGIH: | (See Appendix F: Minimal Oxygen Content, explosion hazard) | | | |
| NIOSH: | 2500 ppm Ceiling ; 2662 mg/m3 Ceiling | | | |

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.



Material Name: ACETYLENE, DISSOLVED

Engineering Controls

Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Eye protection not required, but recommended.

Skin Protection

Protective clothing is not required.

Respiratory Protection

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

Glove Recommendations

Protective gloves are not required, but recommended.

| Section 9 - PHYSICAL AND CHEMICAL PROPERTIES | | | | | | | | |
|--|---|----------------------------------|----------------------------|--|--|--|--|--|
| Appearance | Not available | Physical State | gas | | | | | |
| Odor | sweet odor | Color | colorless | | | | | |
| Odor Threshold | Not available | рН | Not available | | | | | |
| Melting Point | Not available | Boiling Point | Not available | | | | | |
| Boiling Point Range | Not available | Freezing point | Not available | | | | | |
| Evaporation Rate | Not available | Flammability (solid, gas) | Not available | | | | | |
| Autoignition Temperature | 305 °C (581 °F) | Flash Point | Not available | | | | | |
| Lower Explosive Limit | 2.5 % | Decomposition temperature | Not available | | | | | |
| Upper Explosive Limit | 100 % | Vapor Pressure | 760 mmHg @ -84 °C | | | | | |
| Vapor Density (air=1) | 0.9 | Specific Gravity (water=1) | Not available | | | | | |
| Water Solubility | Solubility 0.94 % (@ 25 °C) Partition coefficient: n-octanol/water | | 2691.53 | | | | | |
| Viscosity | 0.01 cp | Kinematic viscosity | Not available | | | | | |
| Solubility (Other) | Not available | Bioconcentration Factor (BCF) | 3.48 | | | | | |
| Density | 1.1747 g/L at 0 °C | Henry's Law Constant | 0.00277024 atm- m3/mole | | | | | |



Material Name: ACETYLENE, DISSOLVED

SDS ID: MAT00280

| al Name: ACETTLEN | E, DISSOLVED | | 5D5 ID: M/ | |
|--|--|--------------------------------|----------------------------|--|
| КОС | 4508.17 (estimated from water solubility) | Physical Form | gas | |
| Sublimation | -84 °C (-119 °F) | Molecular Formula | Н-С-С-Н | |
| Molecular Weight | 26.04 | | | |
| Solvent Solubility Soluble acetone, Benzene, chloro | oform, ether | · | | |
| · · · | Section 10 - STABILIT | Y AND REACTIVITY | 7 | |
| Conditions to Avoid Avoid heat, flames, spar Incompatible Material metals, halogens, oxidiz Hazardous decomposit | ion of heat. Avoid contact with cur ks and other sources of ignition. Co s ing materials, metal carbide, reduct | ontainers may rupture or exp | | |
| Oxides of carbon | Section 11 - TOXICOLO | CICAL INFORMATIO | | |
| Information on Likely | | JICAL INFORMATIN | | |
| Inhalation nausea, vomiting, chest suffocation, lung conges Skin Contact rash Eye Contact no information on signif | | ess, dizziness, loss of coordi | nation, bluish skin color, | |
| Ingestion ingestion of a gas is unli Acute and Chronic To: Component Analysis - | ikely xicity | ious sources and no selected | l endpoints have been | |
| Product Toxicity Data Acute Toxicity Estimat No data available. Immediate Effects | te | | | |

Frostbite, suffocation, Depression of central nervous system

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

No data available.

Respiratory Sensitization No data available. **Dermal Sensitization**



Material Name: ACETYLENE, DISSOLVED

No data available. **Component Carcinogenicity** None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA. Germ Cell Mutagenicity No data available. **Tumorigenic Data** No data available **Reproductive Toxicity** No data available. Specific Target Organ Toxicity - Single Exposure Category 3. central nervous system Specific Target Organ Toxicity - Repeated Exposure **Aspiration hazard** No data available. Medical Conditions Aggravated by Exposure No data available. **Additional Data** Stimulants such as epinephrine may induce ventricular fibrillation.

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

No LOLI ecotoxicity data are available for this product's components. **Persistence and Degradability** No information available for the product. **Bioaccumulative Potential** No information available for the product. **Mobility** No information available for the product.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001. D003.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

Section 14 - TRANSPORT INFORMATION

US DOT Information: Shipping Name: ACETYLENE, DISSOLVED Hazard Class: 2.1 UN/NA #: UN1001 Required Label(s): 2.1

TDG Information: Shipping Name: ACETYLENE, DISSOLVED Hazard Class: 2.1 UN#: UN1001 Required Label(s): 2.1 International Bulk Chemical Code



Material Name: ACETYLENE, DISSOLVED

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

Flammable; Gas Under Pressure; Specific Target Organ Toxicity

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

| Component | CAS | CA | MA | MN | NJ | PA |
|----------------------|---------|-----|-----|-----|-----|-----|
| ACETYLENE, DISSOLVED | 74-86-2 | Yes | Yes | Yes | Yes | Yes |

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

Not listed under California Proposition 65.

Component Analysis - Inventory

ACETYLENE, DISSOLVED (74-86-2)

| US | CA | AU | CN | EU | JP - ENCS | JP - ISHL | KR KECI - Annex 1 | KR KECI - Annex 2 |
|-----|-----|-----|-----|-----|-----------|-----------|-------------------|-------------------|
| Yes | DSL | Yes | Yes | EIN | Yes | Yes | Yes | No |

| KR - REACH CCA | MX | NZ | PH | TH-TECI | TW, CN | VN (Draft) | |
|----------------|-----|-----|-----|---------|--------|------------|--|
| No | Yes | Yes | Yes | Yes | Yes | Yes | |

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 1 Fire: 4 Instability: 3 Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe **Summary of Changes** Updated: 05/01/2015

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU -Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA -California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CERCLA -Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG -Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN -European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; F - Background (for Venezuela Biological Exposure Indices); IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH -

Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan



Material Name: ACETYLENE, DISSOLVED

SDS ID: MAT00280

Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL), KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; KR REACH CCA - Korea Registration and Evaluation of Chemical Substances Chemical Control Act; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts[™] - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; Ne- Non-specific; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; Ng - Non-quantitative; NSL - Non-Domestic Substance List (Canada); NTP -National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL-Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH-Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA -Superfund Amendments and Reauthorization Act; Sc - Semi-quantitative; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TH-TECI - Thailand -FDA Existing Chemicals Inventory (TECI); TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); VN (Draft) - Vietnam (Draft); WHMIS -Workplace Hazardous Materials Information System (Canada).

Other Information

Disclaimer:

Matheson Tri-Gas, Inc. makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Matheson Tri-Gas, Inc. shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.