

ATTENTION: SAFETY DIRECTOR

((C))

FROM: INDUSTRIAL CHEMICAL LAB., INC.
1015 NORTH 14 ST.
OMAHA, NE. 68102
TELEPHONE: (402)342-4248

TRADE NAME: ARISTO SUPREME GYM FINISH
DATE ISSUED: 4/18/91 REVISED DATE: 5/25/86

		0	MINIMAL HAZARD
HEALTH:	2	1	SLIGHT HAZARD
FLAMMABILITY:	2	2	MODERATE HAZARD
REACTIVITY:	0	3	SERIOUS HAZARD
PERSONAL PROTECTION:	2	4	SEVERE HAZARD

INGREDIENTS

INGREDIENT:

RESINS

CAS REG. NO.: NOT EST. PERCENTAGE: 40
TLV: NOT EST.

INGREDIENT:

STODDARD SOLVENT

CAS REG. NO.: 64741-41-9 PERCENTAGE: 60
TLV: 100 PPM (TWA)

PHYSICAL DATA

BOILING POINT: 320 SPECIFIC GRAVITY: 0.875 VAPOR PRESSURE: NA
PERCENT VOLATILE BY VOLUME: 60 VAPOR DENSITY: >1
EVAPORATION RATE: ETHYL ETHER -1 >1
SOLUBILITY IN WATER: NEGLIGIBLE

APPEARANCE AND ODOR:

VISCOUS AMBER LIQUID WITH MINERAL SPIRIT ODOR.

FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 103 DEGREES F TCC
FLAMMABLE LIMITS: NA
LEL: NA UEL: NA
EXTINGUISHING MEDIA:
FOAM, DRY CHEMICAL CO2
SPECIAL FIRE FIGHTING PROCEDURES:
WATER WILL BE INEFFECTIVE.
UNUSUAL FIRE AND EXPLOSION HAZARDS:

SPRAY FRONT TO BACK.

REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID:

NONE

INCOMPATIBILITY (MATERIALS TO AVOID):

NONE

HAZARDOUS DECOMPOSITION PRODUCTS:

CO, CO2

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID:

NONE

HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE:

100 PPM (TWA)

ROUTE(S) OF ENTRY: INHALATION: + SKIN: + INGESTION: +

EFFECTS OF OVEREXPOSURE:

CONTACT WITH EYES OR SKIN MAY CAUSE IRRITATION. INHALATION OF MIST OR VAPOR MAY RESULT IN NAUSEA, HEADACHE, OR NARCOSIS. INGESTION MAY BE FATAL.

CARCINOGENICITY: NTP: - IARC MONOGRAPHS: - OSHA REGULATED: -

EMERGENCY FIRST AID PROCEDURES:

FOR SKIN CONTACT, WASH THOROUGHLY WITH SOAP AND WATER. FOR EYE CONTACT, FLUSH WITH CLEAR WATER FOR 15 MINUTES AND CONSULT A PHYSICIAN. IF INHALED, AND RESPIRATORY EFFECTS OCCUR, REMOVE TO FRESH AIR. IF INGESTED, DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN.

PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

PICK UP WITH OIL ABSORBENT, SAWDUST, OR PAINT REMOVER.

WASTE DISPOSAL METHOD:

LANDFILL IN ACCORDANCE WITH APPROPRIATE LOCAL, STATE AND FEDERAL REGULATIONS.

RCRA: INGITABLE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

KEEP OUT OF REACH OF CHILDREN. KEEP AWAY FROM STRONG OXIDIZERS, SOURCES OF HEAT AND OPEN FLAME. AVOID EYE AND PROLONGED SKIN CONTACT. AVOID PROLONGED BREATHING OF VAPOR. DO NOT REUSE CONTAINER. DO NOT CUT, WELD OR PUNCTURE CONTAINER. REPLACE LID AFTER USE.

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE):

RESPIRATOR MEETING NIOSH/MESA 23C SPECS.

VENTILATION:

MECHANICAL EXHAUST IS ADEQUATE.

PROTECTIVE GLOVES:

PLASTIC OR NEOPRENE

EYE PROTECTION:

SPLASHPROOF CHEMICAL SAFETY GOGGLES.

OTHER PROTECTIVE EQUIPMENT:

NONE