Version 2.1

Revision Date 05/12/2020 Print Date 06/01/2020

9/4/2024: File reviewed, more current MSDS/SDS not available. CAS

AM

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

RENOWN BASEBOARD STRIPPER AEROSOL REN05022-Material name :

Material number

0000000001034140 :

Manufacturer or supplier's details

DISTRIBUTOR

Home Depot 701 San Marco Blvd. Jacksonville, FL 32207 Customer Service: 866-412-6726

VERISK 3E	: 1-800-451-8346 (USA) 1-760-602-8703 (INTERNATIONAL)	

Recommended use of the chemical and restrictions on use

Recommended use : Floor Care

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	white
Odour	alcohol-like, amine-like

GHS Classification

Flammable aerosols Gases under pressure Skin irritation Serious eye damage	:	Category 2 Liquefied gas Category 2 Category 1
GHS label elements		
Hazard pictograms	:	Flame Gas cylinder Corrosion
Signal word	:	Danger
Hazard statements	:	H223 Flammable aerosol. H280 Contains gas under pressure; may explode if heated. H315 Causes skin irritation. H318 Causes serious eye damage.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames

Version 2.1 Revision Date 05/12/2020 Print Date 06/01/2020 and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ eye protection/ face protection. **Response:** P302 + P352 IF ON SKIN: Wash with plenty of water. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. Storage: P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Disposal: P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
propan-2-ol	67-63-0	>= 5 - < 10
butane	106-97-8	>= 5 - < 10
2-aminoethanol	141-43-5	>= 3 - < 5
2-butoxyethanol	111-76-2	>= 3 - < 5
ethanol	64-17-5	>= 1 - < 3
propane	74-98-6	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	 Move out of dangerous area. Consult a physician. Do not leave the victim unattended. Show this safety data sheet to the doctor in attendance.
If inhaled	: If unconscious, place in recovery position and seek medical advice.
In case of skin contact	 Wash off with soap and water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty. If on clothes, remove clothes. Wash off immediately with plenty of water for at least 15

Version 2.1	Revision Date 05/12/2020	Print Date 06/01/2020
In case of eye contact	minutes.Wash contaminated clothing befoSmall amounts splashed into eyes tissue damage and blindness.	
	Continue rinsing eyes during trans Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing If in eyes, rinse with water for 15 r	 I.
If swallowed	 Clean mouth with water and drink Keep respiratory tract clear. Never give anything by mouth to a DO NOT induce vomiting unless of physician or poison control center Take victim immediately to hospit 	an unconscious person. directed to do so by a
Most important symptoms and effects, both acute and delayed	 Effects are immediate and delaye Symptoms may include blistering. Effects are dependent on exposu contact time). Causes skin irritation. Causes serious eye damage. Review section 2 of SDS to see a 	, irritation, burns, and pain. re (dose, concentration,
Notes to physician	: Treat symptomatically. Symptom	•

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media Unsuitable extinguishing media	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical High volume water jet	
Specific hazards during firefighting	Do not allow run-off from fire fighting to enter drains or wa courses.	ater
Hazardous combustion products	Carbon dioxide (CO2) Carbon monoxide Smoke Nitrogen oxides (NOx)	
Specific extinguishing methods Further information	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Fire residues and contaminated fire extinguishing water n be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.	nust
Special protective equipment for firefighters	Wear self-contained breathing apparatus for firefighting if necessary.	

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	: Use personal protective equipment.
protective equipment and	Ensure adequate ventilation.
emergency procedures	Remove all sources of ignition.
	Evacuate personnel to safe areas.

Version 2.1	Revision Date 05/12/2020	Print Date 06/01/2020
Environmental precautions	Beware of vapours accumulating concentrations. Vapours can accuPrevent product from entering dra Prevent further leakage or spillage	imulate in low areas. ins. e if safe to do so.
Methods and materials for containment and cleaning up	 If the product contaminates rivers respective authorities. Soak up with inert absorbent mate acid binder, universal binder, saw Sweep up or vacuum up spillage a container for disposal. 	erial (e.g. sand, silica gel, dust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Do not breathe vapours or spray mist. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Always replace cap after use.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Keep in a cool, well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Do not store near acids.
Storage temperature	: 4.4 - 49 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0

Version 2.1

Revision Date 05/12/2020 Print Date 06/01/2020

		STEL	500 ppm 1,225 mg/m3	OSHA P0
		PEL	400 ppm 980 mg/m3	CAL PEL
		STEL	500 ppm 1,225 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH
2-aminoethanol	141-43-5	TWA	3 ppm	ACGIH
		STEL	6 ppm	ACGIH
		TWA	3 ppm 8 mg/m3	NIOSH REL
		ST	6 ppm 15 mg/m3	NIOSH REL
		TWA	3 ppm 6 mg/m3	OSHA Z-1
		STEL	6 ppm 15 mg/m3	OSHA P0
		TWA	3 ppm 8 mg/m3	OSHA P0
		PEL	3 ppm 8 mg/m3	CAL PEL
		STEL	6 ppm 15 mg/m3	CAL PEL
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
		PEL	20 ppm 97 mg/m3	CAL PEL
ethanol	64-17-5	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0
		STEL	1,000 ppm	ACGIH
		PEL	1,000 ppm 1,900 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL

Version 2.1

Revision Date 05/12/2020

Print Date 06/01/2020

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workwee k	40 mg/l	ACGIH BEI
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200.mg/g Creatinine	ACGIH BEI

Engineering measures	effective ventilation in all processing areas	
Personal protective equipme		
Respiratory protection	Use respiratory protection unless adequate local exha ventilation is provided or exposure assessment demor hat exposures are within recommended exposure gui	nstrates
Hand protection Material Remarks	Protective gloves The suitability for a specific workplace should be discu vith the producers of the protective gloves.	issed
Eye protection	Safety glasses Ensure that eyewash stations and safety showers are he workstation location.	close to
Skin and body protection	mpervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work	place.
Hygiene measures	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: white
Odour	: alcohol-like, amine-like
Odour Threshold	: No data available
рН	: No data available
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	: Not applicable
Evaporation rate	: <1

Version 2.1	Revision Date 05/12/2020	Print Date 06/01/2020
	n-Butyl Acetate = 1.0	
Flammability (solid, gas, liquid)	: Flammable aerosol.	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Density	: No data available	
Solubility(ies)		
Water solubility	: soluble	
Partition coefficient: n- octanol/water	: No data available	
Auto-ignition temperature	: not determined	
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: No data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Alkali metals Copper Strong acids
Hazardous decomposition products	: Carbon oxides Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	:	None known.
Symptoms of Overexposure	:	Effects are immediate and delayed.
		Symptoms may include blistering, irritation, burns, and pain.

Version 2.1	Revision Date 05/12/2020	Print Date 06/01/2020
	Effects are dependent on exposicontact time). Causes skin irritation. Causes serious eye damage. Review section 2 of SDS to see Treat symptomatically. Symptor	all potential hazards.
Carcinogenicity:		
IARC	No component of this product prese equal to 0.1% is identified as proba	
ACGIH	human carcinogen by IARC. Confirmed animal carcinogen with humans	unknown relevance to
00114	2-butoxyethanol ethanol	111-76-2 64-17-5
OSHA NTP	No component of this product prese equal to 0.1% is on OSHA's list of r No component of this product prese equal to 0.1% is identified as a kno by NTP.	regulated carcinogens. ent at levels greater than or
Acute toxicity		
Product:		
Acute oral toxicity	: Acute toxicity estimate : > 5,000 Method: Calculation method	mg/kg
Acute inhalation toxicity	: Acute toxicity estimate : 15.99 m Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method	ng/l
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 Method: Calculation method	mg/kg
Components:		
propan-2-ol: Acute oral toxicity	: LD50 Oral Rat: 4,396 mg/kg Method: Calculation method	
2-aminoethanol: Acute oral toxicity	: LD50 Oral Mouse: 700 mg/kg	
	LD50 Oral Rat: 1,515 mg/kg	
Acute inhalation toxicity	: LC50 Mouse: > 1.21 mg/l	
2-butoxyethanol: Acute oral toxicity	: LD50 Oral Rat: 880 mg/kg	

SAFETY DATA SHEET

Version 2.1	Revision Date 05/12/2020	Print Date 06/01/2020
Acute dermal toxicity	: LD50 Dermal Rabbit: 1,060 mg/kg	
ethanol:		
Acute oral toxicity	: LD50 Oral Rat: 7,060 mg/kg	
Acute inhalation toxicity	: LC50 Rat: 124.7 mg/l Exposure time: 4 h Test atmosphere: vapour	
Skin corrosion/irritation		
Product:		
Remarks: Irritating to skin.		
Serious eye damage/eye irritatio	on	
Product:		
Remarks: May cause irrevers	sible eye damage.	
Respiratory or skin sensitisatio	n	
No data available		
Germ cell mutagenicity		
No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		
STOT - single exposure		
No data available		
STOT - repeated exposure		
No data available		
Aspiration toxicity		
No data available		
Further information		
Product:		

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Version 2.1 Revision Date 05/12/2020 Print Date 06/01/2020 Ecotoxicity No data available Persistence and degradability No data available **Bioaccumulative potential** Product: Partition coefficient: n-: Remarks: No data available octanol/water Components: propan-2-ol : Partition coefficient: n-: log Pow: 0.05 octanol/water butane : Partition coefficient: n-: Pow: 2.89 octanol/water 2-aminoethanol : Partition coefficient: n-: log Pow: -1.31 octanol/water ethanol: Partition coefficient: n-: Remarks: No data available octanol/water Mobility in soil No data available Other adverse effects No data available **Product:** 40 CFR Protection of Environment; Part 82 Protection of Regulation Stratospheric Ozone - CAA Section 602 Class I **Substances** This product neither contains, nor was manufactured Remarks with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). Additional ecological : No data available information

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container.
Contaminated packaging	Dispose of in accordance with local regulations.Empty remaining contents.Dispose of as unused product.

Version 2.1

Revision Date 05/12/2020

Print Date 06/01/2020

%

Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	:	Flammable (gases, aerosols, liquids, or solids) Gases under pressure Skin corrosion or irritation Serious eye damage or eye irritation	
SARA 302	:	No chemicals in this material are subject to the reportir requirements of SARA Title III, Section 302.	ıg
SARA 313	:	The following components are subject to reporting level established by SARA Title III, Section 313: 2-butoxyethanol 111-76-2	els 4.5 °

Version 2.1

Revision Date 05/12/2020

Print Date 06/01/2020

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

DSLAll components of this product are on the Canadian DSLTSCAOn TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Version 2.1

Revision Date 05/12/2020

Print Date 06/01/2020

Further information

NFPA:

HEALTH	3
FLAMMABILITY	3
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme


HMIS III:

HEALTH	3
FLAMMABILITY	3
PHYSICAL HAZARD	3

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic



Version 2.1

Revision Date 05/12/2020

Print Date 06/01/2020

Version:	2.1
Revision Date:	05/12/2020
Print Date:	06/01/2020

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.