




# SAFETY DATA SHEET

7/7/2025: File reviewed, more current MSDS/SDS not available. CAS

## 1. Identification

Product identifier	Carb & Choke Cleaner
Other means of identification	
Product Code	No. 03077 (Item# 1003337)
Recommended use	Carburetor cleaner
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufactured or sold by:	
Company name	CRC Industries, Inc.
Address	885 Louis Dr. Warminster, PA 18974 US
Telephone	
General Information	215-674-4300
Technical Assistance	800-521-3168
Customer Service	800-272-4620
24-Hour Emergency	800-424-9300 (US)
(CHEMTREC)	703-527-3887 (International)
Website	www.crcindustries.com

## 2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	
Label elements		

Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

Precautionary statement  
Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Wear eye protection/face protection. Wear protective gloves. Avoid release to the environment.

<b>Response</b>	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Collect spillage.
<b>Storage</b>	Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
acetone		67-64-1	80 - 90
carbon dioxide		124-38-9	5 - 10
n-heptane		142-82-5	3 - 5
3-methylhexane		589-34-4	1 - 3
2-methylhexane		591-76-4	< 1
3-ethylpentane		617-78-7	< 0.3
3,3-dimethylpentane		562-49-2	< 0.2

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire-fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
<b>General fire hazards</b>	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

### Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

## 7. Handling and storage

### Precautions for safe handling

Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

### Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3 5000 ppm
n-heptane (CAS 142-82-5)	PEL	2000 mg/m3 500 ppm

#### US. ACGIH Threshold Limit Values

Components	Type	Value
2-methylhexane (CAS 591-76-4)	STEL	500 ppm
3,3-dimethylpentane (CAS 562-49-2)	TWA	400 ppm
	STEL	500 ppm
3-ethylpentane (CAS 617-78-7)	TWA	400 ppm
	STEL	500 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
3-methylhexane (CAS 589-34-4)	TWA	400 ppm
	STEL	500 ppm
acetone (CAS 67-64-1)	TWA	400 ppm
	STEL	500 ppm
carbon dioxide (CAS 124-38-9)	TWA	250 ppm
	STEL	30000 ppm
n-heptane (CAS 142-82-5)	TWA	5000 ppm
	STEL	500 ppm
	TWA	400 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
acetone (CAS 67-64-1)	TWA	590 mg/m3
		250 ppm
carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3
		30000 ppm
n-heptane (CAS 142-82-5)	TWA	9000 mg/m3
		5000 ppm
		1800 mg/m3
	Ceiling	440 ppm
		350 mg/m3
	TWA	85 ppm

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Wear protective gloves such as: Nitrile. Polyvinyl alcohol (PVA). Viton/butyl.

**Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance****Physical state**

Liquid.

**Form**

Aerosol.

**Color**

Colorless.

**Odor**

Solvent.

**Odor threshold**

Not available.

<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	-138.5 °F (-94.7 °C) estimated
<b>Initial boiling point and boiling range</b>	132.9 °F (56.1 °C) estimated
<b>Flash point</b>	< 0 °F (< -17.8 °C) Tag Closed Cup
<b>Evaporation rate</b>	Fast.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	1.1 % estimated
<b>Flammability limit - upper (%)</b>	12.8 % estimated
<b>Vapor pressure</b>	5061 hPa estimated
<b>Vapor density</b>	> 2 (air = 1)
<b>Relative density</b>	0.84 estimated
<b>Solubility (water)</b>	Slightly soluble.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	539.6 °F (282 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity (kinematic)</b>	Not available.
<b>Percent volatile</b>	91.4 % estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Heat, flames and sparks. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents. Strong acids. Strong bases. Aldehydes. Alkalies. Amines. Ammonia. Halogens. Peroxides.
<b>Hazardous decomposition products</b>	Carbon oxides.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
---	--

### Information on toxicological effects

<b>Acute toxicity</b>	May be fatal if swallowed and enters airways.
-----------------------	---

Components	Species	Test Results
3-methylhexane (CAS 589-34-4)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg

Components	Species	Test Results
<b>Oral</b>		
LD50	Rat	> 2000 mg/kg
acetone (CAS 67-64-1)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	20000 mg/kg
<b>Oral</b>		
LD50	Rat	5800 mg/kg
n-heptane (CAS 142-82-5)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	3000 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
Not listed.	
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	
Not regulated.	
<b>US. National Toxicology Program (NTP) Report on Carcinogens</b>	
Not listed.	
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.
<b>Chronic effects</b>	Prolonged inhalation may be harmful.

## 12. Ecological information

Ecotoxicity		Toxic to aquatic life with long lasting effects.	
Components		Species	Test Results
acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
n-heptane (CAS 142-82-5)			
Aquatic			
Acute			
Crustacea	EC50	Water flea (Daphnia magna)	1.5 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	2.1 - 2.98 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

<b>Persistence and degradability</b>	No data is available on the degradability of this product.
--------------------------------------	--

## Bioaccumulative potential

### Partition coefficient n-octanol / water (log Kow)

acetone	-0.24
n-heptane	4.66

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

---

## 13. Disposal considerations

<b>Disposal of waste from residues / unused products</b>	This material and its container must be disposed of as hazardous waste. Consult authorities before disposal. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	D001: Waste Flammable material with a flash point <140 F F003: Waste Non-halogenated Solvent - Spent Non-halogenated Solvent
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## 14. Transport information

### DOT

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	N82
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	304
<b>Packaging bulk</b>	None

### IATA

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>ERG Code</b>	10L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.

### IMDG

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	F-D, S-U
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.



## 15. Regulatory information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

#### US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not listed.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

3,3-dimethylpentane (CAS 562-49-2) Listed.

acetone (CAS 67-64-1) Listed.

#### CERCLA Hazardous Substances: Reportable quantity

3,3-dimethylpentane (CAS 562-49-2) 100 LBS

acetone (CAS 67-64-1) 5000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

#### Safe Drinking Water Act (SDWA)

Not regulated.

#### Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

acetone (CAS 67-64-1) 6532

#### Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

acetone (CAS 67-64-1) 35 %WV

#### DEA Exempt Chemical Mixtures Code Number

acetone (CAS 67-64-1) 6532

#### FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

acetone (CAS 67-64-1) Low priority

#### Food and Drug Administration (FDA)

Not regulated.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes

Hazard categories Delayed Hazard - No

Fire Hazard - Yes

Pressure Hazard - Yes

Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

### US state regulations

#### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

acetone (CAS 67-64-1)

#### US. New Jersey Worker and Community Right-to-Know Act

3-methylhexane (CAS 589-34-4)

acetone (CAS 67-64-1)

carbon dioxide (CAS 124-38-9)

n-heptane (CAS 142-82-5)

#### US. Massachusetts RTK - Substance List

2-methylhexane (CAS 591-76-4)

3-methylhexane (CAS 589-34-4)

acetone (CAS 67-64-1)

carbon dioxide (CAS 124-38-9)



n-heptane (CAS 142-82-5)

#### US. Pennsylvania Worker and Community Right-to-Know Law

3,3-dimethylpentane (CAS 562-49-2)

3-methylhexane (CAS 589-34-4)

acetone (CAS 67-64-1)

carbon dioxide (CAS 124-38-9)

n-heptane (CAS 142-82-5)

#### US. Rhode Island RTK

acetone (CAS 67-64-1)

carbon dioxide (CAS 124-38-9)

n-heptane (CAS 142-82-5)

#### US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

##### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

acetaldehyde (CAS 75-07-0)

Listed: April 1, 1988

benzene (CAS 71-43-2)

Listed: February 27, 1987

cumene (CAS 98-82-8)

Listed: April 6, 2010

ethylbenzene (CAS 100-41-4)

Listed: June 11, 2004

naphthalene (CAS 91-20-3)

Listed: April 19, 2002

##### US - California Proposition 65 - CRT: Listed date/Developmental toxin

benzene (CAS 71-43-2)

Listed: December 26, 1997

toluene (CAS 108-88-3)

Listed: January 1, 1991

##### US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

benzene (CAS 71-43-2)

Listed: December 26, 1997

#### Volatile organic compounds (VOC) regulations

##### EPA

**VOC content (40 CFR 51.100(s))** 9.2 %

**Consumer products (40 CFR 59, Subpt. C)** Compliant

##### State

**Consumer products** This product is regulated as a Carburetor Cleaner. This product is compliant for use in all 50 states.

**VOC content (CA)** 9.2 %

**VOC content (OTC)** 9.2 %

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 02-28-2014

**Revision date** 10-04-2017  
**Prepared by** Allison Yoon  
**Version #** 04  
**Further information** CRC # 920B/1002914  
**HMIS® ratings** Health: 2  
Flammability: 4  
Physical hazard: 0  
Personal protection: B  
**NFPA ratings** Health: 2  
Flammability: 4  
Instability: 0

**NFPA ratings**



**Disclaimer**

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

**Revision Information**

Product and Company Identification: Product Codes  
Transport Information: Proper Shipping Name/Packing Group  
Other information, including date of preparation or last revision: Further information  
GHS: Classification