HOLOGIC

MATERIAL SAFETY DATA SHEET

4/7/2024: File reviewed, more current MSDS/SDS not available. CAS

1. Product and Company lo	dentification
Material name	Carbon Dioxide (CO2) Cartridge
Version #	01
Issue date	04-11-2013
Revision date	-
Supersedes date	-
CAS #	N/A
Manufacturer information	
Supplier	Hologic Inc
	250 Campus Drive
	Marlborough, Massachusetts 01752
	USA
Email:	sds@hologic.com
Telephone:	(800) 442-9892
Emergency telephone:	(3E): 1-866-519-4752 CODE: 333605
Manufacturer	Liss Patrongyártó, Töltő és Forgalmazó Kft
	(Liss Ltd.) Carl von Linde út 1.
	H-9653 Répcelak
Telephone:	+06 (95) 588 100
Fax:	+06 (95) 588 114
Emergency telephone:	+36 1 476 6464
2. Hazards Identification	
Physical state	Gas.
Appearance	Colorless gas.
Emergency overview	CAUTION
	Contents under pressure. Gas reduces oxygen available for breathing. Contact with liquefied gas
	might cause frostbites, in some cases with tissue damage.
OSHA regulatory status	This product is hazardous according to OSHA 29 CFR 1910.1200.
Potential health effects Routes of exposure	Inhelation. Okin contact. Eve contact
•	Inhalation. Skin contact. Eye contact.
Eyes Skin	Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("cold burn"). Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("cold burn").
Inhalation	Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations that reduce oxygen
	below safe breathing levels.
Ingestion	This material is a gas under normal atmospheric conditions and ingestion is unlikely.
Target organs	Heart. Respiratory system. Central nervous system. Eye. Skin.
Target organs	
Chronic effects	May affect the nervous system and cause headache, nausea, vomiting, and narcosis.
	This material is not expected to be harmful to aquatic life. Emissions of gas affecting global warming.

1. Product and Company Identification

Carbon Dioxide (CO2) Cartridge 913162 RD-00866 Rev. 002 Revision date: - Issue date: 04-11-2013

percent by volume.

Carbon dioxide

Composition comments

>99

124-38-9

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

4. First Aid Measures

First aid procedures	
Eye contact	GAS: Flush thoroughly with water for at least 15 minutes. Make sure to remove any contact lenses from the eyes before rinsing. LIQUEFIED GAS: If frostbite occurs, immediately flush eyes with plenty of warm water (not exceeding 105°F/41°C) for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention if irritation develops or persists.
Skin contact	GAS: Remove contaminated clothing immediately and wash skin with soap and water. LIQUEFIED GAS: If frostbite occurs, immerse involved area in warm water (between 100 F/38 C and 110 F/43 C, not exceeding 112 F/44 C). Keep immersed for 20 to 40 minutes. Seek medical assistance.
Inhalation	Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory tract irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation. Get medical attention.
Ingestion	Seek medical advice.
General advice	First aid personnel must be aware of own risk during rescue.
5. Fire Fighting Measures	
Flammable properties	The product is not flammable.
Extinguishing media	
Suitable extinguishing media	Dry chemical. Carbon Dioxide. Halon.
	Large Fires: Foam, water spray or fog. Use fire-extinguishing media appropriate for surrounding materials.
Protection of firefighters	
Specific hazards arising from the chemical	The product itself does not burn. Closed containers can burst violently when heated, due to excess pressure build-up.
Protective equipment and precautions for firefighters	Self-contained breathing apparatus, operated in positive pressure mode and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
Fire fighting equipment/instructions	Evacuate area. Stop flow of gas. Remove pressurized gas cylinders from the immediate vicinity. Cool material exposed to heat with water spray and remove it if no risk is involved.
Hazardous combustion products	Carbon oxides. Nitrogen oxides.
6. Accidental Release Mea	sures
Personal precautions	Avoid inhalation and contact with skin and eyes. Ensure adequate ventilation. Wear appropriate personal protective equipment (See Section 8). Stay upwind. Ventilate closed spaces before entering them.
Environmental precautions	Avoid release to the environment.

Methods for cleaning up Ventilate well, stop flow of gas or liquid if possible.

7. Handling and Storage

Handling
 Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Keep container closed. Use only with adequate ventilation. Contents under pressure. Do not puncture. Close valve after each use and when empty. Do not attempt to refill spent cartridges. Wear appropriate personal protective equipment. Wash thoroughly after handling.
 Storage
 Keep container tightly closed. Store in a cool, dry place with adequate ventilation. Keep away from

Keep container tightly closed. Store in a cool, dry place with adequate ventilation. Keep away from incompatible materials, open flames, and high temperatures. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
121 00 0)	TWA	5000 ppm	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Carbon dioxide (CAS 124-38-9) PEL 5000 ppm 9000 mg/m3 5000 ppm Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) Value Components Type Value Carbon dioxide (CAS 124-38-9) STEL 54000 mg/m3 5000 ppm Carbon dioxide (CAS 124-38-9) TWA 9000 ppm Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Components Type Value Carbon dioxide (CAS 124-38-9) TWA 5000 ppm Cardon dioxide (CAS 124-38-9) TWA 5000 ppm TWA	Components	Туре	Value
Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) Components Type Value Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 9000 mg/m3 Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) TWA Cambon dioxide (CAS STEL 15000 ppm Carbon dioxide (CAS STEL 15000 ppm Cardon dioxide (CAS STEL 15000 ppm Cardon dioxide (CAS STEL 15000 ppm Cardon dioxide (CAS STEL 30000 ppm Cardon dioxide (CAS STEL 27000 mg/m3 124-38-9) TWA 5000 ppm Cardon dioxide (CAS STEL 27000 mg/m3 124-38-9) TWA 5000		PEL	C C
Components Type Value Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) 30000 ppm Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296(97, as amended) Components Type Value Carbon dioxide (CAS STEL 15000 ppm Carbon dioxide (CAS STEL 15000 ppm Carbon dioxide (CAS STEL 15000 ppm Carbon dioxide (CAS STEL 0000 ppm Carbon dioxide (CAS STEL 0000 ppm Carbon dioxide (CAS STEL 0000 ppm Carbon dioxide (CAS STEL 30000 ppm 124-38-9) TWA 5000 ppm Carbon dioxide (CAS STEL 30000 ppm 124-38-9) TWA 5000 ppm Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 5000 ppm Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 5000 ppm TWA 300000 ppm 500			
Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 30000 ppm Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Type Value Components Type Value Carbon dioxide (CAS STEL 15000 ppm 124-38-9) TWA 5000 ppm Carbon dioxide (CAS STEL 15000 ppm Carbon dioxide (CAS STEL 30000 ppm Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 9000 ppm TWA 9000 ppm 30000 ppm Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 9000 ppm WA 9000 ppm 30000 ppm Mexico. Occupational Exposure Limit Values Components Type Carbon dioxide (CAS STEL 27000 mg/m3	Canada. Alberta OELs (Occu	upational Health & Safety Code, Sch	edule 1, Table 2)
124-38-9) 30000 ppm 9000 mg/m3 5000 ppm Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Components Type Carbon dioxide (CAS STEL 24-38-9) TWA S0000 ppm </td <td>Components</td> <td>Туре</td> <td>Value</td>	Components	Туре	Value
TWA 30000 ppm 9000 mg/m3 5000 ppm Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended/ Components Type Carbon dioxide (CAS STEL 124-38-9) TWA Candaa. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Carbon dioxide (CAS STEL 124-38-9) TWA Carbon dioxide (CAS STEL 2000 ppm Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Carbon dioxide (CAS STEL 2124-38-9) TWA Carbon dioxide (CAS STEL Carbon dioxide (CAS STEL Carbon dioxide (CAS STEL 24-38-9) TWA Soudo ppm TWA Carbon dioxide (CAS STEL 24-38-9) SOU00 ppm TWA 9000 mg/m3 124-38-9) STEL 24-38-9) SOU00 ppm TWA 9000 mg/m3 124-38-9) STEL 24-38-9) STEL 24-38-9) STEL 24-38-9) STEL 24-38-9) STEL 124-38-9) STEL 124-38-9)		STEL	54000 mg/m3
5000 ppm Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296(97, as amended) Components Type Value Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Carbon dioxide (CAS STEL 30000 ppm Carbon dioxide (CAS STEL 54000 mg/m3 Components Type Value Components Type </td <td>,</td> <td></td> <td></td>	,		
Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Components Type Value Carbon dioxide (CAS STEL 15000 ppm 124-38-9) TWA 5000 ppm Canda. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Value Carbon dioxide (CAS STEL 30000 ppm 124-38-9) TWA 5000 ppm Carbon dioxide (CAS STEL 30000 ppm Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 5000 ppm Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 5000 ppm Macco. Occupational Exposure Limit Values Zordon mg/m3 5000 ppm Carbon dioxide (CAS STEL 27000 mg/m3 5000 ppm 124-38-9) Type Value Value Value Value Value Value Value VAL		TWA	
Safety Regulation 296/97, as amended) Type Value Components STEL 15000 ppm 124-38-9) TWA 5000 ppm Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Image: Control of Exposure to Biological or Chemical Agents) Components Type Value Carbon dioxide (CAS STEL 30000 ppm 124-38-9) TWA 5000 ppm Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) Components Components Type Value Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 9000 ppm TWA 9000 ppm 10000 ppm TWA 9000 ppm 10000 ppm 124-38-9) TWA 9000 ppm Mexico. Occupational Exposure Limit Values Components Type Components Type Value Carbon dioxide (CAS STEL 27000 mg/m3 124-38-9) TWA 9000 ppm TWA 9000 ppm 15000 ppm 124-38-9) TWA 9000 mg/m3 <			
Carbon dioxide (CAS STEL 15000 ppm 124-38-9) TWA 5000 ppm Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Carbon dioxide (CAS STEL 30000 ppm 124-38-9) TWA 5000 ppm Carbon dioxide (CAS STEL 30000 ppm Carbon dioxide (CAS STEL 30000 ppm Carbon dioxide (CAS STEL 54000 mg/m3 Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 5000 ppm Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 9000 mg/m3 124-38-9) TWA 9000 ppm Mexico. Occupational Exposure Limit Values 27000 mg/m3 Carbon dioxide (CAS STEL 27000 mg/m3 124-38-9) TWA 9000 mg/m3			for Chemical Substances, Occupational Health and
124-38-9) TWA 5000 ppm Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Carbon dioxide (CAS STEL 30000 ppm 124-38-9) TWA 5000 ppm Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) Components Type Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 5000 ppm TWA 9000 mg/m3 124-38-9) TWA 9000 mg/m3 5000 ppm 124-38-9) TWA 9000 mg/m3 Mexico. Occupational Exposure Limit Values TWA 9000 mg/m3 Carbon dioxide (CAS STEL 27000 mg/m3 124-38-9) TWA 9000 ppm Mexico. Occupational Exposure Limit Values TWA 9000 mg/m3 Carbon dioxide (CAS STEL 27000 mg/m3 124-38-9) TWA 9000 ppm TWA 9000 ppm 15000 ppm Inserving controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventili	Components	Туре	Value
TWA 5000 ppm Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Carbon dioxide (CAS STEL 30000 ppm 124-38-9) TWA 5000 ppm Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) Components Type Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 5000 ppm Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 30000 ppm Maxico. Occupational Exposure Limit Values TWA 9000 mg/m3 Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 9000 ppm Mexico. Occupational Exposure Limit Values TWA 9000 ppm Carbon dioxide (CAS STEL 27000 mg/m3 124-38-9) TWA 9000 ppm Mexico. Occupational Exposure Limit Values TWA 9000 ppm Inserving controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilatio or other engineering controls on aniatian airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels below recomm		STEL	15000 ppm
Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Carbon dioxide (CAS STEL 30000 ppm 124-38-9) TWA 5000 ppm Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) Components Type Value Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) 30000 ppm 124-38-9) TWA 30000 ppm 10000 ppm TWA 9000 mg/m3 5000 ppm Mexico. Occupational Exposure Limit Values 27000 mg/m3 5000 ppm Carbon dioxide (CAS STEL 27000 mg/m3 15000 ppm 124-38-9) Type Value 15000 ppm Carbon dioxide (CAS STEL 27000 mg/m3 5000 ppm I24-38-9) TWA 9000 mg/m3 5000 ppm ineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or there engineering controls to an acceptable level. Soudo ppm sonal protective equipment Eye / face protection Wear safety glasses with side shields (or gogg	124-38-9)	710/0	5000 nm
Components Type Value Carbon dioxide (CAS 124-38-9) STEL 30000 ppm Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) Components Type Carbon dioxide (CAS Carbon dioxide (CAS STEL 54000 mg/m3 Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) TWA 90000 mg/m3 Maxico. Occupational Exposure Limit Values TWA 90000 ppm Components Type Value Carbon dioxide (CAS STEL 27000 mg/m3 124-38-9) TWA 9000 ppm Mexico. Occupational Exposure Limit Values 27000 mg/m3 Components Type Value Carbon dioxide (CAS STEL 27000 mg/m3 124-38-9) TWA 9000 ppm TWA 9000 mg/m3 5000 ppm TWA	Canada Ontaria OELa (Car		
Carbon dioxide (CAS STEL 30000 ppm 124-38-9) TWA 5000 ppm Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) Components Type Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) 30000 ppm TWA 9000 mg/m3 124-38-9) 30000 ppm TWA 9000 mg/m3 5000 ppm 5000 ppm Mexico. Occupational Exposure Limit Values Components Corbon dioxide (CAS STEL 27000 mg/m3 124-38-9) Type Value Carbon dioxide (CAS STEL 27000 mg/m3 124-38-9) TWA 9000 ppm Maxico. Occupational Exposure Limit Values 27000 mg/m3 Components Type Value Carbon dioxide (CAS STEL 27000 mg/m3 124-38-9) 15000 ppm TWA mineering controls Good general ventiliation (typically 10 air changes probury should be used. Ventiliation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventiliatio or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been establ			emical Agents)
124-38-9) TWA 5000 ppm Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) Components Type Value Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) 30000 ppm TWA 9000 mg/m3 5000 ppm STEL Components Type VA 9000 mg/m3 5000 ppm STEL Components Type Carbon dioxide (CAS STEL Carbon dioxide (CAS STEL Carbon dioxide (CAS STEL 2arbon dioxide (CAS STEL 2bold ppm TWA 9000 mg/m3 5000 ppm Ineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been estab		Туре	Value
TWA 5000 ppm Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) Components Type Carbon dioxide (CAS STEL 124-38-9) 30000 ppm TWA 9000 mg/m3 124-38-9) TWA Walue 30000 ppm Mexico. Occupational Exposure Limit Values Value Carbon dioxide (CAS STEL Carbon dioxide (CAS STEL Carbon dioxide (CAS STEL 24-38-9) Type Value Value Carbon dioxide (CAS STEL 124-38-9) TWA 124-38-9) STEL 124-38-9) TWA 124-38-9) Solo0 ppm Inneering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or ther engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintai nairborne levels to an acceptable level. </td <td></td> <td>STEL</td> <td>30000 ppm</td>		STEL	30000 ppm
Components Type Value Carbon dioxide (CAS 124-38-9) STEL 54000 mg/m3 30000 ppm TWA 9000 mg/m3 5000 ppm Mexico. Occupational Exposure Limit Values TWA Carbon dioxide (CAS Carbon dioxide (CAS 124-38-9) Type Value Carbon dioxide (CAS 124-38-9) STEL 27000 mg/m3 5000 ppm Mexico. Occupational Exposure Limit Values TVP Value Carbon dioxide (CAS 124-38-9) STEL 27000 mg/m3 5000 ppm ineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilatio or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels to an acceptable level. sonal protective equipment Eye / face protection Wear safety glasses with side shields (or goggles). Skin protection Wear safety glasses with side shields (or goggles). Wear appropriate clothing to prevent skin contamination or freezing. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators a	124-30-9)	TWA	5000 ppm
Carbon dioxide (CAS STEL 54000 mg/m3 124-38-9) 30000 ppm TWA 9000 mg/m3 5000 ppm 5000 ppm Mexico. Occupational Exposure Limit Values 7000 mg/m3 Carbon dioxide (CAS STEL Carbon dioxide (CAS STEL 2 arbon dioxide (CAS Stell 2 arbon dioxide (CAS Stell 2 arbon dioxide (CAS Stell 3 arbon dioxide (CAS	Canada. Quebec OELs. (Min	istry of Labor - Regulation Respecti	ng the Quality of the Work Environment)
124-38-9) 30000 ppm TWA 9000 mg/m3 5000 ppm Mexico. Occupational Exposure Limit Values Components Type Carbon dioxide (CAS STEL 124-38-9) 15000 ppm TWA 9000 mg/m3 5000 ppm Sonal protective equipment Eye / face protection Gear appropriate clothing to prevent skin contamination or freezing. Skin protection Wear safety glasses with side shields (or goggles). Skin protection Wear appropriate clothing to prevent skin contamination or freezing. Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134. Respirator type: Wear air supplied respiratory protection. <td>Components</td> <td>Туре</td> <td>Value</td>	Components	Туре	Value
TWA 30000 ppm 9000 mg/m3 5000 ppm Mexico. Occupational Exposure Limit Values Components Type Value Carbon dioxide (CAS 124-38-9) STEL 27000 mg/m3 5000 ppm ineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilatio or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels to an acceptable level. Sonal protective equipment Eye / face protection Wear safety glasses with side shields (or goggles). Skin protection Wear appropriate clothing to prevent skin contamination or freezing. Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134. Respirator type: Wear air supplied respiratory protection. General hygiene Do not eat, drink or smoke when using the product. Observe good industrial hygiene practices.		STEL	54000 mg/m3
TWA 9000 mg/m3 5000 ppm Mexico. Occupational Exposure Limit Values Components Type Value Carbon dioxide (CAS 124-38-9) STEL 27000 mg/m3 5000 ppm ineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilatio or other engineering controls were applicable, maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels to an acceptable level. Sonal protective equipment Eye / face protection Wear safety glasses with side shields (or goggles). Skin protection Wear appropriate clothing to prevent skin contamination or freezing. Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134. Respirator type: Wear air supplied respiratory protection. General hygiene Do not eat, drink or smoke when using the product. Observe good industrial hygiene practices.	124-30-9)		30000 ppm
Mexico. Occupational Exposure Limit Values Components Type Value Carbon dioxide (CAS 124-38-9) STEL 27000 mg/m3 TWA 9000 mg/m3 5000 ppm ineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilatio or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels to an acceptable level. Sonal protective equipment Eye / face protection Wear safety glasses with side shields (or goggles). Skin protection Wear appropriate clothing to prevent skin contamination or freezing. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134. Respirator type: Wear air supplied respiratory protection. General hygiene Do not eat, drink or smoke when using the product. Observe good industrial hygiene practices.		TWA	9000 mg/m3
Components Type Value Carbon dioxide (CAS STEL 27000 mg/m3 124-38-9) 15000 ppm TWA 9000 mg/m3 5000 ppm TWA ineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilatio or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels to an acceptable level. sonal protective equipment Eye / face protection Eye / face protection Wear safety glasses with side shields (or goggles). Skin protection Wear appropriate clothing to prevent skin contamination or freezing. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134. Respirator type: Wear air supplied respiratory protection. General hygiene Do not eat, drink or smoke when using the product. Observe good industrial hygiene practices.			5000 ppm
Carbon dioxide (CAS STEL 27000 mg/m3 124-38-9) 15000 ppm TWA 9000 mg/m3 5000 ppm Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilatio or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels to an acceptable level. sonal protective equipment Eye / face protection Skin protection Wear safety glasses with side shields (or goggles). Skin protection Wear appropriate clothing to prevent skin contamination or freezing. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134. Respirator type: Wear air supplied respiratory protection. General hygiene Do not eat, drink or smoke when using the product. Observe good industrial hygiene practices.			
124-38-9) TWA 15000 ppm 9000 mg/m3 5000 ppm ineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilatio or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels to an acceptable level. sonal protective equipment Eye / face protection Eye / face protection Wear safety glasses with side shields (or goggles). Skin protection Wear appropriate clothing to prevent skin contamination or freezing. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134. Respirator type: Wear air supplied respiratory protection. General hygiene Do not eat, drink or smoke when using the product. Observe good industrial hygiene practices.	Mexico. Occupational Expos	sure Limit Values	
TWA15000 ppm 9000 mg/m3 5000 ppmineering controlsGood general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilatio or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels to an acceptable level.sonal protective equipment Eye / face protectionWear safety glasses with side shields (or goggles).Skin protectionWear appropriate clothing to prevent skin contamination or freezing.Respiratory protectionIf engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134. Respirator type: Wear air supplied respiratory protection.General hygieneDo not eat, drink or smoke when using the product. Observe good industrial hygiene practices.			Value
5000 pmineering controlsGood general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilatio or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels to an acceptable level.sonal protective equipment Eye / face protectionWear safety glasses with side shields (or goggles).Skin protectionWear safety glasses with side shields (or goggles).Respiratory protectionIf engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134. Respirator type: Wear air supplied respiratory protection.General hygieneDo not eat, drink or smoke when using the product. Observe good industrial hygiene practices.	Components Carbon dioxide (CAS	Туре	
ineering controlsGood general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilatio or other engineering controls to maintain airborne levels below recommended exposure limits. I exposure limits have not been established, maintain airborne levels to an acceptable level.sonal protective equipment Eye / face protectionWear safety glasses with side shields (or goggles).Skin protectionWear appropriate clothing to prevent skin contamination or freezing.Respiratory protectionIf engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134. Respirator type: Wear air supplied respiratory protection.General hygieneDo not eat, drink or smoke when using the product. Observe good industrial hygiene practices.	Components Carbon dioxide (CAS	Type STEL	27000 mg/m3 15000 ppm
sonal protective equipmentWear safety glasses with side shields (or goggles).Eye / face protectionWear safety glasses with side shields (or goggles).Skin protectionWear appropriate clothing to prevent skin contamination or freezing.Respiratory protectionIf engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134. Respirator type: Wear air supplied respiratory protection.General hygieneDo not eat, drink or smoke when using the product. Observe good industrial hygiene practices.	Components Carbon dioxide (CAS	Type STEL	27000 mg/m3 15000 ppm 9000 mg/m3
Eye / face protectionWear safety glasses with side shields (or goggles).Skin protectionWear appropriate clothing to prevent skin contamination or freezing.Respiratory protectionIf engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134. Respirator type: Wear air supplied respiratory protection.General hygieneDo not eat, drink or smoke when using the product. Observe good industrial hygiene practices.	Components Carbon dioxide (CAS 124-38-9)	Type STEL TWA Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main	27000 mg/m3 15000 ppm 9000 mg/m3 5000 ppm 9 air changes per hour) should be used. Ventilation rates pplicable, use process enclosures, local exhaust ventilatio tain airborne levels below recommended exposure limits. I
Skin protectionWear appropriate clothing to prevent skin contamination or freezing.Respiratory protectionIf engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134. Respirator type: Wear air supplied respiratory protection.General hygieneDo not eat, drink or smoke when using the product. Observe good industrial hygiene practices.	Components Carbon dioxide (CAS 124-38-9) ineering controls	Type STEL TWA Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main	27000 mg/m3 15000 ppm 9000 mg/m3 5000 ppm 9 air changes per hour) should be used. Ventilation rates pplicable, use process enclosures, local exhaust ventilatio tain airborne levels below recommended exposure limits. I
Respiratory protectionIf engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134. Respirator type: Wear air supplied respiratory protection.General hygieneDo not eat, drink or smoke when using the product. Observe good industrial hygiene practices.	Components Carbon dioxide (CAS 124-38-9) ineering controls sonal protective equipment	Type STEL TWA Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been establi	27000 mg/m3 15000 ppm 9000 mg/m3 5000 ppm 9 air changes per hour) should be used. Ventilation rates pplicable, use process enclosures, local exhaust ventilatio tain airborne levels below recommended exposure limits. I ished, maintain airborne levels to an acceptable level.
	Components Carbon dioxide (CAS 124-38-9) ineering controls sonal protective equipment Eye / face protection	Type STEL TWA Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been established be watched to be an established be and the shield shiel	27000 mg/m3 15000 ppm 9000 mg/m3 5000 ppm 9 air changes per hour) should be used. Ventilation rates pplicable, use process enclosures, local exhaust ventilatio tain airborne levels below recommended exposure limits. I ished, maintain airborne levels to an acceptable level. s (or goggles).
	Components Carbon dioxide (CAS 124-38-9) ineering controls sonal protective equipment Eye / face protection Skin protection	Type STEL TWA Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been establis Wear safety glasses with side shields Wear appropriate clothing to prevent If engineering controls do not maintai limits (where applicable) or to an acce been established), an approved respi respirators are used, a program should	27000 mg/m3 15000 ppm 9000 mg/m3 5000 ppm 9 air changes per hour) should be used. Ventilation rates pplicable, use process enclosures, local exhaust ventilatio tain airborne levels below recommended exposure limits. I ished, maintain airborne levels to an acceptable level. s (or goggles). skin contamination or freezing. in airborne concentrations below recommended exposure eptable level (in countries where exposure limits have not irator must be worn. In the United States of America, if Ild be instituted to assure compliance with OSHA 29 CFR

Appearance Colorless gas.

Form	Compressed gas.
Color	Colorless
Odor	Odorless.
Odor threshold	Not available.
рН	Not available.
Vapor pressure	43700 mm Hg (21.1°C / 70°F)
Vapor density	1.5
Boiling point	-109 °F (-78.33 °C)
Melting point/Freezing point	Not available.
Solubility (water)	Soluble in water.
Specific gravity	Not available.
Flash point	Not available.
Flammability limits in air, upper, % by volume	Not available.
Flammability limits in air, lower, % by volume	Not available.
Auto-ignition temperature	Not available.
Molecular weight	44.01 g/mol
Molecular formula	C-02

10. Chemical Stability & Reactivity Information

Chemical stability	This product is stable under expected conditions of use.
Conditions to avoid	Heat and direct sunlight.
Incompatible materials	Metals. Acids. Oxidizers.
Hazardous decomposition products	Temperatures above 1700° C may cause decomposition and the release of oxygen and highly toxic carbon monoxide.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

11. Toxicological Information

Sensitization	Not a skin sensitizer.
Acute effects	Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations that reduce oxygen below safe breathing levels. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. Carbon dioxide when inhaled in elevated concentrations may act to produce mild narcotic effects, stimulation of the respiratory center, and asphyxiation depending on the concentration present and duration of exposure. Low concentrations (3-5%) cause increased respiration and headache. Concentrations at 8% or higher cause headache, nausea and vomiting which may lead to unconsciousness if not moved to open air or given oxygen promptly. At concentrations of 10% or higher, carbon dioxide causes rapid circulatoty insufficirncy leading to coma and death.
Local effects	Contact with compressed gas can cause damage (frostbite) due to rapid evaporative cooling.
Chronic effects	May cause central nervous system effects.
Carcinogenicity	No data recorded.
Mutagenicity	No data recorded.
Neurological effects	May cause drowsiness or dizziness.
Reproductive effects	No data available.

12. Ecological Information

Ecotoxicity	This material is not expected to be harmful to aquatic life. Emissions of gas affecting global warming.
Persistence and degradability	Not available.
Bioaccumulation / Accumulation	Not available.

Mobility in environmental
mediaThe product is a volatile substance, which may spread in the atmosphere.

13. Disposal Considerations

Waste codes	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal instructions	Dispose in accordance with all applicable regulations.
Waste from residues / unused products	Dispose in accordance with all local, State and Federal regulations.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport Information

DOT

501	
Basic shipping requirements	s:
UN number	UN2037
Proper shipping name	Receptacles, small, containing gas or gas cartridges
Hazard class	2.2
Subsidiary hazard class	5.1
Additional information:	
Special provisions	A14
Packaging exceptions	306
Packaging non bulk	304
Packaging bulk	None
DOT	
BULK	
Basic shipping requirements	S:
UN number	UN2037
Proper shipping name	Receptacles, small, containing gas or gas cartridges
Hazard class	2.2
Subsidiary hazard class	5.1
Additional information:	
Special provisions	A14
Packaging exceptions	306
Packaging non bulk	304
Packaging bulk	None
ΙΑΤΑ	
UN number	UN2037
UN proper shipping name	Receptacles, small, containing gas or gas cartridges
Transport hazard class(es)	2.2
Subsidiary class(es)	5.1
Labels required	2.2, 5.1
IMDG	
UN number	UN2037
UN proper shipping name	Receptacles, small, containing gas or gas cartridges
Transport hazard class(es)	2.2
Subsidiary class(es)	5.1
Labels required	2.2, 5.1
TDG	1010007
UN number	UN2037
Proper shipping name	Receptacles, small, containing gas or gas cartridges
Hazard class	2.2
Subsidiary hazard class	5.1 A14
Special provisions	2.2, 5.1
Labels required Packaging exceptions	306
Packaging exceptions Packaging non bulk	308
Packaging bulk	None
Fackaying bulk	

15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated. Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. CERCLA (Superfund) reportable quantity (lbs) (40 CFR 302.4) None Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - Yes Reactivity Hazard - No Section 302 extremely No hazardous substance (40 CFR 355, Appendix A) SARA 311/312 Hazardous No chemical Not controlled Drug Enforcement Administration (DEA) (21 CFR 1308.11-15) Food and Drug Administration Total food additive (FDA) Direct food additive GRAS food additive Canadian regulations This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS status Controlled WHMIS classification A - Compressed Gas

WHMIS labeling



Inventory status Country(s) or region On inventory (yes/no)* Inventory name Australia Australian Inventory of Chemical Substances (AICS) Yes Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No China Inventory of Existing Chemical Substances in China (IECSC) Yes European Inventory of Existing Commercial Chemical Yes Europe Substances (EINECS) Europe European List of Notified Chemical Substances (ELINCS) No Inventory of Existing and New Chemical Substances (ENCS) Japan Yes Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes Philippines Philippine Inventory of Chemicals and Chemical Substances Yes (PICCS) Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

State regulations

US - California Hazardous Substances (Director's): Listed substance

Carbon dioxide (CAS 124-38-9)

Listed.

US - California Proposition Not listed.	65 - Carcinogens & Reproduc	tive Toxicity (CRT): Listed substance	
US - New Jersey RTK - Sub	stances: Listed substance		
Carbon dioxide (CAS 124-38-9) Listed.		Listed.	
US. Massachusetts RTK - Substance List			
Carbon dioxide (CAS 124-38-9)		Listed.	
US. New Jersey Worker and	Community Right-to-Know A	Act	
Not regulated.			
US. Pennsylvania RTK - Haz			
Carbon dioxide (CAS 124	1-38-9)	Listed.	
Mexico regulations	This safety data sheet was prepared in accordance with the Official Mexican Standard (NOM-018-STPS-2000).		
16. Other Information			
HMIS® ratings	Health: 1 Flammability: 0 Physical hazard: 0		
NFPA ratings	Health: 1 Flammability: 0 Instability: 0		
Disclaimer	THE INFORMATION CONTAINED IN THIS DOCUMENT RELATES TO THIS SPECIFIC MATERIAL AND MAY NOT BE VALID IF THE MATERIAL IF USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OR HER OWN PARTICULAR USE.		