MATERIAL SAFETY DATA SHEET



The information and recommendations contained herein are based upon data believed to be correct, however, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained herein.

Section I		`							
Company Name					Product Name CARNA-WAX				
Midwest Floor Care, Inc. Address (Number, Street, City, State, and ZIP Code)					<u></u>				
1' O Box 30266					Emergency Telephone Number				
Lincoln, NF 68503					816-234-3000 Poison Conti Teluphoric Number for Information402-477 -2701				
Chemical Family Wax, petroleum distillate					Date Prepared 5/91 S. Lov				
	lazardous Ingr				I				
Hazardous Components (Specific Chemical Identity; Common				mon Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)	
Section III — I	Physical/Chem	ical Cha	aracteris	tics					
Boiling Point				300°F	Specific Gravity (H ₂ O = 1)		0.76		
Vapor Pressure (mm Hg.)				. Unkno	Melting Point		NA		
Vapor Density (AIR = 1)				Unknown	Evaporation Rate (Butyl Acetete = 1)		Unknown		
Solubility in Water	In	solub	le			 			
Appearance and C	Odor V	iscou	s, ye	llow, wa	xy, solve	nt odor			
Section IV —	Fire and Explo	sion H	azard Da	ata			·		
Frash Point (Mothod Used)					Flammable Lim	ls	LEL NA	UEL	
Extinguishing Moda Fram, CO2, dry chemical							— <u></u>		
Special Fire Fighti	ng Procedures			Use to c	ool conta	iners. Fir	ce fighting	pe <u>rs</u> onne	
	ear self								
Unusual Fire and	Explosion Hazard:					ks and flar			
		<u> </u>	0.1.0.7.0	<u>u,</u>	Trom Spar	KS GIIG TTG	110 .		
Section V —	Reactivity Dat	a							
Stability	Unstable	1	Conditions to Avoid						
	Stable		High temperatures, surfaces, electric arcs.						
	Materials to Avoid OX (d i ? (i) !	0		<u> </u>					
Hazardous Decor	пірэмов от Пуркос	ducts							
		On decomposition products including CO_CO2							
Hazardous Polymorization	May Occur		CCR KHIKKOS	2 IO WANG					
	Will Not Occur	χ		, <u>, , , , , , , , , , , , , , , , , , </u>				50	

The information and recommendations contained herein are based upon data believed to be correct, however, no guarantee or werrenny of any kind expressed or implied is made with respect to the information contained herein.

Section VI — I	lealth Hazard Data				
Flouto(s) of Entry:	Inhalation? X	Skin? X		Ingestion? X	
Health Hazards (Ac	ule and Chronic) Signs and Sympto	oms of Exposure		blurred vision.	
	rolonged contact				
Inhalati	· · · · · · · · · · · · · · · · · · ·	spitory irritati	· · · · · · · · · · · · · · · · · · ·		
				neumonitis which	can
	e fatal.				
Ingestio	n: Can cause gas	tro intestinal i	rritation, n	ausea, vomiting,	-
	iarrhea.				
Carcinogenicity: None kno	WID NTP?	IARC Monog	raphs?	OSHA Regulated?	
Medical Conditions				·	-
Generally Aggravati					
Emergency and Fir	is, allergic resp si Aid Procedures	onses			
Hyes: 1	lush with water 1	5 min. Get medi	cal attentio	n immediately.	
Skin: V	lash with soap and	water.			
<u>Inhalati</u>	on: If affected,	move to fresh a	iir. If breat	hing difficult,	
	<u>idminister oxygen.</u>			·	
lngestic	on: DO NOT induce	e vomiting. Cet	medical atte	ention.	*
			·		
			<u> </u>		·
					 {
Section VII	Precautions for Safe Hand	Hing and Hee			
Steps to Bu Taker	s in Case Material ts Retnased or S	Solled	1	C	
	Absorb on paper,			Dispose by Tiqui	
				runoff to hodies	
Wasin Disrosal M	huthool				
Dispuse	· in accordance wi	th federal, stat	e & local re	gulations.	
Procuutions to Br	Taken in Handling and Storing				
Avoid	sparks and open fl	ame. Use adequa	ite ventilati	on.	
Other Precaution	s				ut o
			e all nazara	precautions on da	
	when handling and — Control Measures	atsposing.			
Respiratory Prote	sction (Soucily Typu)	2011		<u> </u>	
Ventilation	Local Exhaust	OSII approved res	Special		
	Machine d Cook d	cient to maintai	Othur	<u></u>	·
M. aust Ct.	Relow		rotuction		
	ant as nitrile	Lyu i	Chemic	al goggles	
Preven	Coming or Equipment t prolonged conta	ct: boots & impo	rvious cloth	ing if necessary.	
Work/Hygiunic F	Practices after every use.				



CARNA-WAX

MIDWEST FLOOR CARE, INC. Home Office: P. O. Box 30266 Lincoln, NE 68503

USES

CLEANS, POLISHES, AND PROTECTS ALL WOOD FLOORS AND FURNITURE.

FEATURES

PETROLEUM BASED CARNAUBA WAX THAT PRODUCES A HARD GLOSSY FILM.

BENEFITS

PRESERVES AND PROTECTS WOOD. EASY TO MAINTAIN.

DIRECTIONS

APPLY A THIN COAT OF WAX WITH MOP, DISTRIBUTING EVENLY ON THE FLOOR. ALLOW A HALF AN HOUR TO DRY, THEN POLISH WITH A RED OR BLUE PAD BEFORE THE WAX DRIES COMPLETELY.

TECHNICAL DATA

COLOR: YELLOW

FRAGRANCE: SOLVENT

SOLIDS: 12%

FLASH POINT: 105 DEGREES FAHRENHEIT

