

12-21-2020: File
reviewed; more
current MSDS/SDS
not available. JMC

All Scribbles except Neon
731

AUG 14 2014

103-3400 thru 103-3755
103-4400 thru 103-4490

1404966



MATERIAL SAFETY DATA SHEET

Identity

Duncan Scribbles SC 100, SC 200, SC300-316, [REDACTED]

MSDS # 703

Res

SECTION I

Manufacturer's Name

Duncan Enterprises

Address

5673 E. Shields Ave.
Fresno, CA 93727

HMIS Codes

Health 0 Reactivity 0
Fire 1 Protective Equip. G
 (if spraying)

Emergency Telephone Number

(209) 445-1222

Telephone Number

(209) 291-4444

Date Prepared

August 1987

Revised

January 1992

Prepared By

Curt Sathre

SECTION II

HAZARDOUS INGREDIENTS

Hazardous Components

none

OSHA PEL

ACGIH TLV

CAS #

%

Other Information

none

SECTION III

PHYSICAL DATA

Boiling Point, (DEG°F)

212°F

Melting Point, (DEG°F)

n/a

Specific Gravity (Water=1):

1.1

Appearance And Odor

Opaque colored latex paint

pH

8.0 - 9.0

Vapor Pressure, (MM HG.)

n/a

Vapor Density (AIR=1)

Less than 1 water

Water Solubility, %

Insoluble

Freezing Point

n/a

Evaporation Rate (Butyl Acetate=1)

Less than 1 water

103-3400a, thru 103-3785a
103-4400a, thru 103-4490a

MSDS 703

SECTION VII
PRECAUTIONS FOR SAFE HANDLING

Steps To Be Taken In Case Material Is Released Or Spilled

Clean up properly with paper towels and a wet sponge.

Waste Disposal Method

Put paper towels in trash and rinse out sponge. Follow Federal, State and Local regulations for disposal.

Precautions To Be Taken In Handling And Storing

Keep container sealed.

Other Precautions

n/a

SECTION VIII
CONTROL MEASURES

Respiratory Protection (Specify Type)

If spraying, do not inhale mist. Use respirator that is NIOSH approved for sprays and mists.

Ventilation

Local Exhaust

Recommended

Mechanical (General)

Recommended when spraying

Protective Gloves

no

Other Protective Clothing Or Equipment

None needed

Work/Hygienic Practices

Good hygiene practices should be followed.

Special

Use respirator when spraying

Other

none

Eye Protection

Safety glasses with side shields. Do not wear contact lenses.

SECTION IX
ADDITIONAL INFORMATION

CALIFORNIA Proposition 65

n/a



"Products bearing the Nontoxic Product Seal are certified in a program to toxicological evaluation by a nationally recognized toxicologist to contain no materials in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems. These products are certified to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236. In addition, there is no physical hazard as defined within 29 CFR Part 1910.1200(c)."

DISCLAIMER -- Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Since conditions of use are beyond our control, we make no warranties, expressed or implied.

103-3400 B-thru 103375
103-4400 B-thru 103-4490
B

MSDS 703

SECTION IV
FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used) n/a	Flammable Limits LEL n/a UEL n/a
Extinguishing Media Use appropriate techniques and media for surrounding fire.	
Special Fire Fighting Procedures None.	
Unusual Fire And Explosion Hazards Material can spatter above 212°F. Polymer film can burn.	

SECTION V
REACTIVITY DATA

Stability	Unstable:	Stable: X
Conditions To Avoid n/a		
Incompatibility (Materials To Avoid) n/a		
Hazardous Decomposition or Byproducts n/a		
Hazardous Polymerisation	May Occur:	Will Not Occur: X
Conditions To Avoid n/a		

SECTION VI
HEALTH HAZARD DATA

Routes Of Entry	Inhalation? no	Skin? no	Ingestion? no
Health Hazards (Acute and Chronic) None. Nontoxic			
Carcinogenicity	NTP? no	IARC Monographs? no	OSHA Regulated? no
Signs And Symptoms of Exposure n/a			
Medical Conditions Generally Aggravated by Exposure Abrasive, can scratch eyes.			
Emergency And First Aid Procedures Eye contact: Flush with water at least 15 minutes. Skin contact: Wash with soap and water.			