

7/16/2024: File reviewed, more current MSDS/SDS not available. CAS

5-27-04 ✓

33110-XXXX

Material Safety Data Sheet

SOAPSTONE, PG. 1 OF 3

Manufacturer: Sculpture House, Inc. 100 Camp Meeting Avenue Skillman, NJ 08558	Emergency Telephone No.: (609) 466-2986
--	---

SECTION I: PRODUCT IDENTIFICATION

Trade Names & Synonyms: SOAPSTONE, STEATITE, TALC ORE	Part No.: GREEN SOAPSTONE
	CAS No.: 14801-96-6
Chemical Name & Synonyms: MAGNESIUM SILICATE HYDRATE	Formula: 3MGO 4SiO2 H2O
Chemical Family: ALKALINE METAL SILICATE	

SECTION II: HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES & SOLVENTS	%	TLV (Units)	ALLOYS & METALLIC COATINGS	%	TLV (Units)
Pigments N/A			Base Metal N/A		
Catalyst N/A			Alloys N/A		
Vehicle N/A			Metallic Coatings N/A		
Solvents N/A			Filler Material +Coating or Core Filler N/A		
Additives N/A			Others N/A		
Others N/A			Hazardous Mixtures of Other Liquids, Solids or gases N/A		

V-3750

SECTION III: PHYSICAL DATA

Appearance/Odor: LIGHT TO DARK GREEN, WITH A WHITE POWDER DUSTING - NO ODOR.	Vapor Density (Air = 1): N/A
Boiling Point (°F): N/A	Vapor Pressure (mm Hg): N/A
Solubility in Water: NEGLIGIBLE	Specific Gravity (H ₂ O = 1): 2.5 - 2.8
Evaporation Rate: N/A	Volatile % by Volume: N/A
Melting Point: N/A	

SOAPSTONE, PG. 2 OF 3

SECTION IV: FIRE AND EXPLOSION HAZARD DATA		
Flash Point (Method Used):	Flammable Limits (L.E.L.):	Flammable Limits (L.E.L.):
Extinguishing Media:		
NON-FLAMMABLE		
Special Fire Fighting procedures:		
Unusual Fire & Explosion Hazards:		

SECTION V: HEALTH HAZARD DATA
Threshold Limit Value: 20 MPPCF (OSHA) 10 mg/M3 (MSHA) 6mg/M3 (ACGIH)
Effects of Overexposure: IRRITATION TO RESPIRATORY TRACT.
Emergency & First Aid Procedures: WASH SKIN WITH SOAP AND WATER. FLUSH EYES WITH WATER.

SECTION VI: REACTIVITY DATA	
Stability	Conditions to Avoid: NONE
Unstable: Stable: <input checked="" type="checkbox"/>	
Incompatibility (Materials to Avoid): NONE	
Hazardous Decomposition Products: NONE	
Hazardous Polymerization	Conditions to Avoid: NONE
May Occur: Will Not Occur: <input checked="" type="checkbox"/>	

SECTION VII: SPILL OR LEAK PROCEDURES
For Spills or Leakage: NORMAL CLEAN-UP PROCEDURES. CARE SHOULD BE TAKEN TO AVOID CAUSING DUST TO BECOME AIRBORNE. VACUUM CLEANING SYSTEMS ARE RECOMMENDED. DO NOT FLUSH TO SEWER.
Waste Disposal Method: DISPOSAL MUST BE MADE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.