

2424-0000 AUG 18 2008

* Incrd. 618 NIB Frisket Kit *

02902-0002

MATERIAL SAFETY DATA SHEET
OSHA Hazard Communication
Standard (29 CFR 1910.1200)



SIMILAR TO OSHA FORMS 20 AND 174
US Department of Labor
Printed on 7/30/92 at 15:06:54

Material/Product Identity	Seq. No. 4	Rev. No. A
Incredible White Mask Liquid Frisket	ASTM D4236-89	Certified
Color: White Liquid	Certification:	Product
ID # N/A	Regulatory	Not known to
	Status	be regulated

SECTION I MANUFACTURER'S NAME AND LOCATION 00312-1004

Manufact. Name	Graphic Arts Systems Inc.		
Address line 1	19499 Miles Road		
Address line 2	Cleveland, OH	44128	
Address line 3	USA Emerg. Tel. No. (800) 468-6942 USA		
Info. Tel. No.	(800) 447-2349	Contact Lawrence Katz	<i>Current per Brian</i>
Prep. Date	7/23/92	Title President	<i>Graphic Arts 7/17/92</i>

SECTION II HAZARDOUS COMPONENTS/IDENTITY/STANDARDS/CONTENT INFORMATION

Ingredient Listing	CAS No.	OSHA PEL	ACGIH TLV	STEL	% COMP
Latex Emulsion	Mixture	N/L/	N/L	N/L	< 100%
Ammonia	7664-41-7	25 ppm	25 ppm	35 ppm	< 5 %

This is a professional artist's product. It consists of a polymer solution with a small quantity of ammonia. The product has been evaluated for expected hazards that may occur in normal use by professional artists. Avoid excessive heat, avoid breathing mists and use with adequate ventilation.

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	Not App.	Deg. F (Cel)	Spec. Grav.	Less than 1
Melting Point	N/K	Deg. F (Cel)	(H2O=1)	
Vapor Pressure	Water-like		Vapor Density	Same as Water
Evaporation Rate	Water-like		Water Solubility	Soluble
odor			Appearance	Milky Aqueous Liquid

SECTION IV FIRE and EXPLOSION HAZARD DATA

Flash Point	Not App.	Deg. F. (Cel)	Flash Pt. Method	Not App.
Lower Flam. Limit	Not App.	%	Upper Flam. Limit	Not App. %
Exting. Medium	Water spray, dry chemical, CO2			
Specialized Fire Fighting Proc.	Burning dry latex produces dense black clouds of smoke. Wear self-contained breathing apparatus and protective clothing to prevent exposure to usual and expected combustion fumes. No unusual toxic gases are expected.			
Unusual Fire & Explosion Hazard	Expect the usual toxic gases to be produced; dried rubber may produce large amounts of black smoke.			

SECTION V REACTIVITY DATA

(Unstable)	Conditions Excessive Heat; freezing to avoid
Stable (yes/no)	Yes
(Stable)	
Incompat. (Avoid)	Solvents, acids, metals, salts may coagulate latex.
Haz. Decomp. (y/n)	No
Cond. to Avoid	Haz. Polym. (yes/no) No As with any other organic material, combustion and flame in air may produce nitrogen oxides, carbon dioxide and carbon monoxide.

Confirm all information prior to use

Abbreviations:	Not Applicable N/A	Not Flammable N/F	Ceiling Value C
	Not Known N/K		Not Determined N/D
	Respirable Fraction R		Not Listed N/L
Permissible Exposure Limit PEL		ACGIH Threshold Limit Value TLV	Unknown UNKN

The data shown is taken from sources judged to be reliable. The user should verify the accuracy and the suitability of this information for any application or purpose. No other warranty is given. (TLV Reg. TM, ACGIH)

MATERIAL SAFETY DATA SHEET
OSHA Hazard Communication
Standard (29 CFR 1910.1200)



SIMILAR TO OSHA FORMS 20 AND 174
US Department of Labor
Printed on 7/30/92 at 15:06:58

Material Identity Incredible White Mask Liquid Frisket
Color White Liquid ID # N/A

SECTION VI HEALTH HAZARD DATA

Routes of Entry: Inhalation Low hazard; avoid inhaling mist if sprayed.
Skin Not likely to be absorbed Ingest. Not likely to be ingested
Health Hazards None expected from ordinary uses of the product; ammonia content, while low, could irritate eyes if vaporized. Avoid eye and skin contact. If sprayed, use adequate cross ventilation. If sprayed or applied by air brush or air gun, avoid breathing mist. Use a NIOSH approved mask suitable for liquid aerosols.

NTP Carcinogen N/L IARC Carcinogen N/L OSHA Carcinogen N/L
Signs/Symptoms None expected but eye irritation may occur.
of Exposure
Medical Conditions None known. Avoid wearing contact lenses if eye contact to Avoid is possible.
First Aid If contact with eyes occurs, rinse with lukewarm, clean water for 15 minutes; contact a physician if irritation occurs. Skin Measures contact, wash with water.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

Spill Contain and collect for disposal.
Waste Disp Observe all federal, state and local laws concerning health and environment.
Precautions None known; use caution as spill area may be slippery.
Other Precautions None known.

SECTION VIII CONTROL MEASURES

Resp. Protect. Not usually required but a suitable mask for aerosols and mists should be worn if material is to be sprayed in large quantity.
Local Exhaust Not usually required but required if sprayed..
Spec. Local. Exh. None usually required.
Mech. Exhaust None required except if sprayed.
Other Mech. Exhaust None
Protect. Gloves Vinyl or rubber gloves.
Eye Protect Not required for ordinary uses of this product
Protect. Clothing None specifically required; artist smock suggested.
Work Practices Standard industrial practice for the handling of artist materials should be used..

LABEL STATEMENTS

Acute Toxicity Signal Word 1 No Acute Health Labeling Required
Acute Phrase 1 DO NOT TAKE INTERNALLY. AVOID CONTACT WITH EYES.
Acute Phrase 2 KEEP OUT OF REACH OF CHILDREN.
Acute Phrase 3 Refer to MSDS for additional information.
Chronic Toxicity Chronic Signal No chronic health labeling required
Chronic Phrase 1
Chronic Phrase 2
Chronic Phrase 3

ASTM D4236 Complies with ASTM D4236-89
Certification Assurance

=====
Confirm all information prior to use
Abbreviations: Not Applicable N/A.. Not Flammable N/F Ceiling Value C
Not Determined N/D
Not Known N/K Not Listed N/L
Respirable Fraction R Unknown UNKWN
Permissible Exposure Limit PEL ACGIH Threshold Limit Value TLV
The data shown is taken from sources judged to be reliable. The user should judge both the accuracy and the suitability of this information for any intention or purpose. No other warranty is given. (TLV Reg. TM, ACGIH)

POISINDEX INFORMATION SYSTEM PRODUCT INFORMATION FORM - SUBMITTED ON 7/30/92

Brand/Product Name Incredible White Mask Liquid Frisket
 Color Name White Liquid
 Product Sizes 4.5 and 8.5 Fluid Ounce; Larger sizes may be ordered.
 Catalog/Reg. # N/A Use/Application Art Material
 Color I.D. Name N/A Index # N/A
 Product Color(s) N/A Formula Date Prior to 1992
 State (pH if Liq.) 9.20 Industr Use (Y/N) Yes
 Viscosity Unknown Consumer Use (Y/N) Yes
 Entry into Market Before 1992 Children's Use (Y/N) Unlikely
 Manufacturer's Graphic Arts Systems Inc.
 Name, Address & 19499 Miles Road , Cleveland
 Telephone Number OH 44128 USA (800) 447-2349

Toxicity Information, Contact Dr. Jaeger at 201-666-7929 or 800-468-6943

Chemical Ingredients	CAS #/ID #/Color Index #	% H/L or Range
1 Latex Emulsion	Mixture	< 100%
2 Ammonia	7664-41-7	< 5 %
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		



Submitted by Environmental Medicine, Inc. 263 Center Avenue

Item Numbers: 02902-0002 Westwood, NJ 07675 USA on behalf of the named manufacturer Page 3 of 4

Material/Product Identity
Incredible White Mask Liquid Frisket

Seq. No. 4
ASTM D4236-89
Certification
Regulatory
Status

Rev. No. A
Certified
Product
Not known to
be regulated

White Liquid N/A

Manufact. Name	Graphic Arts Systems Inc.
Address line 1	19499 Miles Road
Address line 2	Cleveland, OH 44128
Address line 3	USA Emerg. Tel. No. (800)468-6942 USA
Info. Tel. No.	(800) 447-2349
Prep. Date	7/23/92
	Contact Lawrence Katz
	Title President

REQUIRED LABEL STATEMENTS

Conformity Phrase Complies with ASTM D4236-89

Acute Signal Word No Acute Health Labeling Required

Acute Phrase 1 DO NOT TAKE INTERNALLY. AVOID CONTACT WITH EYES.

Acute Phrase 2 KEEP OUT OF REACH OF CHILDREN.

Acute Phrase 3 Refer to MSDS for additional information.

Chronic Signal Word No chronic health labeling required

Chronic Phrase 1

Chronic Phrase 2

Chronic Phrase 3

Mis'c Warning Word KEEP OUT OF REACH OF CHILDREN

