SAFETY DATA SHEET



4-17-2023: File reviewed, more current MSDS/SDS not available. JMC

1. Identification

Product identifier Liquid Wrench Penetrating Oil

Other means of identification

SDS number L112

Part No. L106, L112, L112/4, L112/6, L103

Tariff code 3403.19.5000

Recommended use Penetrating Oil

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Blumenthal Brands Integrated, LLC

Address 600 Radiator Road

Indian Trail, NC 28079

Telephone Customer Service/ (704) 821-7643

Technical

Website www.solvewithB.com
E-mail sds@solvewithB.com

Emergency phone number INFOTRAC (United States) (800) 535-5053

INFOTRAC (International) (352) 323-3500

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 2Health hazardsAcute toxicity, oralCategory 4Skin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2A

Sensitization, skin Category 1B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable aerosol. Harmful if swallowed. Contains gas under pressure; may explode if heated.

Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear eye protection/face protection.

L106, L112, L112/4, L112/6, L103 Version #: 14 Revision date: 04-14-2020 Issue date: 04-27-2015

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Hazard(s) not otherwise classified (HNOC)

Dispose of contents/container in accordance with local/regional/national/international regulations.

None known.

Supplemental information

92.42% of the mixture consists of component(s) of unknown acute inhalation toxicity. 98.08% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 98.08% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the workplace.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Hydrotreated Light Naphthenic Distillates Petroleum		64742-53-6	70 - < 80
1,6,10-dodecatriene, 7,11-dimethyl-3-methylene-, (6e)-, Hydrogenated		1581740-29-5	1 - < 3
1-Hexadecene		629-73-2	1 - < 3
1-Tetradecene		1120-36-1	1 - < 3
Carbon Dioxide		124-38-9	1 - < 3
Other components below reportable le	evels		10 - < 20

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison
	center or doctor/physician if you feel unwell.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

> Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Ingestion

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Suitable extinguishing media

L106, L112, L112/4, L112/6, L103 Version #: 14 Revision date: 04-14-2020 Issue date: 04-27-2015

Material name: Liquid Wrench Penetrating Oil

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
Hydrotreated Light Naphthenic Distillates Petroleum (CAS 64742-53-6)	PEL	5 mg/m3	Mist.
		2000 mg/m3	

Material name: Liquid Wrench Penetrating Oil

US. OSHA Table Z-1 Limits for A Components	Type	Value	Form
		500 ppm	
US. ACGIH Threshold Limit Valu	ies		
Components	Туре	Value	Form
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
Hydrotreated Light Naphthenic Distillates Petroleum (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	Form
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Hydrotreated Light Naphthenic Distillates	Ceiling	1800 mg/m3	

Biological limit values

Petroleum (CAS 64742-53-6)

Appropriate engineering

controls

No biological exposure limits noted for the ingredient(s).

STEL

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

10 mg/m3

Mist.

Individual protection measures, such as personal protective equipment

Eye/face protection Face shield is recommended. Wear safety glasses with side shields (or goggles).

Skin protection

Wear appropriate chemical resistant gloves. Hand protection Other Wear appropriate chemical resistant clothing.

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an Respiratory protection

air-supplied respirator. Chemical respirator with organic vapor cartridge and full facepiece if

threshold limits are exceeded. Dust & vapor respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Liquid Opaque **Appearance**

Liquid. **Physical state** Aerosol. **Form** Color Yellow Odor Fragrance **Odor threshold** Not available. Not available. Ηq Melting point/freezing point Not available.

Initial boiling point and boiling 446 °F (

range

446 °F (230 °C) estimated

Flash point 200.0 °F (93.3 °C) Tag Closed Cup

Evaporation rate Not available.
Flammability (solid, gas) Not applicable.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.08852 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 7.26 lbs/gal
Explosive properties Not explosive.

Flame extension > 18 in Flammability (flash back) No

Flammability class Combustible IIIB estimated

Heat of combustion (NFPA

30B)

36.35 kJ/g

Oxidizing properties Not oxidizing.

Percent volatile 0.1 % estimated

Specific gravity 0.87 VOC 0 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decompositionNo hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Material name: Liquid Wrench Penetrating Oil

SDS US

Ingestion Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or

vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components Species Test Results

1-Hexadecene (CAS 629-73-2)

<u>Acute</u>

Dermal

LD50 Rabbit > 10 mg/kg, 24 Hours

Oral

LD50 Rat > 5 mg/kg

1-Tetradecene (CAS 1120-36-1)

Acute

Dermal

LD50 Rabbit > 10 mg/kg, 24 Hours

Inhalation

Vapor

LC50 - 18.5 mg/l, 4 Hours

Oral

LD50 Rat > 5 mg/kg

Hydrotreated Light Naphthenic Distillates Petroleum (CAS 64742-53-6)

<u>Acute</u>

Dermal

LD50 Rabbit > 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat > 3.9 mg/l, 4 Hours

Oral

LD50 Rat > 2000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Hydrotreated Light Naphthenic Distillates Petroleum Known To Be Human Carcinogen.

(CAS 64742-53-6)

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Reproductive toxicity

May cause drowsiness and dizziness.

Specific target organ toxicity - Not classified.

repeated exposure

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

1,6,10-dodecatriene, 7,11-dimethyl-3-methylene-, (6e)-, 6.08 - 6.48 OECD 117, Log Kow

Hydrogenated

1-Tetradecene 7.3

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Transport hazard class(es) Aerosols, flammable, (each not exceeding 1 L capacity), Limited Quantity

Class 2.1 Subsidiary risk -

Subsidiary risk -Label(s) 2.1

Packing group Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not available.

Environmental hazards Yes ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN1950

UN proper shipping name Aerosols, flammable, MARINE POLLUTANT (Petroleum Distillates)

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not available.

Environmental hazards

Marine pollutant Yes EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.


Petroleum Distillates

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code





IATA; IMDG



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Yes

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Hydrotreated Light Naphthenic Distillates Petroleum (CAS 64742-53-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

04-27-2015 Issue date **Revision date** 04-14-2020

Version # 14

HMIS® ratings Health: 2

Flammability: 1 Physical hazard: 0

Health: 2

NFPA ratings

Flammability: 1 Instability: 0

Material name: Liquid Wrench Penetrating Oil

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

Product and Company Identification: Product Codes Physical & Chemical Properties: Multiple Properties