#### 7/16/2024: File reviewed, more current MSDS/SDS not available. CAS

# **Safety Data Sheet**

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be Consulted for specific requirements

# **U.S. Department of Labor**

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

Identity (As used on Label and List)	Note: Blank spaces are not permitted. If any item is not
Orton Pyrometric Cones / Bars / TempCheks /	applicable, or no information is available, the space must be
Cone Plaques/Kiln wash	marked to indicate that.

### **Section 1 – Product Identification**

Emergency Telephone Number
(614) 895-2663
Telephone Number for Information
(614) 895-2663
Signature of Preparer (Optional)

### Section 2 – Hazardous Ingredients/Identity Information

Hazardous Components	OSHA		Other Limits	(%)
(Specific Chemical Identity: Common Name(s))	PEL	ACGIH TLV	Recommended	(Optional)
Plaques, TempCheks, TempTAB, Pyrometric Cone				
and Bar Numbers				
022, 021, 020, 019, 018, 017, 016, 015, 014, 013,				
012, 011, 010, 09, 08, 07, 06, 05½, 05, 04, 03, 02,				
01, 1, 2, 3, 4, 5, 5½, 6, 7, 8, 9, 10, 11, 12, 12½, 13,				
13 <sup>1</sup> / <sub>2</sub> , 14, 14 <sup>1</sup> / <sub>2</sub> , 15, 15 <sup>1</sup> / <sub>2</sub> , 16, 17, 18, 19, 20, 21, 23,				
26, 27, 28, 29, 30, 31, 31 <sup>1</sup> / <sub>2</sub> , 32, 32 <sup>1</sup> / <sub>2</sub> , 33, 34, 35, 36				
37, 38, 39, 40, 41 (Contain 2-65% Silica)				
Silica as dust	10	0.025mg/m <sup>3</sup> TWA		
Silica as dust	mg/m <sup>3</sup>	(respirable dust)		



#### DANGER

May cause cancer by inhalation.

Causes Damage to lungs through prolonged or repeated exposure by inhalation.

#### **Response:**

If exposed or concerned: get medical advice

# Disposal:

Dispose of contents/containers in accordance with local regulation

#### Prevention

Do not eat, drink, or smoke when using this product Do not breath dust

# Section 3 – Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity $(H_2O = 1)$	1.8 - 2.0
Vapor Pressure (mmHg)	N/A	Melting Point	N/A
Vapor Density (Air = 1)	N/A	<b>Evaporation Rate</b> (Butyl Acetate = 1)	N/A
Solubility in Water			

Nil

Appearance and Color Solid-Shape of pyramid or rectangular shape – some products contain organic colors for aid in identification

### Section 4 – Fire And Explosion Hazard Data

	1				
Flash Point (Method Used)	Flammable Limits	LEL	UEL		
N/A	N/A	N/A	N/A		
Extinguishing Media					
N/A					
Special Fire Fighting Procedures					
All products except those labeled Fast Fire or PCE contain 4-6% organic material that will oxidize above 300°F					
Unusual Fire and Explosion Hazards					

N/A

### Section 5 – Reactivity Data

Stability	Unstable		Conditions to Avoid	
	Stable	X		
Incompatibility (Mate	erials to Avoid)			
N/A	,			
Hazardous Decompos N/A	sition or Byproducts			
Hazardous	May Occur		Conditions to Avoid	
11a2a1 u0u5	-			
Polymerization	-			

### Section 6 – Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
-	N/A	None Anticipated	None Anticipated
Health Hazards (Acute	and Chronic)		
Product is non-hazardous	s when used as intended. Pr	oduct should not be ground into d	ust or ingested.
Product may contain crys	stalline silica, which may ca	use cancer, when inhaled, based o	n animal testing.
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
· ·	No	No	No
Signs and Symptoms of	Exposure		
N/A	-		
<b>Medical Conditions Ge</b>	nerally Aggravated by Exp	oosure	
	• • • •		
N/A			
N/A Emergency and First A	id Procedures		

### Section 7 – Precautions for Safe Handling and Use

Steps to be taken in Case Material is Released or Spilled

#### No specific precautions Waste Disposal Method

Disposal must meet existing federal, state, and local environmental control for low soluble glass frit - titanium dioxide

#### – silica

Precautions to Be Taken in Handling and Storing

Keep out of reach of children. Wash hands after handling.

#### **Other Precautions**

Organic components may produce harmful gases during firing, if not fully oxidized. Also other gases may be produced during firing, therefore, provide adequate ventilation to kiln or kiln area.

### **Section 8 – Control Measures**

Respiratory Protection (Specify Typ	e)		
N/A			
Ventilation	Local Exhaust		Special
	N/A		N/A
	Mechanical (General)		Other
	N/A		N/A
Protective Gloves		Eye Protection	
N/A		N/A	
Other Protective Clothing or Equip	ment		
No special requirements			
Work/Hygienic Practices			
Wash hands after handling			

## Section 9 - Physical and Chemical Properties

**Appearance**: Pyrometric Cones are three sided elongated pyramids 1" to 2" long. Cone plaques are rectangular clay forms ranging in Length, width, and height between  $3^{\circ}-4^{\circ}x1^{\circ}x1/2^{\circ}$ . TempCheks and TempTABs are ceramic disks 1 1/8" in diameter by  $\frac{1}{4}$ " thick.

Odor: none	
Vapor Pressure: none	
PH: neutral	
Melting point: above 1000°F	
Freezing point: none	
Flammability: none	

### Section 10 – Stability and Reactivity

### Reactivity: None

Chemical Stability: Stable

### Section 11 – Toxicological Information

Not toxic

### Section 12 – Ecological Information

None available

# Section 13 – Disposal Considerations

No precautions known

# **Section 14 – Transport Information**

Non-hazardous

# <u>Section 15 – Regulatory Information</u>

**California Proposition 65**: Crystalline silica (airborne particles of respirable size) is classified as a substance known to the state of California to be a carcinogen

### <u>Section 16 – Other Information</u>

Rev 8/31/18

Product resources found at www.ortonceramic.com