

MATERIAL HEALTH AND  
SAFETY BULLETIN

41-549  
41-550 # 284  
97-1309

6/12/2024: File Reviewed. More current MSDS/SDS not available. CAS  
This company has closed

MANUFACTURER'S NAME

Andrew Jeri Company, Inc.  
110 Bayview Blvd. P. O. Box 850  
Oldsmar, Florida 33557-0850

TELEPHONE (813) 855 3232

PRODUCT:	Photo Maskoid and Reducer (Photo Retouching Medium)	WARNING STATEMENT
GENERIC NAME:	Volatile Solvent and Mixture	If swallowed, contact physician immediately. Physician should consult Los Angeles Pois- Control Center (213) 644 - 2121 regarding vomiting. (24 hour number)
CHEMICAL NAME:	Not Applicable	For Industrial and Professional use only.
CHEMICAL FAMILY:	Mixture of Chlorinated and Oxygenated Hydrocarbons	
DOT PROPER SHIPPING NAME:	Not Applicable.	

INGREDIENTS

	TLV* (*Threshold limit Value)
Xylene	100A (A, OSHA X)
Ethyl Isobutyl Ketone	100A
Methylene Chloride	500A
Resin Mixtures	Not Applicable

EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT	If this products comes in contact with the eyes, flush with large quantities of water for at least 15 minutes.
SKIN CONTACT	If this product comes in contact with the skin, wash with large quantities of water.
INHALATION	If dizziness, or lightheadedness occur when working in areas with high vapor concentration, victim should seek air free of vapors.
INGESTION	If swallowed, contact physician immediately.

PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION

EYE CONTACT	This product may be an eye irritant.
SKIN EFFECTS	Prolonged or repeated skin contact may result in dermatitis.

REACTIVITY DATA

STABILITY	Stable X
INCOMPATIBILITY (materials to avoid)	This product is incompatible with strong oxidizing agents, strong acids or bases, selected amines, halogens, halogen containing compounds and strong alkalies.

289  
C

#2

HAZARDOUS DECOMPOSITION PRODUCTS Burning decomposition in the presence of air may yield carbon monoxide and/or carbon dioxide, phosgene and HCl.

HAZARDOUS POLYMERIZATION Will not occur.

SPECIAL PROTECTION INFORMATION

VENTILATION General ventilation may be sufficient to keep vapor concentrations within specified time-weighted TLV ranges. If general ventilation proves inadequate to maintain safe vapor concentrations, supplement local exhaust may be required.

SPILL OR LEAK PROCEDURES

PRECAUTIONS IN CASE OF RELEASE OR SPILL Keep sources of ignition and hot metal surfaces isolated from the spill. Flush spilled material into suitable retaining areas or containers with large quantities of water. Small amounts of spilled material may be absorbed into an appropriate absorbant.

WASTE DISPOSAL METHOD Dispose of product in accordance with applicable local, county state and federal regulations. Prevent spilled liquid from entering sewers, storm drains, other unauthorized sewage treatment/drainage systems and natural waterways. Wet down to prevent blowing material.

STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORING PRECAUTIONS Keep products containers cool, dry, and away from sources of ignition. Use and store this product with adequate ventilation. Keep product containers closed when not in use.

FIRE AND EXPLOSION HAZARD DATA

DOT FLAMMABILITY CLASSIFICATION Not applicable FLASH POINT RANGE: None to boiling.

PHYSICAL DATA

APPROXIMATE BOILING RANGE °F 104° - 286° F VAPOR DENSITY: Heavier than Air  
EVAPORATION RATE: slower than Ether PERCENT VOLATILE: 100% SOLUBILITY IN WATER: Negligible  
SPECIFIC GRAVITY Heavier than Water WEIGHT PER GALLON: 8.57  
APPEARANCE AND ODOR: Red to Clear and has a characteristic odor.