

SAFETY DATA SHEET

Revision Date 28-Oct-2016

Revision Number 0

This document complies with the US OSHA Hazard Communication Standard (29 CFR 1910.1200), Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR), and Mexico's NMX-R-019-SC-2011.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier		
Product Name	Dykem Remover and Pre	ep Aerosol
Other means of identification		
Part Number	82038	
Formula Code	8947A	
Synonyms	None	
Recommended use of the chemica	l and restrictions on use	
Recommended Use	Remover & Cleaner, Aero	sol
Uses advised against	No information available	
Supplier's details		
Initial Supplier ITW Permatex Canada 1-35 Brownridge Road Halton Hills, ON, L7G 0C6 Canada		Supplier Address ITW PRO BRANDS 805 E. Old 56 Highway Olathe, KS 66061 TEL: 1-800-443-9536
Emergency telephone number		
Emergency Telephone Number	800-535-5053 Infotrac	
	2. HAZARDS ID	DENTIFICATION
Classification		

Classification

This product is considered hazardous according to the criteria set within the US OSHA Hazard Communication Standard (29 CFR 1910.1200), Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR), and Mexico's NMX-R-019-SC-2011.

Serious Eye Damage/Eye Irritation	Category 2
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

Label Elements

Danger



Hazard Statements

Causes serious eye irritation May cause drowsiness or dizziness Extremely flammable aerosol Contains gas under pressure; may explode if heated

Physical and Health Hazards Not Otherwise Classified Not applicable.

Precautionary Statements

- Prevention
- Wash face, hands and any exposed skin thoroughly after handling.
- · Wear eye/face protection.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Keep away from heat/sparks/open flames/hot surfaces No smoking.
- · Do not spray on an open flame or other ignition source
- Pressurized container: Do not pierce or burn, even after use.

General Advice

None

Eyes

• IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

• If eye irritation persists: Get medical advice/attention.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion

None

Fire

None

Spills and Leaks

None

Storage

- Store in a well-ventilated place. Keep container tightly closed.
- · Store locked up.
- Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
- Protect from sunlight

Disposal

• Dispose of contents/container to an approved waste disposal plant.

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Acetone	67-64-1	54.4	-	-
Ethanol	64-17-5	27.54	-	-
Petroleum gases, liquified, sweetened	68476-86-8	15	-	-
n-Propyl acetate	109-60-4	1.53	-	-
Isopropyl alcohol	67-63-0	1.53	-	-

4. FIRST AID MEASURES

Description of necessary first-a	id measures	
General Advice	Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.	
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if applicable, and continue flushing. Keep eye wide open while rinsing. If symptoms persist, call a physician.	
Skin Contact	Wash off immediately with plenty of water. If skin irritation persists, call a physician. Clothing frozen to the skin should be thawed before being removed.	
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms persist, call a physician.	
Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Consult a physician if necessary.	
Protection of First-aiders	Use personal protective equipment. Remove all sources of ignition.	
Most important symptoms/effects, a	acute and delayed	
Most Important Symptoms/Effects	Eye irritation/reactions. Drowsiness. Dizziness.	
Indication of immediate medical attention and special treatment needed, if necessary		
Notes to Physician	Treat symptomatically.	
Notes to Physician		
Notes to Physician Suitable Extinguishing Media	Treat symptomatically.	
-	Treat symptomatically. 5. FIRE-FIGHTING MEASURES	
Suitable Extinguishing Media	Treat symptomatically. 5. FIRE-FIGHTING MEASURES Carbon dioxide (CO 2). Dry chemical. Alcohol-resistant foam.	
Suitable Extinguishing Media Unsuitable Extinguishing Media Specific Hazards Arising from the	Treat symptomatically. 5. FIRE-FIGHTING MEASURES Carbon dioxide (CO ²). Dry chemical. Alcohol-resistant foam. No information available. Flammable. Flash back possible over considerable distance. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Ruptured cylinders may rocket.	

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges. Pay attention to flashback. Contents under pressure.
Environmental Precautions	
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.
Methods and materials for contain	nent and cleaning up
Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Cleaning Up	Take up with sand or other noncombustible absorbent material and place into containers for later disposal.
	7. HANDLING AND STORAGE
Precautions for safe handling	
Handling	Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. Do not breathe vapors or spray mist. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Use only in area provided with appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
Conditions for safe storage, including any incompatibilities	
Storage	Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat and sources of ignition. Keep out of the reach of children. Do not store above 49°C / 120.2°F.
Incompatible Products	Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm 10% LEL
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	-
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for all	
		other sectors	
		(vacated) STEL: 1000 ppm	
Ethanol	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm 10% LEL
64-17-5		TWA: 1900 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m ³
		(vacated) TWA: 1900 mg/m ³	-
Isopropyl alcohol	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm 10% LEL
67-63-0	TWA: 200 ppm	TWA: 980 mg/m ³	TWA: 980 mg/m ³

		(vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	TWA: 400 ppm STEL: 500 ppm STEL: 1225 mg/m ³
n-Propyl acetate 109-60-4	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 840 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 840 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 1050 mg/m ³	IDLH: 1700 ppm TWA: 200 ppm TWA: 840 mg/m ³ STEL: 250 ppm STEL: 1050 mg/m ³

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).	
Appropriate engineering controls		
Engineering Measures	Showers Eyewash stations Ventilation systems	
Individual protection measures, such as personal protective equipment		
Eye/Face Protection Skin and Body Protection Respiratory Protection	Avoid contact with eyes. Risk of contact, wear: Goggles. Rubber gloves. No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.	
Hygiene Measures	When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Odor	Aerosol. Sweet, Solvent.	Appearance Odor Threshold	Clear, Cloudy White, Colorless. No information available.
Property pH Melting Point/Range Boiling Point/Boiling Range Flash Point Evaporation rate Flammability (solid, gas) Flammability Limits in Air upper flammability limit lower flammability limit lower flammability limit Vapor Pressure Vapor Density Specific Gravity Water Solubility Solubility in other solvents Partition coefficient: n-octan Autoignition Temperature Decomposition Temperature Viscosity	No data available	Remarks/ - None known None known	
Flammable Properties	EXTREMELY FLAMMA	BLE	
Explosive Properties Oxidizing Properties	No data available No data available		

Other information

VOC Content (%) VOC (g/l) 100.000002384186 388 g/l

10. STABILITY AND REACTIVITY

Reactivity	No data available.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Temperatures above 49 $^\circ$ C / 120.2 $^\circ$ F. Incompatible products.
Incompatible materials	Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

Hazardous decomposition products Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Inhalation	May cause drowsiness and dizziness. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal Inhalation of vapors in high concentration may cause irritation of respiratory system.
Eye Contact	Causes serious eye irritation.
Skin Contact	Repeated exposure may cause skin dryness or cracking.
Ingestion	Not an expected route of exposure.

Numerical measures of toxicity - Product

Unknown acute toxicity	0% of the mixture consists of ingredient(s) of unknown toxicity.	
The following values are calculated based on chapter 3.1 of the GHS document:		
LD50 Oral	7251 mg/kg; Acute toxicity estimate	
LD50 Dermal	836601 mg/kg; Acute toxicity estimate	
Inhalation		
dust/mist	452.8 mg/L; Acute toxicity estimate	
Vapor	3634.7 mg/L; Acute toxicity estimate	

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetone	= 5800 mg/kg (Rat)	1700mg/kg (rabbit)	18892 mg/m ³
Ethanol	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat)4 h
Isopropyl alcohol	= 1870 mg/kg (Rat)	12800 mg/kg (Rat)	72.6 mg/L (Rat)4 h
		12870 mg/kg (Rabbit)	
n-Propyl acetate	= 8700 mg/kg (Rat)	> 17756 mg/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Respiratory or Skin Sensitization	No information available.
Germ Cell Mutagenicity	No information available.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.
	Ethanol has been shown to be carcinogenic in long-term studies only when consumed and
	abused as an alcoholic beverage.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethanol	A3	Group 1	Known	Х
Isopropyl alcohol		Group 3		Х

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to its Carcinogenicity to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity STOT - single exposure STOT - repeated exposure	No information available. No information available. No information available.
Chronic Toxicity	Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage. Ethanol has been shown to be carcinogenic in long-term studies only when
Target Organ Effects Aspiration Hazard	consumed as alcoholic beverage. Respiratory system. Eyes. Skin. Central nervous system (CNS). No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to	Daphnia Magna (Water
		-	Microorganisms	Flea)
Acetone		LC50 96 h: 4.74 - 6.33 mL/L	EC50 = 14500 mg/L 15 min	EC50 48 h: 10294 - 17704
67-64-1		(Oncorhynchus mykiss)		mg/L Static (Daphnia
		LC50 96 h: 6210 - 8120		magna) EC50 48 h: 12600 -
		mg/L static (Pimephales		12700 mg/L (Daphnia
		promelas) LC50 96 h: =		magna)
		8300 mg/L (Lepomis		
		macrochirus)		
Ethanol		LC50 96 h: 12.0 - 16.0 mL/L		LC50 48 h: 9268 - 14221
64-17-5		static (Oncorhynchus	EC50 = 35470 mg/L 5 min	mg/L (Daphnia magna)
		mykiss) LC50 96 h: 13400 -		EC50 24 h: = 10800 mg/L
		15100 mg/L flow-through		(Daphnia magna) EC50 48
		(Pimephales promelas)		h: = 2 mg/L Static (Daphnia
		LC50 96 h: > 100 mg/L static		magna)
		(Pimephales promelas)		
n-Propyl acetate		LC50 96 h: 56 - 64 mg/L		EC50 24 h: = 318 mg/L
109-60-4		flow-through (Pimephales		(Daphnia magna)
		promelas) LC50 96 h: 56 -		
		64 mg/L static (Pimephales		
		promelas)		
Isopropyl alcohol	EC50 72 h: > 1000 mg/L	LC50 96 h: = 11130 mg/L		EC50 48 h: = 13299 mg/L
67-63-0	(Desmodesmus	static (Pimephales		(Daphnia magna)
	subspicatus) EC50 96 h: >	promelas)		
	1000 mg/L (Desmodesmus	LC50 96 h: = 9640 mg/L		
	subspicatus)	flow-through (Pimephales		
		promelas)		
		LC50 96 h: > 1400000 µg/L		
		(Lepomis macrochirus)		

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Acetone	-0.24
Ethanol	-0.32
Petroleum gases, liquified, sweetened	2.8
Isopropyl alcohol	0.05
No 1994	

Mobility

No information available.

Other Adverse Effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with local/regional/national regulations.

Contaminated Packaging Do not re-use empty containers.

U002

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone - 67-64-1		Included in waste stream:		U002
		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Acetone	Ignitable
Ethanol	Toxic
	Ignitable
n-Propyl acetate	Toxic
	Ignitable
Isopropyl alcohol	Toxic
	Ignitable

14. TRANSPORT INFORMATION

201

Proper shipping name Hazard Class Reportable Quantity (RQ) Description Emergency Response Guide Number	Consumer commodity ORM-D Acetone: RQ kg= 4172.79 Consumer commodity, ORM-D 126
<u>TDG</u> UN-Number Proper Shipping Name Hazard Class Description	UN1950 Aerosols 2.1 UN1950, Aerosols, 2.1
MEX UN-Number Proper Shipping Name Hazard Class Description	UN1950 Aerosols 2.1 UN1950, Aerosols, 2.1
IATA UN-Number Proper Shipping Name Hazard Class ERG Code Description	UN1950 Aerosols, flammable 2.1 10L UN1950, Aerosols, flammable, 2.1
IMDG/IMO UN-Number Proper Shipping Name	UN1950 Aerosols

Hazard Class	2
Subsidiary Class	See SP63
EmS No.	F-D, S-U
Description	UN1950, Aerosols, 2.1 (See SP63)

15. REGULATORY INFORMATION

International Regulations

Ozone depleting substances Persistent Organic Pollutants Hazardous Waste	Not applicable Not applicable		
Chemical Name		Basel Convention (Hazardous Wastes)	
Acetone		Y42	
Ethanol		Y42	
Isopropyl alcohol		Y42	
The Rotterdam Convention (Prior Informed Consent)	Not applicable		
International Convention for the Prevention of Pollution from Ships (MARPOL)	Not applicable		
International Inventories			

Complies
Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Isopropyl alcohol	67-63-0	1.53	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Acetone	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals: Ethyl alcohol is only considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage.

Chemical Name	CAS-No	California Prop. 65
Ethanol	64-17-5	Developmental

U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Acetone	Х	Х	Х		Х
Ethanol	Х	Х	Х	Х	
Isopropyl alcohol	Х	Х	Х		Х
n-Propyl acetate	Х	Х	Х		Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION					
NFPA_	Health Hazard 2	Flammability 4	Instability 0	Physical and Chemical Hazards -	
<u>HMIS</u>	Health Hazard 2	Flammability 4	Physical Hazard 0	Personal Protection X	
Prepared By	By Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501				
Issuing Date Revision Date Revision Note	28-Oct-2016 28-Oct-2016 Initial Release.				

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet