

<b>LASCO</b>		<b>MATERIAL SAFETY DATA SHEET</b>		Date Revised: APRIL 2000																								
				Supersedes: APRIL 1998																								
Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. LARSEN SUPPLY COMPANY urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents and contractors of the information on this sheet.																												
<b>SECTION I</b>																												
<b>MANUFACTURER'S NAME</b> INSTANT PLASTICS SYSTEMS  <b>ADDRESS</b> P. O. BOX 48007, GARDENA, CA. 90248			<b>Transportation Emergencies:</b> CHEMTREC: (800) 424-9300 or 3 E COMPANY (800) 451-8346  <b>Medical Emergencies:</b> 3 E COMPANY (24 HOUR No) (800) 451-8346  <b>Business: (310) 898-3300</b>																									
<b>CHEMICAL NAME and FAMILY</b> Solvent Cement for PVC Plastic Pipe Mixture of PVC Resin and Organic Solvents			<b>TRADE NAME:</b> LASCO "A" LOW VOC CLEAR PVC CEMENT FORMULA: Proprietary																									
<b>SECTION II - HAZARDOUS INGREDIENTS</b>																												
None of the ingredients below are listed as carcinogens by IARC, NTP or OSHA																												
	CAS#	APPROX %	ACGIH-TLV	ACGIH-STEL																								
				OSHA-PEL																								
				OSHA-STEL																								
				(A) AEL																								
				(B) STEL																								
Polyvinyl Chloride Resin (PVC)	NON/HAZ		N/A	N/A																								
Tetrahydrofuran (THF) **	109-99-9		200 PPM	250 PPM																								
Methyl Ethyl Ketone (MEK)	78-93-3	20*	200 PPM	300 PPM																								
Cyclohexanone	108-94-1		25 PPM Skin	25 PPM Skin																								
* Title III Section 313 Supplier Notification: This product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40CFR372. This information must be included in all MSDS's that are copied and distributed for this material.																												
(A) Dupont's Acceptable Exposure Limit (AEL) guidelines for 8 hour and 12 hour TWA, (B) Dupont's recommended STEL for 15 minute TWA.																												
** Information found in a report from the National Toxicology Program (NTP) on an inhalation study in rats and mice suggests that Tetrahydrofuran (THF) can cause tumors in animals. In the study the rats and mice were exposed to THF vapor levels up to 1800 PPM for two years (their lifetime), 6 hours/day, 5 days/week. Test results showed evidence of liver tumors in female mice and kidney tumors in male rats. There is no data linking Tetrahydrofuran exposure with cancer in humans.																												
<b>BULK SHIPPING INFORMATION / CONTAINERS LARGER THAN ONE LITER</b>			<b>SPECIAL HAZARD DESIGNATIONS</b>																									
DOT Shipping Name: Adhesive DOT Hazard Class: 3 Identification Number: UN 1133 Packaging Group: II Label Required: Flammable Liquid			<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="text-align: center;">HMIS</th> <th style="text-align: center;">NFPA</th> <th style="text-align: center;">HAZARD RATING</th> </tr> </thead> <tbody> <tr> <td>HEALTH:</td> <td style="text-align: center;">2</td> <td style="text-align: center;">2</td> <td style="text-align: center;">0 - MINIMAL</td> </tr> <tr> <td>FLAMMABILITY:</td> <td style="text-align: center;">3</td> <td style="text-align: center;">3</td> <td style="text-align: center;">1 - SLIGHT</td> </tr> <tr> <td>REACTIVITY:</td> <td style="text-align: center;">0</td> <td style="text-align: center;">1</td> <td style="text-align: center;">2 - MODERATE</td> </tr> <tr> <td>PROTECTIVE</td> <td></td> <td></td> <td style="text-align: center;">3 - SERIOUS</td> </tr> <tr> <td>EQUIPMENT:</td> <td style="text-align: center;">H</td> <td></td> <td style="text-align: center;">4 - SEVERE</td> </tr> </tbody> </table>			HMIS	NFPA	HAZARD RATING	HEALTH:	2	2	0 - MINIMAL	FLAMMABILITY:	3	3	1 - SLIGHT	REACTIVITY:	0	1	2 - MODERATE	PROTECTIVE			3 - SERIOUS	EQUIPMENT:	H		4 - SEVERE
	HMIS	NFPA	HAZARD RATING																									
HEALTH:	2	2	0 - MINIMAL																									
FLAMMABILITY:	3	3	1 - SLIGHT																									
REACTIVITY:	0	1	2 - MODERATE																									
PROTECTIVE			3 - SERIOUS																									
EQUIPMENT:	H		4 - SEVERE																									
<b>SHIPPING INFORMATION FOR CONTAINERS LESS THAN ONE LITER</b> DOT Shipping Name: Consumer Commodity DOT Hazard Class: ORM-D			H = Eye, Hand/Skin, Respiratory Protection and Impermeable Apron																									
<b>SECTION III - PHYSICAL DATA</b>																												
<b>APPEARANCE</b>		<b>ODOR</b>		<b>BOILING POINT (°F/°C)</b>																								
Clear, regular syrupy liquid		Ethereal		151°F (67°C) Based on first boiling component: THF																								
<b>SPECIFIC GRAVITY @ 73 ± 3.6°F (23 ± 2°C)</b>		<b>VAPOR PRESSURE (mm Hg.)</b>		<b>PERCENT VOLATILE BY VOLUME (%)</b>																								
0.950 ± 0.040		143 mm Hg. based on first boiling component, THF @ 68°F (20°C)		Approx. 70-80%																								
<b>VAPOR DENSITY (Air = 1)</b>		<b>EVAPORATION RATE (BUAC = 1)</b>		<b>SOLUBILITY IN WATER</b>																								
2.49		> 1.0		Solvent portion completely soluble in water Resin portion separates out																								
VOC STATEMENT: Maximum VOC as manufactured: 850 Grams/liter (g/l). VOC is a reactive diluent per SCAQMD Rule 1168. When tested per SCAQMD Rule 1168, Test method 316A, VOC emission does not exceed 510 Grams/Liter (g/l). Meets SCAQMD Rule 1168 criteria for PVC Welding.																												
<b>SECTION IV - FIRE AND EXPLOSION HAZARD DATA</b>																												
<b>FLASH POINT</b>		<b>FLAMMABLE LIMITS</b>																										
-4°F (-20°C) T.C.C. Based on THF		(PERCENT BY VOLUME)																										
				LEL																								
				UEL																								
				2.0																								
				11.8																								
<b>FIRE EXTINGUISHING MEDIA</b>																												
Ansul "Purple K" potassium bicarbonate dry chemical, carbon dioxide, National Aer-O-Foam universal alcohol resistant foam, water spray.																												
<b>SPECIAL FIRE FIGHTING PROCEDURES</b>																												
Evacuate enclosed areas. Stay upwind. Close quarters or confined spaces require self-contained breathing apparatus, positive pressure hose masks or airline masks. Use water spray to cool containers, to flush spills from source of ignition and to disperse vapors.																												
<b>UNUSUAL FIRE AND EXPLOSION HAZARDS</b>																												
Fire hazard because of low flash point and high volatility. Vapors are heavier than air and may travel to source(s) of ignition at or near ground or lower level(s) and flash back.																												

## SECTION V - HEALTH HAZARD DATA

### PRIMARY ROUTES

OF ENTRY:       X       Inhalation       X       Skin Contact       X       Eye Contact       X       Ingestion

### EFFECT OF OVEREXPOSURE

ACUTE: Inhalation: Severe overexposure may result in nausea, dizziness, headache. Can cause drowsiness, irritation of eyes and nasal passages.

SKIN CONTACT: Skin irritant. Liquid contact may remove natural skin oils resulting in skin irritation. Dermatitis may occur with prolonged contact.

SKIN ABSORPTION: Prolonged or widespread exposure may result in the absorption of harmful amounts of material.

EYE CONTACT: Overexposure may result in severe eye injury with corneal or conjunctival inflammation on contact with the liquid. Vapors slightly uncomfortable.

INGESTION: Moderately toxic. May cause nausea, vomiting, diarrhea. May cause mental sluggishness.

**CHRONIC:** Symptoms of respiratory tract irritation and damage to respiratory epithelium were reported in rats exposed to 5000 ppm THF of 90 days. Elevation of SGPT suggest a disturbance in liver function. The NOEL was reported to be 200 ppm.

REPRODUCTIVE EFFECTS	TERATOGENICITY	MUTAGENICITY	EMBRYOTOXICITY	SENSITIZATION TO PRODUCT	SYNERGISTIC PRODUCTS
N. AP.	N. AP.	N. AP.	N. AP.	N. AP.	N. AV.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Individuals with pre-existing diseases of the eyes, skin or respiratory system may have increased susceptibility to the toxicity of excessive exposures.

### EMERGENCY AND FIRST AID PROCEDURES

INHALATION: If overcome by vapors, remove to fresh air and if breathing stopped, give artificial respiration. If breathing is difficult, give oxygen. Call Physician.

EYE CONTACT: Flush with plenty of water for 15 minutes and call physician .

SKIN CONTACT: Remove contaminated clothing and shoes. Wash skin with soap and water for at least 15 minutes. If irritation develops, get medical attention.

INGESTION: To conscious person, give 2 glasses of water. Do not induce vomiting and call physician or poison control center immediately.

## SECTION VI - REACTIVITY

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	

### INCOMPATIBILITY

(MATERIALS TO AVOID) Caustics, ammonia, inorganic acids, chlorinated compounds, strong oxidizers and isocyanates.

### HAZARDOUS DECOMPOSITION PRODUCTS

When forced to burn , this product gives out carbon monoxide , carbon dioxide , hydrogen chloride and smoke .

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

## SECTION VII - SPILL OR LEAK PROCEDURES

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Eliminate all ignition sources. Avoid breathing of vapors. Keep liquid out of eyes. Flush with large amount of water. Contain liquid with sand or earth.

Absorb with sand or nonflammable absorbent material and transfer into steel drums for recovery or disposal. Prevent liquid from entering drains.

### WASTE DISPOSAL METHOD

Follow all Local, State and Federal regulations. Consult disposal expert. Can be disposed of by incineration. Excessive quantities should not be permitted to enter drains. Empty containers should be air dried before disposing. Hazardous Waste Code: 214.

## SECTION VIII - SPECIAL PROTECTION INFORMATION

### RESPIRATORY PROTECTION (Specify type)

Atmospheric levels should be maintained below established exposure limits contained in Section II. If airborne concentrations exceed those limits, use of NIOSH approved organic vapor cartridge respirator with full face-piece is recommended. The effectiveness of an air purifying respirator is limited. Use it only for a short-term exposure. For emergency and other conditions where short term exposure guidelines may be exceeded, use an approved positive pressure self-contained breathing apparatus.

### VENTILATION

Use only with adequate ventilation, Provide sufficient ventilation in volume and pattern to keep contamination below applicable exposure limits set forth in section II.

Use only explosion proof ventilation equipment.

PROTECTIVE GLOVES	EYE PROTECTION
PVA coated	Splash proof chemical goggles

### OTHER PROTECTIVE EQUIPMENT AND HYGIENIC PRACTICES

Impervious apron and a source of running water to flush or wash eyes and skin in case of contact.

## SECTION IX - SPECIAL PRECAUTIONS

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store in the shade between 40°F - 110°F (5°C - 43.7°C). Keep away from heat, sparks, open flame and other sources of ignition. Avoid prolonged breathing of vapors.

Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Train employees on all special handling procedures before they work with this product.

### OTHER PRECAUTIONS

Follow all precautionary information given on container label and product bulletins and other literature. All handling equipment should be electrically grounded.

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.