2/19/2024: File reviewed - more current MSDS/SDS not available. CAS

# Majic Town & Country Tractor, Truck & Implement Enamel

#### DESCRIPTION

Majic Town & Country Tractor, Truck and Implement Enamel is a durable, heavy-duty alkyd enamel specially formulated for excellent adhesion, and resistance to weathering and corrosion. It can be applied with brush or spray and dries quickly to a high gloss finish. Use it on iron, steel, aluminum and properly primed galvanized metal.

#### **FEATURES**

- Use on equipment, implements, tools, etc., where a hard enamel finish is desired
- Special heavy-duty alkyd formula
- Excellent adhesion
- Authorized by USDA for use in federally inspected meat and poultry plants

#### VOC / MIR (sprays)

420 gm/l (3.50 lbs/gal)

## **AVAILABLE SIZES**

gallon, quart

## 8-0951 Series



# **NET WEIGHT**

9.20 lbs/gal

#### SHIPPING WT

4-gal case/43.85 lbs 4-qt case/11.75 lbs

# SHIPPING RESTRICTION

Call for Info

#### **AVAILABLE COLORS**

8-0951 IH White, 0952 NH Yel, 0953 Rustic Brwn, 0954 Ford Red, 0955 MF Gray, 0956 NH Red, 0957 New JD Yel, 0958 Case Orange, 0959 Matte Blk, 0961 MF Red, 0962 Cat Yel, 0964 JD Yel, 0965 AC Orange, 0966 JD Green, 0967 Lt Ford Gray, 0968 Ford Blue, 0971 Kubota Orange, 0972 IH Red, 0973 Schl Bus Yel, 0974 Oliver Green, 0979 New Ford/NH Blue, 0983 Case Power Yellow, 0984 Alum, 0990 White, 0994 Blk

#### PRODUCT STATISTICS

DRYTIME-TOUCH	DRYTIME-RECOAT	WET/ FILM THK	FILM THK /DRY:	FINISH	<b>GLOSS</b>	
5 -10 hours	24 hours	2.5 mils	1.3 mils	Gloss/Matte	80+ @ 60°	
FLASHPOINT > 105° F	COVERAGE 600-700 sq ft/gal	VISCOSITY 80 - 85 KU	<b>VEHICLE</b> Alkyd		<b>SOLVENT</b> Mineral Spirits	

# **SURFACE PREP**

Bare Metal: Remove all rust scale with wire brush or sander. Remove oil or grease with paint thinner. Prime with rust-inhibiting primer 8-0986 Tractor Truck & Implement Enamel Gray Primer or 8-0989 Tractor Truck & Implement Enamel Red Oxide Primer. Painted Metal: Remove loose or peeling paint and rust scale with wire brush or sander. Remove oil or grease with paint thinner. Prime any bare metal with rust-inhibiting primer. Painted Surfaces: (General) Make sure surface is clean, dry and free of loose paint, dirt, wax, grease, etc. Sand glossy areas. Spot prime absorbent areas.

#### **APPLICATION**

Stir paint thoroughly. DO NOT THIN. Apply with a high quality brush, roller, paint pad. To spray add one pint of Majic Reducer to each gallon of Majic Town & Country Tractor, Truck & Implement Enamel top coats. Where necessary apply a second coat and allow each coat to dry thoroughly before applying the next coat. Do not apply if surface temperature is below 50° (10°C) or in direct sunlight. On unpainted surfaces, apply two coats for best results, sanding lightly between coats. Allow at least 24 hours after the final coat, before subjecting equipment to heavy use. For additional increase in gloss and hardness, and faster dry time, add Majic Catalyst Hardener 8-0950-4.

#### WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to <a href="https://www.epa.gov/lead">www.epa.gov/lead</a>.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.