Valvoline	Page: 1
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE	Version: 1.1
NP75601	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name

: NAPA® MPURP WHEEL BEARING GREASE GREASE

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet	Emergency telephone number 1-800-VALVOLINE
Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509	Regulatory Information Number 1-800-TEAMVAL
United States of America	Product Information 1-800-TEAMVAL
SDS@valvoline.com	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
---------------------	---	---------

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	Asp. Tox. 1; H304	74.99

Valvoline	Page: 2
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE	Version: 1.1
NP75601	

ASPHALT	Not a hazardous substance or mixture.	24.99
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA	Not a hazardous substance or mixture.	9.99

SECTION 4. FIRST AID MEASURES

General advice	: No hazards which require special first aid measures.	
If inhaled	 If breathed in, move person into fresh air. If unconscious place in recovery position and seek medic advice. If symptoms persist, call a physician. 	al
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.]
In case of eye contact	: Remove contact lenses. Protect unharmed eye.	
If swallowed	 Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. 	
Most important symptoms and effects, both acute and delayed	 Acute aspiration of large amounts of oil-laden material maproduce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the developmer long-term sequelae. Repeated aspiration of small quantit of mineral oil can produce chronic inflammation of the lun (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological charappear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputu occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through irritation (nose, throat, airways) 	nt of ities gs nges im

Valvoline.	Pag	je: 3
SAFETY DATA SHEET	Revision Date: 07/31/2	2016
	Print Date: 9/27/2	2016
	SDS Number: R0172	170
NAPA® MPURP WHEEL BEARING GREASE GREASE	Version:	1.1
NP75601		

Notes to physician

: No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	carbon dioxide and carbon monoxide sulfur oxides Hydrocarbons Aldehydes Ketones Nitrogen oxides (NOx) Sulphur oxides
Specific extinguishing methods	:	
		Product is compatible with standard fire-fighting agents.
Further information	:	Standard procedure for chemical fires.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures		earing protective equipment should be excluded bill until clean-up has been completed.
Environmental precautions	Prevent further	r leakage or spillage if safe to do so.
Methods and materials for containment and cleaning up	icid binder, un	nert absorbent material (e.g. sand, silica gel, iversal binder, sawdust). le, closed containers for disposal.
Other information	Comply with al	I applicable federal, state, and local regulations.

Valvoline.	Page: 4
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE	Version: 1.1
NP75601	

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	:	Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
Conditions for safe storage	:	Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	:	No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	PEL	500 ppm 2,000 mg/m3	OSHA_TRA NS
		REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRA NS
		TWA	5 mg/m3 Mist.	Z1A
		TWA	400 ppm 1,600 mg/m3	Z1A
ASPHALT	8052-42-4	TWA	0.5 mg/m3 Inhalable fraction. (as benzene solubles)	ACGIH
		Ceil_Time	5 mg/m3 Fume.	NIOSH/GUID E
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA	64742-52-5	PEL	500 ppm 2,000 mg/m3	OSHA_TRA NS
		REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRA NS

Components with workplace control parameters

Engineering measures

: General room ventilation should be adequate for normal

Valvoline.	Page: 5
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE	Version: 1.1
NP75601	

	conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.	
Personal protective equipmen Respiratory protection	No personal respiratory protective equipment normally required.	
Eye protection	Not required under normal conditions of use. Wear splash- proof safety goggles if material could be misted or splashed into eyes.	
Skin and body protection	Wear as appropriate:	

Skin and body protection	 Wear as appropriate: Safety shoes Wear resistant gloves (consult your safety equipment supplier).
Hygiene measures	: General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	gel
Physical state	:	liquid
Colour	:	red
Odour	:	No data available
Odour Threshold	:	No data available
рН	:	No data available
Melting point/freezing point	:	No data available
	:	640 °F / 338 °C
Flash point	:	471 °F / 244 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available



NAPA® MPURP WHEEL BEARING GREASE GREASE

NP75601

Vapour pressure	: < 0.01 mmHg (20 °C)
Relative vapour density	: No data available
Relative density	: 0.95 (15.6 °C)
Density	: 0.90 g/cm3 (20 °C)
Solubility(ies) Water solubility	: negligible
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: > 315 °C
Thermal decomposition	: No data available
Viscosity Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20.5 mm2/s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	carbon dioxide and carbon monoxide Hydrocarbons Sulphur oxides

Valvoline.	Page: 7
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE	Version: 1.1
NP75601	

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	: Inhalation Skin contact Eye Contact Ingestion	
Acute toxicity Not classified based on availal <u>Product:</u>		
Acute oral toxicity	: Acute toxicity estimate (Rat): 3,019 mg/kg	
Acute dermal toxicity	: Acute toxicity estimate (Rabbit): 169,492 mg/kg	
<u>Components:</u> DISTILLATES (PETROLEUM) Acute oral toxicity	SOLVENT-DEWAXED HEAVY PARAFFINIC: : LD 50 (Rat): > 5,000 mg/kg	
Acute dermal toxicity	: LD 50 (Rabbit): > 5,000 mg/kg	
DISTILLATES (PETROLEUM) Acute oral toxicity	HYDROTREATED HEAVY NAPHTA: : LD 50 (Rat): > 5 g/kg	
Acute inhalation toxicity	 LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: Not classified as acutely toxic by inhalation under GHS. 	
Acute dermal toxicity	 LD 50 (Rabbit): > 2,000 mg/kg Assessment: Not classified as acutely toxic by dermal absorption under GHS. Remarks: No mortality observed at this dose. 	

Skin corrosion/irritation

Not classified based on available information. Product: Result: Not irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

<u>Components:</u> DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: Result: Mildly irritating to skin

ASPHALT: Result: Not irritating to skin

Page: 8



Revision Date: 07/31/2016

Print Date: 9/27/2016

SDS Number: R0172170 Version: 1.1

NAPA® MPURP WHEEL BEARING GREASE GREASE

NP75601

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA: Species: Rabbit Result: Not irritating to skin

Serious eye damage/eye irritation

Not classified based on available information. **Product:** Result: Not irritating to eyes

Remarks: Unlikely to cause eye irritation or injury.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: Result: Mildly irritating to eyes

ASPHALT: Result: Possibly irritating to eyes

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA: Species: Rabbit Result: Mildly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information. Components: DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA: Species: Guinea pig Assessment: Does not cause skin sensitisation. Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information. **Carcinogenicity** Not classified based on available information. **Reproductive toxicity** Not classified based on available information. **STOT - single exposure** Not classified based on available information. **STOT - repeated exposure** Not classified based on available information. **Aspiration toxicity** Not classified based on available information. **Product:** No aspiration toxicity classification

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: May be fatal if swallowed and enters airways.

Valvoline	Page: 9
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE	Version: 1.1
NP75601	

Further information <u>Product:</u> Remarks: No data available		
Carcinogenicity: IARC	Group 2B: Possibly carcinogenic	to humans
	ASPHALT	8052-42-4
OSHA	No component of this product pr equal to 0.1% is identified as a c carcinogen by OSHA.	
NTP	No component of this product pr equal to 0.1% is identified as a k by NTP.	5

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity			
DISTILLATES (PETROLEUM)	HYDROTREATED HEAVY NAPHTA:		
Toxicity to fish	 LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 		
Toxicity to daphnia and other aquatic invertebrates	 EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202 		
Toxicity to algae	 NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201 		
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	 NOEL (Daphnia (water flea)): 10 mg/l Exposure time: 21 d Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211 		

Persistence and degradability DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:



Page: 10

Revision Date: 07/31/2016

Print Date: 9/27/2016

SDS Number: R0172170 Version: 1.1

NAPA® MPURP WHEEL BEARING GREASE GREASE

NP75601

Biodegradability	: Result: Inherently biodegradable Biodegradation: 31 %
	Exposure time: 28 d Method: OECD Test Guideline 301F

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects No data available

Product:

Additional ecological information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
General advice	: Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	: Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods	

CFR_RAIL_C

No	dangerous	goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Valvoline	Page: 11
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE	Version: 1.1
NP75601	

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant

no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards	No SARA Hazards
SARA 313 : Component(s)SARA 313	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop 65 The components of this produc	Proposition 65 warnings are not required for this product based on the results of a risk assessment.
	3



Version: 1.1

Print Date: 9/27/2016 SDS Number: R0172170

NAPA® MPURP WHEEL BEARING GREASE GREASE

NP75601

TSCA	: On TSCA Inventory
AUSTR	: On the inventory, or in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL.
ENCS	: On the inventory, or in compliance with the inventory
KECL	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2016



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.H304May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

Valvoline	Page: 13
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE	Version: 1.1
NP75601	

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

Valvoline.	Page: 14
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE	Version: 1.1
NP75601	

PMRA : Health Canada Pest Management Regulatory Agency RTK : Right to Know WHMIS : Workplace Hazardous Materials Information System