PENRAY WINTER THAW Safety Data Shoet



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012. Date of issue: 04/16/2014 Revision date: 04/16/2014 Version: 1.0

	ubstance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	: PENRAY WINTER THAW EMERGENCY DIESEL FUEL TREATMENT
Product code	: 202132
1.2. Relevant identified uses of the su	ubstance or mixture and uses advised against
Use of the substance/mixture	: Diesel fuel treatment.
1.3. Details of the supplier of the safe	ty data sheet
The Penray Companies, Inc. 440 Denniston Ct. 60090 Wheeling, IL T (800) 373-6729 rotto@penray.com	
1.4. Emergency telephone number	
Emergency number	: (800) 373-6729 CHEMTREC (800) 424-9300 CHEMTREC International +1 (703) 527-3887 24 hr
SECTION 2: Hazards identification	1
2.1. Classification of the substance o	r mixture
GHS-US classification	
Flammable Liquid 2 Skin irritation 2 Eye irritation 2A Carcinogenicity 1B Specific target organ toxicity - Single exposur Aspiration hazard 1	e 3
2.2. Label elements	
GHS-US labelling	
Hazard pictograms (GHS-US)	GHS02 GHS07 GHS08
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause cancer. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways
Precautionary statements (GHS-US)	: Keep away from heat/sparks/open flames/hot surfaces.– No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. If exposed or concerned: Get medical advice/attention. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Ge medical advice/attention. If you feel unwell. If swallowed: Immediately call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.
2.3. Other hazards	
No additional information available	

Not applicable

EN (English)



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Name	Product identifier	%	GHS-US classification
Kerosene, petroleum	(CAS No) 8008-20-6	40 - 70	Flam. Liq. 3 Skin Irrit. 2 STOT SE 3 Asp. Tox. 1
Isopropyl alcohol	(CAS No) 67-63-0	15 - 40	Flam. Liq. 2 Eye Irrit. 2A STOT SE 3
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	1 - 5	Flam. Liq. 3 Acute Tox. 4 (Dermal, Inhalation) Skin Irrit. 2
Solvent naphtha, petroleum, heavy aromatic	(CAS No) 64742-94-5	0.5 - 1.5	Flam. Liq. 3 Asp. Tox. 1
Naphthalene	(CAS No) 91-20-3	0.1 - 1	Acute Tox. 4 (Oral, Dermal) Carc. 2
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	0.1 - 1	Asp. Tox. 1
Phenylethane	(CAS No) 100-41-4	< 0.1	Flam. Liq. 2 Acute Tox. 4 (Inhalation) Carc. 2
Cumene	(CAS No) 98-82-8	< 0.1	Flam. Liq. 3 Acute Tox. 4 (Oral) Carc. 2

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation	: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
First-aid measures after ingestion	: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never giv anything by mouth to an unconscious person. Get immediate medical advice/attention.
4.2. Most important symptoms and effe	cts, both acute and delayed
Symptoms/injuries after inhalation	: May cause drowsiness, dizziness and central nervous system depression. May cause respirator tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking or the skin.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.
4.3. Indication of any immediate medicate	al attention and special treatment needed

4.3. Indication of any immediate medical attention and special treatment needed Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECT	ION 5: Firefighting meas	sures	
5.1.	Extinguishing media		
Suitable	e extinguishing media	: Powder, water spray, foam, carbon dioxide.	
Unsuita	ble extinguishing media	: Do not use a heavy water stream.	
5.2.	Special hazards arising from	n the substance or mixture	
Fire ha	zard	: Products of combustion may include, and are not limited to: oxides of carbon.	
5.3.	Advice for firefighters		
Protect	on during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.	
SECTION 6: Accidental release measures			
6.1.	6.1. Personal precautions, protective equipment and emergency procedures		
Genera	Imeasures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to	



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

6.2. Methods and materia	al for containment	and cleaning up	
For containment	:		material (e.g. sand, vermiculite), then place in a suitable ow to enter waterways. Use appropriate Personal
Methods for cleaning up	:	Scoop up material and place in a disp	osal container. Provide ventilation.
6.3. Reference to other s	ections		
See section 8 for further information	ation on protective c	lothing and equipment and section 13 f	for advice on waste disposal.
SECTION 7: Handling ar	nd storage		
7.1. Precautions for safe	handling		
Precautions for safe handling	:	breathing gas/mist/vapors/spray. Do r	No smoking. Avoid contact with skin and eyes. Avoid not swallow. Handle and open container with care. Use only ot eat, drink or smoke. Use only outdoors or in a well-
Hygiene measures	:	Launder contaminated clothing before	e reuse. Wash hands before eating, drinking, or smoking.
7.2. Conditions for safe s			
Storage conditions	:	Keep out of the reach of children. Kee Store locked up. Keep cool. Keep awa	p container tightly closed and in a well-ventilated place. ay from heat, sparks, and flame.
7.3. Specific end use(s)			
Not available.			
SECTION 8: Exposure c	ontrols/person	al protection	
8.1. Control parameters			
Kerosene, petroleum (8008-2	20-6)		
USA ACGIH	ACGIH TWA (mg	/m³)	200 mg/m ³
	L		
Isopropyl alcohol (67-63-0) USA ACGIH	ACGIH TWA (ppr	2)	200 ppm
USA ACGIH	ACGIH STEL (pp	,	400 ppm
USA OSHA	OSHA PEL (TWA	,	980 mg/m ³
USA OSHA	OSHA PEL (TWA		400 ppm
) (ppiii)	
Xylenes (o-, m-, p- isomers)	,		
USA ACGIH	ACGIH TWA (ppn		100 ppm
USA ACGIH	ACGIH STEL (pp	m)	150 ppm
USA OSHA	OSHA PEL (TWA	, ()	435 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Naphthalene (91-20-3)			
USA ACGIH	ACGIH TWA (ppr	n)	10 ppm
USA ACGIH	ACGIH STEL (pp	m)	15 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	50 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm
	I		
Phenylethane (100-41-4) USA ACGIH	ACGIH TWA (ppr	2)	20 ppm
USA OSHA	OSHA PEL (TWA	,	435 mg/m ³
USA OSHA	OSHA PEL (TWA	, , ,	100 ppm
034 03114	OSHA FLL (TWA) (ppiii)	
Cumene (98-82-8)	-		
USA ACGIH	ACGIH TWA (ppr		50 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	245 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
8.2. Exposure controls			
Appropriate engineering controls	S :	Use ventilation adequate to keep export recommended exposure limits.	osures (airborne levels of dust, fume, vapor, etc.) below

Personal protective equipment

: Avoid all unnecessary exposure. EN (English)



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Hand protection	: Wear chemically resistant protective gloves.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and o	chemical properties
Physical state	: Liquid
Appearance	: Clear.
Colour	: Amber.
Odour	: Petroleum odor.
Odour threshold	: No data available.
рН	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: ~82 °C (~180 °F) (Isopropyl alcohol)
Flash point	: ~ 13 °C (~ 56 °F)
Self ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Flammable
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: No data available.
Relative density	: 0.795 - 0.825
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.
9.2. Other information	

No additional information available

SECTIO	N 10: Stability and reactivity			
10.1. F	Reactivity			
No danger	rous reaction known under conditions of normal use.			
10.2.	Chemical stability			
Stable und	der normal storage conditions. May form flammable/explosive vapour-air mixture.			
10.3. I	Possibility of hazardous reactions			
No danger	rous reaction known under conditions of normal use.			
10.4.	Conditions to avoid			
Heat. Inco	Heat. Incompatible materials. Open flame.			
10.5. I	Incompatible materials			
Strong oxidizing agents.				
10.6. I	Hazardous decomposition products			
May includ	May include, and are not limited to: oxides of carbon.			
SECTIO	N 11: Toxicological information			
11.1. I	Information on toxicological effects			
Acute toxic	city : Not classified			

EN (English)

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

202132	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 20 mg/l/4h
Kerosene, petroleum (8008-20-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.28 mg/l/4h
Isopropyl alcohol (67-63-0)	
LD50 oral rat	4396 mg/kg
LD50 dermal rat	12800 mg/kg
LD50 dermal rabbit	12870 mg/kg
LC50 inhalation rat (mg/l)	72.6 mg/l/4h
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	4300 mg/kg
LD50 dermal rabbit	>1700 mg/kg
LC50 inhalation rat (ppm)	5000 ppm/4h
LC50 inhalation rat (mg/l)	47635 mg/l/4h
Solvent naphtha, petroleum, heavy aromatic	(64742-94-5)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000mg/kg
LC50 inhalation rat (mg/l)	> 5.28 mg/l/4h
Naphthalene (91-20-3) LD50 oral rat	400 malka
LD50 dermal rabbit	490 mg/kg
	> 20 g/kg
Phenylethane (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15354 mg/kg
LC50 inhalation rat (mg/l)	17.2 mg/l/4h
Cumene (98-82-8)	
LD50 oral rat	1400 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (mg/m ³)	39000 mg/m ³ /4 h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: May cause cancer.
202132	
IARC group	2A (Diesel fuel exhaust)
Isopropyl alcohol (67-63-0)	
IARC group	3
Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3
Naphthalene (91-20-3)	
IARC group	2B
National Toxicity Program (NTP) Status	1, 3
Phenylethane (100-41-4)	
IARC group	2B
National Toxicity Program (NTP) Status	1
Cumene (98-82-8)	
Cumene (98-82-8) IARC group National Toxicity Program (NTP) Status	2B 1

EN (English)



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause drowsiness, dizziness and central nervous system depression. May cause respirator tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information	n
12.1. Toxicity	
Ecology - general	: May cause long-term adverse effects in the aquatic environment.
12.2. Persistence and degradability	
202132	
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
202132	
Bioaccumulative potential	Not established.
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
No additional information available	
SECTION 13: Disposal consideratio	ns
13.1. Waste treatment methods	
Waste disposal recommendations	This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.
Additional information	: Handle empty containers with care because residual vapours are flammable.
SECTION 14: Transport information	
In accordance with DOT	
14.1. UN number	
UN-No.	: UN1993
14.2. UN proper shipping name	
Proper Shipping Name	: Flammable liquids, n.o.s. (Petroleum, Isopropanol)
Department of Transportation Hazard Classes	: 3
Hazard labels	
Packing group (DOT)	: 11
14.3. Additional information	
Other information	: No supplementary information available.
Special transport precautions	: Do not handle until all safety precautions have been read and understood.
SECTION 15: Regulatory informatio	n
SECTION 15: Regulatory informatio 15.1. US Federal regulations	n

Kerosene, petroleum (8008-20-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Isopropyl alcohol (67-63-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
04/16/2014	EN (English)	6/7



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Isopropyl alcohol (67-63-0)			
SARA Section 313 - Emission Reporting	1.0 %		
Xylenes (o-, m-, p- isomers) (1330-20-7)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)			
SARA Section 313 - Emission Reporting	1.0 %		
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
Naphthalene (91-20-3)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)			
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.		
SARA Section 313 - Emission Reporting	0.1 %		
Solvent naphtha, petroleum, light aromatic (64742-95-6)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
Phenylethane (100-41-4)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)			
SARA Section 313 - Emission Reporting	0.1 %		
Cumene (98-82-8)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
Listed on SARA Section 313 (Specific toxic chemical listings)			
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.		
SARA Section 313 - Emission Reporting	1.0 %		
15.2. US State regulations			
202132			
State or local regulations	This product contains chemicals known to the State of California to cause cancer.		
SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:			
IARC International Age	ency for Research on Cancer.		
 1 - Carcinogenic to humans; 2A - Probably carcinogenic to humans; 2B - Possibly carcinogenic to humans; 3 - Not classifiable; 4 - Probably not carcinogenic to humans. 			
NTP National Toxicol			
2 - Known Humar 3 - Reasonably ar 4 - Substances de	 Evidence of Carcinogenicity; Known Human Carcinogens; Reasonably anticipated to be Human Carcinogen; Substances delisted from report on Carcinogens; Twelfth Report - Items under consideration. 		
SECTION 16: Other information			

SECTION 16: Other information

Indication of changes	:	None.
Date of issue	:	04/16/2014
Other information	:	None.
NFPA health hazard	:	2
NFPA fire hazard	:	3
NFPA reactivity	:	0



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

