



Safety Data Sheet

Spartan Chemical Company, Inc.

Revision Date: 10-Aug-2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: WOODFORCE OMU 50 FINISH
Product Number: 5824
Recommended Use: Wood Floor Finish
Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee, Ohio 43537 USA
800-537-8990 (Business hours)
www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171
Transportation/Spill/Leak: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Skin Corrosion/Irritation: Category 2
Serious Eye Damage/Eye Irritation: Category 2B
Skin Sensitization: Category 1
Reproductive Toxicity: Category 2
Specific Target Organ Toxicity (Single Exposure): Category 3
Aspiration Toxicity: Category 1
Flammable Liquids: Category 3

GHS Label Elements

Signal Word:

Symbols:

Warning



Hazard Statements:

Causes skin irritation.
Causes eye irritation.
May cause an allergic skin reaction
Suspected of damaging fertility or the unborn child
May cause respiratory irritation. May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Flammable liquid and vapor.

Precautionary Statements:

Prevention:	Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wear eye / face protection Wear protective gloves Wash hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking Keep container tightly closed Ground container and receiving equipment. Use explosion-proof electrical equipment. Use only non-sparking tools Take precautionary measures against static discharge
Response:	If exposed or concerned: Get medical attention.
-Eyes	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
-Skin	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.
-Inhalation:	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell
-Ingestion:	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting.
-Specific Treatment:	See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.
Fire:	In case of fire: Use CO2, dry chemical, or foam for extinction
Storage:	Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Disposal:	Dispose of contents and container in accordance with local, state and federal regulations.
Hazards Not Otherwise Classified:	Not Applicable
Other Information:	<ul style="list-style-type: none"> • May be harmful if swallowed. • Contains petroleum distillates. Possible aspiration hazard. • Keep out of reach of children.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
petroleum distillates	64742-47-8	30-60
urethane modified alkyd resin	PROPRIETARY	30-60
urethane modified long oil alkyd	PROPRIETARY	3-7
zirconium carboxylate	22464-99-9	0.1-1
methyl ethyl ketoxime	96-29-7	0.1-1

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Eye Contact:	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
-Skin Contact:	Take off contaminated clothing. Wash with soap and water. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.
-Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison control center or physician if you feel unwell.
-Ingestion:	IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Do NOT induce vomiting.
Note to Physicians:	Contains petroleum distillates. Possible aspiration hazard.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:	Carbon dioxide, Dry chemical, Alcohol resistant foam
Specific Hazards Arising from the Chemical:	Vapors may travel to source of ignition and flash back.
Hazardous Combustion Products:	May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.
Protective Equipment and Precautions for Firefighters:	Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Cool fire-exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Remove all sources of ignition. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.
Environmental Precautions:	Do not rinse spill onto the ground, into storm sewers or bodies of water.
Methods for Clean-Up:	Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13). Immediately place absorbent material in a sealed water-filled metal container to avoid spontaneous combustion of absorbent material contaminated with this product.

7. HANDLING AND STORAGE

Advice on Safe Handling:	Handle in accordance with good industrial hygiene and safety practice. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. All equipment used when handling the product must be grounded. Use spark-proof tools and explosion-proof equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Rags, towels or mops soaked with this product are subject to spontaneous combustion if not handled properly. Thoroughly rinse these materials with water to remove product before disposal or discard in special containers designed for this purpose. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
Storage Conditions:	Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep out of the reach of children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
zirconium carboxylate 22464-99-9	STEL: 10 mg/m ³ Zr TWA: 5 mg/m ³ Zr	TWA: 5 mg/m ³ Zr (vacated) TWA: 5 mg/m ³ Zr (vacated) STEL: 10 mg/m ³ Zr	IDLH: 25 mg/m ³ Zr TWA: 5 mg/m ³ except Zirconium tetrachloride Zr STEL: 10 mg/m ³ Zr

Engineering Controls:	Provide good general ventilation. If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be considered.
Personal Protective Equipment	
Eye/Face Protection:	Wear splash goggles.
Skin and Body Protection:	Wear solvent-resistant gloves. The use of other protective equipment such as solvent-resistant boots should be considered in order to prevent or minimize contact with this product.
Respiratory Protection:	Ensure adequate ventilation, especially in confined areas If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section 3 should be considered. Respirator selection must be made by a technically qualified person who is familiar with the specific work conditions.

General Hygiene Considerations: Wash hands and any exposed skin thoroughly after handling.
See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid
Color:	light brown
Odor:	Sweet Resinous
pH:	Not applicable
Melting Point / Freezing Point:	No information available.
Boiling Point / Boiling Range:	No information available. 540-640
Flash Point:	43 °C / 109 °F
Evaporation Rate:	< 1 (BuAc = 1)
Flammability (solid, gas)	No information available.
Upper Flammability Limit:	No information available.
Lower Flammability Limit:	No information available.
Vapor Pressure:	No information available.
Vapor Density:	No information available.
Specific Gravity:	0.868
Solubility(ies):	Insoluble in water
Partition Coefficient:	No information available.
Autoignition Temperature:	No information available.
Decomposition Temperature:	No information available.
Viscosity:	No information available.

10. STABILITY AND REACTIVITY

Reactivity: This material is considered to be non-reactive under normal conditions of use.
Chemical Stability: Stable under normal conditions.
Possibility of Hazardous Reactions: Not expected to occur with normal handling and storage.
Conditions to Avoid: Heat, flames and sparks.
Incompatible Materials: Strong oxidizing agents. Strong acids.
Hazardous Decomposition Products: May include carbon monoxide, carbon dioxide (CO₂) and other toxic gases or vapors.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eyes, Skin, Ingestion, Inhalation.
Symptoms of Exposure:
-Eye Contact: Pain, redness and swelling of the conjunctiva.
-Skin Contact: Pain, redness and cracking of the skin. May cause sensitization by skin contact
-Inhalation: May cause irritation of respiratory tract. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Nasal discomfort and coughing.
-Ingestion: Pain, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Immediate, Delayed, Chronic Effects
Product Information: Data not available or insufficient for classification.

Target Organ Effects: Central nervous system. -Eyes. kidney. Respiratory System. -Skin.

Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral): 10211 mg/kg
 ATEmix (dermal): 4084 mg/kg

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
petroleum distillates 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h

methyl ethyl ketoxime 96-29-7	= 930 mg/kg (Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat) 4 h
----------------------------------	---------------------	------------------------	-----------------------

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
petroleum distillates 64742-47-8	Not Available	45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static	Not Available	4720: 96 h Den-dronereides heteropoda mg/L LC50
methyl ethyl ketoxime 96-29-7	83: 72 h Desmodemus subspicatus mg/L EC50	777 - 914: 96 h Pimephales promelas mg/L LC50 flow-through 320 - 1000: 96 h Leuciscus idus mg/L LC50 static 760: 96 h Poecilia reticulata mg/L LC50 static	Not Available	750: 48 h Daphnia magna mg/L EC50

Persistence and Degradability: No information available.

Bioaccumulation: No information available.

Other Adverse Effects: No information available.

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes: Dispose of in accordance with federal, state and local regulations.

Contaminated Packaging: Dispose of in accordance with federal, state and local regulations.

US EPA Waste Number: D001

14. TRANSPORT INFORMATION

DOT:

UN/ID No: UN1993
Proper Shipping Name: Flammable liquids, n.o.s., (contains petroleum distillates)
Hazard Class: 3
Packing Group: III
Special Provisions: Class 3, Packing Group III materials meet the exception requirements of section 49 CFR 173.150 when individual containers of not more than 1.3 gallons are packed in a strong outer packaging and ground transportation is utilized. Such containers may be reclassified as "Limited Quantity".
 Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation expert for information specific to your situation.

IMDG:

UN/ID No: UN1993
Proper Shipping Name: Flammable liquids, n.o.s., (contains petroleum distillates)
Hazard Class: 3
Packing Group: III

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product does not contain listed substances above the "de minimus" level

SARA 311/312 Hazard Categories

Acute Health Hazard:	Yes
Chronic Health Hazard:	Yes
Fire Hazard:	Yes
Sudden release of pressure hazard:	No
Reactive Hazard:	No

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION

NFPA	Health Hazards: 2	Flammability: 2	Instability: 0	Special: N/A
HMIS	Health Hazards: 2*	Flammability: 2	Physical Hazards: 0	

Revision Date: 10-Aug-2015
 Reasons for Revision: Section 14 and 15

Disclaimer:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet