		Page: 1
SAFETY DATA SHEET		Revision Date: 01/09/2019
		Print Date: 12/5/2022
		SDS Number: R0172415
Valvoline™ MP 2-CYCLE TC-W3 Motor Oil		Version: 2.3
VV460		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ MP 2-CYCLE TC-W3 Motor Oil

<p>Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825)</p> <p>SDS@valvoline.com</p>	<p>Emergency telephone number 1-800-VALVOLINE (1-800-825-8654)</p> <p>Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825)</p> <p>Product Information 1-800-TEAMVAL (1-800-832-6825)</p>
--	--


SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 4

Skin irritation : Category 2

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : Combustible liquid.
Causes skin irritation.

Precautionary Statements : **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Wash skin thoroughly after handling.
Wear protective gloves/ eye protection/ face protection.
Response:
IF ON SKIN: Wash with plenty of soap and water.

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 12/5/2022

SDS Number: R0172415

Valvoline™ MP 2-CYCLE TC-W3 Motor Oil

Version: 2.3

VV460

If skin irritation occurs: Get medical advice/ attention.
 Take off contaminated clothing and wash before reuse.
 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Static-accumulating flammable liquid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	Not a hazardous substance or mixture.	>=30.00 - < 40.00
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	Flam. Liq. 4; H227 Skin Irrit. 2; H315	>=20.00 - < 30.00
RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED	64742-01-4	Not a hazardous substance or mixture.	>=20.00 - < 30.00
Naphtha (petroleum), heavy aromatic	64742-94-5	Asp. Tox. 1; H304	>=1.50 - < 5.00

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
 If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
 If on skin, rinse well with water.



SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 12/5/2022

SDS Number: R0172415

Valvoline™ MP 2-CYCLE TC-W3 Motor Oil

Version: 2.3


VV460

Wash contaminated clothing before re-use.
If on clothes, remove clothes.

- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
Causes skin irritation.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO2)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
nitrogen oxides (NOx)
Hydrocarbons
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use a water spray to cool fully closed containers.

		Page: 4
SAFETY DATA SHEET		Revision Date: 01/09/2019
		Print Date: 12/5/2022
		SDS Number: R0172415
Valvoline™ MP 2-CYCLE TC-W3 Motor Oil		Version: 2.3
VV460		

Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.
Suppress (knock down) gases/vapours/mists with a water spray jet.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
No smoking.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
------------	---------	------------	---------	-------

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 12/5/2022

SDS Number: R0172415

Valvoline™ MP 2-CYCLE TC-W3 Motor Oil

Version: 2.3

VV460

		(Form of exposure)	parameters / Permissible concentration	
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC	64741-88-4	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC	64742-94-5	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 12/5/2022

SDS Number: R0172415

Valvoline™ MP 2-CYCLE TC-W3 Motor Oil

Version: 2.3

VV460

Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : < -38 °F / < -39 °C

Boiling point/boiling range : > 356 °F / 180 °C
(1013 hPa)

Flash point : 196 °F / 91 °C

Evaporation rate : 0.1
butyl acetate=1

Flammability (solid, gas) : No data available

Flammability (liquids) : Static-accumulating flammable liquid.

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : 6.0 %(V)

Lower explosion limit / Lower flammability limit : 1.0 %(V)

Vapour pressure : 0.2 mmHg (68 °F / 20 °C)

Relative vapour density : No data available

Relative density : No data available

Density : Average 0.8550 g/cm³ (68 °F / 20 °C)

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 12/5/2022

SDS Number: R0172415

Valvoline™ MP 2-CYCLE TC-W3 Motor Oil

Version: 2.3

VV460

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 36.8 mm²/s (104 °F / 40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.
None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation

Skin contact

Eye Contact

Ingestion

Acute toxicity

Not classified based on available information.

Components:**Distillates, petroleum, solvent-refined heavy paraffinic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 12/5/2022

SDS Number: R0172415

Valvoline™ MP 2-CYCLE TC-W3 Motor Oil

Version: 2.3

VV460

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Assessment: Not classified as acutely toxic by inhalation under GHS.
 Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
 Remarks: No mortality observed at this dose.

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.28 mg/l
 Exposure time: 4 h
 Test atmosphere: vapour
 Method: OECD Test Guideline 403
 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
 Assessment: No adverse effect has been observed in acute dermal toxicity tests.

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
 Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: Not classified as acutely toxic by inhalation under GHS.
 Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Naphtha (petroleum), heavy aromatic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 3,800 mg/m3
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Assessment: Not classified as acutely toxic by inhalation under GHS.

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 12/5/2022

SDS Number: R0172415

Valvoline™ MP 2-CYCLE TC-W3 Motor Oil

Version: 2.3

VV460

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:
Distillates, petroleum, solvent-refined heavy paraffinic:

Species : Rabbit
Result : No skin irritation

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Assessment : Irritating to skin.
Result : Irritating to skin.

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Species : Rabbit
Result : No skin irritation

Naphtha (petroleum), heavy aromatic:

Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:
Distillates, petroleum, solvent-refined heavy paraffinic:

Species : Rabbit
Result : No eye irritation

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Species : Rabbit
Result : Slight, transient irritation

Respiratory or skin sensitisation
Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:
Distillates, petroleum, solvent-refined heavy paraffinic:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

**SAFETY DATA SHEET**

Revision Date: 01/09/2019

Print Date: 12/5/2022

SDS Number: R0172415

Valvoline™ MP 2-CYCLE TC-W3 Motor Oil

Version: 2.3

VV460

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Genotoxicity in vitro : Test Type: Ames test
Result: negative

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:**Distillates, petroleum, solvent-refined heavy paraffinic:**

No aspiration toxicity classification

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

No aspiration toxicity classification

Naphtha (petroleum), heavy aromatic:

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET	Revision Date: 01/09/2019
	Print Date: 12/5/2022
	SDS Number: R0172415
Valvoline™ MP 2-CYCLE TC-W3 Motor Oil VV460	Version: 2.3

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 203
 Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l
 Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
 Exposure time: 21 d
 Test substance: WAF
 Method: OECD Test Guideline 211

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 12/5/2022

SDS Number: R0172415

Valvoline™ MP 2-CYCLE TC-W3 Motor Oil

Version: 2.3

VV460

Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Scud (Gammarus pulex)): > 10,000 mg/l
 Exposure time: 48 h
 Test Type: semi-static test
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 201

Persistence and degradability

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:
 Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 - 4 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:
 Biodegradability : Result: Inherently biodegradable
 Biodegradation: 58.6 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F

RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:
 Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 - 4 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B
 Remarks: Information given is based on data obtained from similar substances.

No data available

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available



SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 12/5/2022

SDS Number: R0172415

Valvoline™ MP 2-CYCLE TC-W3 Motor Oil

Version: 2.3

VV460

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS


Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

		Page: 14
SAFETY DATA SHEET		Revision Date: 01/09/2019
		Print Date: 12/5/2022
		SDS Number: R0172415
Valvoline™ MP 2-CYCLE TC-W3 Motor Oil		Version: 2.3
VV460		

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant		no
------------------	--	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Hazard not otherwise classified (physical hazards)
Skin corrosion or irritation

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

SAFETY DATA SHEET

Revision Date: 01/09/2019

Print Date: 12/5/2022

SDS Number: R0172415

Valvoline™ MP 2-CYCLE TC-W3 Motor Oil

Version: 2.3

VV460

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TCSI : Not in compliance with the inventory


TSCA list

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 01/09/2019


<p>NFPA:</p>  <p style="text-align: center;">Special hazard.</p>	<p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: yellow;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	2	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	2						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIA

Full text of H-Statements

- H227 Combustible liquid.
- H304 May be fatal if swallowed and enters airways.

		Page: 16
SAFETY DATA SHEET		Revision Date: 01/09/2019
		Print Date: 12/5/2022
		SDS Number: R0172415
Valvoline™ MP 2-CYCLE TC-W3 Motor Oil		Version: 2.3
VV460		

H315 Causes skin irritation.


Sources of key data used to compile the Safety Data Sheet
 Valvoline internal data including own and sponsored test reports
 The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

	Page: 17
SAFETY DATA SHEET	Revision Date: 01/09/2019
	Print Date: 12/5/2022
	SDS Number: R0172415
Valvoline™ MP 2-CYCLE TC-W3 Motor Oil VV460	Version: 2.3

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System