

**1. Identification**

**Product identifier** 450 GYM FINISH

**Other means of identification**

**SDS number** 552N-97A

**Product code** HIL00284

**Recommended use** Gym Finish

**Recommended restrictions** For Labeled Use Only

**Manufacturer/Importer/Supplier/Distributor information**

**Manufacturer**

**Company name** HILLYARD INDUSTRIES

**Address** 302 North Fourth St.

St. Joseph, MO 64501

**Contact person** Regulatory Affairs

**Telephone number** (816) 233-1321 (Ext. 8285)

**Fax** (816) 383-8485

**E-mail** regulatoryaffairs@hillyard.com

**Emergency telephone #** (800) 424-9300

(Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals)

**2. Hazard(s) identification**

**Physical hazards** Flammable liquids Category 3

**Health hazards** Acute toxicity, inhalation Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2B

Sensitization, skin Category 1

Germ cell mutagenicity Category 1B

Carcinogenicity Category 1B

Specific target organ toxicity, repeated exposure Category 1

**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 3

Hazardous to the aquatic environment, long-term hazard Category 3

**OSHA defined hazards** Not classified.

**Label elements**



**Signal word** Danger

**Hazard statement** Flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Causes damage to organs (central nervous system) through prolonged or repeated exposure. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

### Response

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use appropriate media to extinguish.

### Storage

Keep container tightly closed. Keep cool. Store locked up.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law in compliance with applicable federal, state and local requirements.

### Hazard(s) not otherwise classified (HNOC)

None known.

### Supplemental information

NOTICE: Saw dust from freshly sanded floors or dust from wood floors that have been abraded between coats will spontaneously catch fire if improperly discarded. Immediately after abrading or sanding wood floors, place dust waste in a sealed, water-filled metal container and immediately remove from building.

NOTICE: Rags or applicators soaked in a combustible liquid will spontaneously catch fire if improperly discarded. Immediately after using rags or applicators soaked in a combustible liquid, place waste in a sealed, water-filled metal container and immediately remove from building.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvent with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Use With Adequate Ventilation. Avoid breathing vapors or spray mist. Open windows and doors, use exhaust fans or other means to insure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

Spill and Waste: Remove all sources of ignition. Ventilate and remove with inert absorbent. Incinerate in approved facility. Do not incinerate closed container. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Light Aromatic Hydrocarbons		8052-41-3	40 - < 50
C9-15 Heavy Aromatic Hydrocarbons		64742-95-6	1 - < 3
Xylene		1330-20-7	1 - < 3
Ethyl Benzene		100-41-4	< 0.3
Other components below reportable levels			50 - < 60

## 4. First-aid measures

### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a poison center or doctor/physician if you feel unwell.

### Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

### Ingestion

Rinse mouth thoroughly. Get medical attention if symptoms occur.

### Most important symptoms/effects, acute and delayed

Dizziness. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
<b>5. Fire-fighting measures</b>	
<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Flammable liquid and vapor.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water. Prevent product from entering drains.  Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.  Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe the mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
<b>Conditions for safe storage, including any incompatibilities</b>	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Ethyl Benzene (CAS 100-41-4)	PEL	435 mg/m <sup>3</sup>
		100 ppm
Light Aromatic Hydrocarbons (CAS 8052-41-3)	PEL	2900 mg/m <sup>3</sup>
		500 ppm
Xylene (CAS 1330-20-7)	PEL	435 mg/m <sup>3</sup>
		100 ppm

#### US. ACGIH Threshold Limit Values

Components	Type	Value
Ethyl Benzene (CAS 100-41-4)	TWA	20 ppm
Light Aromatic Hydrocarbons (CAS 8052-41-3)	TWA	100 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Ethyl Benzene (CAS 100-41-4)	STEL	545 mg/m <sup>3</sup>
		125 ppm
	TWA	435 mg/m <sup>3</sup> 100 ppm
Light Aromatic Hydrocarbons (CAS 8052-41-3)	Ceiling	1800 mg/m <sup>3</sup>
	TWA	350 mg/m <sup>3</sup>
Xylene (CAS 1330-20-7)	STEL	655 mg/m <sup>3</sup> 150 ppm
		TWA

### Biological limit values

#### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethyl Benzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

### Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

## Individual protection measures, such as personal protective equipment

<b>Eye/face protection</b>	Avoid contact with eyes. Chemical splash goggles where there is a potential for eye contact.
<b>Skin protection</b>	
<b>Hand protection</b>	Wear appropriate chemical resistant gloves.
<b>Other</b>	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
<b>Respiratory protection</b>	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor cartridge.
<b>Thermal hazards</b>	None known.

**General hygiene considerations** Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

<b>Appearance</b>	Clear, amber liquid
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Amber
<b>Odor</b>	Solvent odor
<b>Odor threshold</b>	Not available
<b>pH</b>	Not applicable
<b>Melting point/freezing point</b>	Not applicable / Not available
<b>Initial boiling point and boiling range</b>	335 °F (168.33 °C)
<b>Flash point</b>	> 100.0 °F (> 37.8 °C) Setafash
<b>Evaporation rate</b>	< 1 Ethyl ether = 1
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	2.9 mm Hg
<b>Vapor density</b>	4.8145 AIR=1
<b>Relative density</b>	0.897 at 77°F
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Negligible
<b>Partition coefficient (n-octanol/water)</b>	Not available
<b>Auto-ignition temperature</b>	Not available
<b>Decomposition temperature</b>	Not available
<b>Viscosity</b>	Not available
<b>Other information</b>	
<b>Density</b>	7.42 lb/gal
<b>Explosive properties</b>	Not explosive.
<b>Oxidizing properties</b>	Not oxidizing.
<b>Percent volatile</b>	49 - 50 %
<b>VOC</b>	< 450 g/l

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.

<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong acids. Strong oxidizing agents. Halogens.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Harmful if inhaled.
<b>Skin contact</b>	Causes skin irritation. May cause an allergic skin reaction.
<b>Eye contact</b>	Causes eye irritation.
<b>Ingestion</b>	Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics** Dizziness. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

### Information on toxicological effects

**Acute toxicity** Harmful if inhaled.

Product	Species	Test Results
---------	---------	--------------

450 GYM FINISH

**Acute**

**Dermal**

LD50	Rabbit	269800 mg/kg
------	--------	--------------

**Oral**

LD50	Rat	91050 mg/kg
------	-----	-------------

Components	Species	Test Results
------------	---------	--------------

Ethyl Benzene (CAS 100-41-4)

**Acute**

**Dermal**

LD50	Rabbit	17800 mg/kg
------	--------	-------------

**Oral**

LD50	Rat	3500 mg/kg
------	-----	------------

Xylene (CAS 1330-20-7)

**Acute**

**Dermal**

LD50	Rabbit	> 43 g/kg
------	--------	-----------

**Inhalation**

LC50	Rat	6350 mg/l, 4 Hours
------	-----	--------------------

**Oral**

LD50	Rat	3523 - 8600 mg/kg
------	-----	-------------------

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/eye irritation** Causes eye irritation.

### Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity** May cause genetic defects.

**Carcinogenicity** May cause cancer.

### IARC Monographs. Overall Evaluation of Carcinogenicity

Ethyl Benzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not listed.

**US. National Toxicology Program (NTP) Report on Carcinogens**

Not listed.

<b>Reproductive toxicity</b>	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Not an aspiration hazard.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

**12. Ecological information****Ecotoxicity** Harmful to aquatic life with long lasting effects.

Product	Species	Test Results
450 GYM FINISH		
<b>Aquatic</b>		
Crustacea	EC50 Daphnia	747.236, 48 hours
Fish	LC50 Fish	790.0172, 96 hours
<i>Acute</i>		
Crustacea	EC50 Daphnia	192.1408, 48 hours estimated
Fish	LC50 Fish	119.1792, 96 hours estimated
<b>Components</b>		
Ethyl Benzene (CAS 100-41-4)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50 Water flea (Daphnia magna)	>= 1.37 - <= 4.4 mg/l, 48 hours
Fish	LC50 Atlantic silverside (Menidia menidia)	>= 4.4 - <= 5.7 mg/l, 96 hours
Xylene (CAS 1330-20-7)		
<b>Aquatic</b>		
<i>Acute</i>		
Fish	LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss)	>= 6.702 - <= 10.032 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of this product.**Bioaccumulative potential****Partition coefficient n-octanol / water (log Kow)**

Ethyl Benzene 3.15

**Mobility in soil** No data available.**Other adverse effects** The product contains volatile organic compounds which have a photochemical ozone creation potential.**13. Disposal considerations****Disposal instructions** Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.**Local disposal regulations** Dispose in accordance with all applicable regulations.**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F  
D018: Waste Benzene

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products**

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Notice: Saw dust from freshly sanded floors or dust from wood floors that have been abraded between coats will spontaneously catch fire if improperly discarded. Immediately after abrading or sanding wood floors, place dust waste in a sealed, water-filled metal container and immediately remove from building. Notice: Rags or applicators soaked in a combustible liquid will spontaneously catch fire if improperly discarded. Immediately after using rags or applicators soaked in a combustible liquid, place waste in a sealed, water-filled metal container and immediately remove from building.

**Contaminated packaging**

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. Transport information**

**DOT**

Not regulated as dangerous goods.  
Not Regulated For Ground Transportation.

**IATA**

<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	Flammable
<b>Packing group</b>	III
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	128
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.

**IMDG**

<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	Flammable
<b>Packing group</b>	III
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	F-E, S-E
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

**IATA; IMDG**



**15. Regulatory information**

**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.



**Toxic Substances Control Act (TSCA)**

One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Ethyl Benzene (CAS 100-41-4)

Listed.

Xylene (CAS 1330-20-7)

Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)****SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical**

Yes

**Classified hazard categories**

Flammable (gases, aerosols, liquids, or solids)  
Acute toxicity (any route of exposure)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Respiratory or skin sensitization  
Germ cell mutagenicity  
Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Ethyl Benzene	100-41-4	< 0.3
Xylene	1330-20-7	1 - < 3

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Ethyl Benzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)**

Contains component(s) regulated under the Safe Drinking Water Act.

**US state regulations****US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

C9-15 Heavy Aromatic Hydrocarbons (CAS 64742-95-6)

Ethyl Benzene (CAS 100-41-4)

Light Aromatic Hydrocarbons (CAS 8052-41-3)

Xylene (CAS 1330-20-7)

**California Proposition 65**

**WARNING:** This product can expose you to chemicals including Ethyl Benzene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). This product can expose you to Ethyl Benzene, which is known to the State of California to cause cancer.

**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Ethyl Benzene (CAS 100-41-4)

Listed: June 11, 2004

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 04-17-2015  
**Revision date** 09-23-2021  
**Version #** 04  
**HMIS® ratings** Health: 3\*  
Flammability: 3  
Physical hazard: 0

**Disclaimer** No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or disposal of these products.

**Revision information** This document has undergone significant changes and should be reviewed in its entirety.