

34

ACTIVA Products, Inc.

MATERIAL SAFETY DATA SHEET

7/24/2024: File reviewed. More current MSDS/SDS not available. CAS

DATE OF PREPARATION March 24, 1986

The information contained herein is based on data available to us and is believed to be correct. Since this information may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and Buyer may rely thereon only at Buyer's risk. We make no guarantee that the health and safety precautions we have suggested will be adequate for all individuals and/or situations involving its handling and use. No warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof.
 Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet.

Section I

MANUFACTURER'S NAME Activa Products, Inc.

STREET ADDRESS 288 Littleton Rd. CITY, STATE, AND ZIP CODE Westford, MA 01886
Gateway #24

EMERGENCY TELEPHONE NO.
(508) 692-9300

PRODUCT CLASS

MANUFACTURER'S CODE IDENTIFICATION

Adhesive

TRADE NAME

DOT PROPER SHIPPING NAME Not a regulated material.

Section II - HAZARDOUS INGREDIENTS

INGREDIENT/CAS NUMBER	PERCENTAGE RANGE	OSHA PEL	ACGIH TLV	LEL	VAPOR PRESSURE mm Hg. 20°C
This product does not contain regulated levels of hazardous ingredients as defined in 29 CFR 1910.1200.					

NA - NOT APPLICABLE

Section III - PHYSICAL DATA

NE - NOT ESTABLISHED

BOILING RANGE >200°F pH 4.5 PERCENT VOLATILE BY WEIGHT 47 WEIGHT PER GALLON 9.1 lbs.

Section IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT

NA

EXTINGUISHING MEDIA

Liquid material - non-flammable. Use water spray, foam, dry chemical or carbon dioxide on dried product.

UNUSUAL FIRE AND EXPLOSION HAZARDS

There is the possibility of pressure build-up in closed containers when heated. Water spray may be used to cool the containers.

EFFECTS OF OVEREXPOSURE

ACUTE

Eye contact may cause irritation. Prolonged or repeated skin contact with liquid product may cause irritation.

CHRONIC

No anticipated chronic effects.

FIRST AID PROCEDURES

EYES: Flush immediately with large amounts of water for at least 15 minutes. Consult a physician if irritation persists. SKIN: Wash contact area with soap and water.

INHALATION: Remove to fresh air.

Section IV - REACTIVITY DATA

STABILITY UNSTABLE STABLE CONDITIONS TO AVOID

INCOMPATIBILITY (Materials to avoid) Not established.

HAZARDOUS COMBUSTION PRODUCTS

Incomplete combustion can yield low molecular weight hydrocarbons and carbon monoxide.

HAZARDOUS POLYMERIZATION MAY OCCUR WILL NOT OCCUR

CONDITIONS TO AVOID

NA

Section VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Contain and remove with inert absorbent. Keep spill out of sewers.

WASTE DISPOSAL METHOD This product does not meet the definition of hazardous waste under 40 CFR 261. Solidify and dispose of in an approved industrial landfill; consult your state or local authorities in the event more restrictive requirements apply.

Section VIII - SPECIAL PROTECTION INFORMATION

EYE PROTECTION

Safety glasses.

SKIN PROTECTION

Rubber gloves recommended for prolonged or repeated contact with product.

Remove and launder contaminated clothing before reuse.

RESPIRATORY PROTECTION

Not normally required.

VENTILATION

Standard industrial ventilation.

Section IX - ADDITIONAL INFORMATION

Note: The product does contain limited amounts of residual monomer. Under conditions of normal handling and use the residual monomer does not present a hazard. Monomer vapors released into the workplace atmosphere when emulsions are heat cured or dried may present a health problem if good ventilation is not used.

In storage the monomer will migrate from the emulsion and establish an equilibrium between the headspace in the storage container and the liquid emulsion. Levels in excess of acceptable exposures can accumulate in non-vented headspaces above the emulsion. Bulk storage tanks should be vented with humidified air. All procedures appropriate for a confined space entry should be completed prior to performing any work in a bulk storage tank.

Note: The product does contain trace amounts of formaldehyde. Under typical use conditions for this product applicable exposure guidelines will not be exceeded.