

MATERIAL SAFETY DATA SHEET

Date Issued: 12/16/2011
 MSDS No: LS1006
 Date Revised: 08/14/2012
 Revision No: 2

Ronson® Butane Fuel Refill

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Ronson® Butane Fuel Refill
PRODUCT DESCRIPTION: Butane Refill
PRODUCT CODE: 99142
CHEMICAL FAMILY: Alkane
GENERIC NAME: Butane

3/4/2024: more current MSDS/SDS not available.
 CAS

MANUFACTURER

Ortho Technology, Inc.
 17401 Commerce Park Boulevard
 Tampa, FL 33647
Product Stewardship: 1-800-999-3161

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC : 1-800-424-9300

2. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT(S)	CAS	Wt.%
Isobutane	75-28-5	60 - 100

See Section 8 for Exposure Limits

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Clear odorless gas in in aerosol container

POTENTIAL HEALTH EFFECTS

SKIN ABSORPTION: No absorption through the skin.

INGESTION: Product does not lend itself to ingestion.

INHALATION: Not considered carcinogenic. Variable simple asphixyant / anesthetic.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

INHALATION: Non toxic, but may displace oxygen in air. No apparent ill effects in breathing concentration of 5% for 2 hours. Causes drowsiness in a short time in concentrations of 1%.

ACUTE TOXICITY: Nausea, vomiting, coughing and pulmonary irritation.

CHRONIC EFFECTS: Dizziness, weakness, peripheral numbness and nervousness.

MEDICAL CONDITIONS AGGRAVATED: Respiratory related chronic illnesses (i.e. asthma, etc.)

ROUTES OF ENTRY: Inhalation only

4. FIRST AID MEASURES

SKIN: Contact with liquid can freeze tissue, similar to thermal burn. May cause frostbite.

NOTES TO PHYSICIAN: Simple Asphixyant / Frost Bite.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: (-120°F) Closed Cup

FLAMMABLE LIMITS: 1.8 to 9.5

MATERIAL SAFETY DATA SHEET

Date Issued: 12/16/2011
 MSDS No: LS1006
 Date Revised: 08/14/2012
 Revision No: 2

Ronson® Butane Fuel Refill

Notes: In Air Volume %

AUTOIGNITION TEMPERATURE: Not Available

FLAMMABLE CLASS: Flammable gas Hazard class 2.1

EXTINGUISHING MEDIA: Carbon Dioxide, dry chemical, mist or water spray.

EXPLOSION HAZARDS: Moderate

FIRE FIGHTING PROCEDURES: Confine fire to immediate area; disperse liquid or vapor if spill occurs; shut off source of leak if possible.

FIRE EXPLOSION: Fire hazard - dangerous

HAZARDOUS DECOMPOSITION PRODUCTS: None except asphyxiation by displacement.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Remove all ignition sources. If applicable stop leak. Disperse vapors with water spray. No smoking, flames or flares in hazard area. Isolate hazard area and deny entry of non qualified emergency response personnel.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Product is highly flammable and forms explosive mixtures with air, oxygen and all oxidizing agents. Avoid high temperatures that may elevate component pressure above container rating. Use and store this product with adequate ventilation; Use non sparking tools; electrically ground all equipment and lines; use explosion proof equipment (Class I group D, Division 1 & 2)

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

HAZARDOUS COMPONENTS					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³
Isobutane	TWA	N/A	N/A	800 ppm	N/A

ENGINEERING CONTROLS: Ventilation: Local exhaust to meet exposure limits Class I Group D, Division 1 & 2 (NEC)

PERSONAL PROTECTIVE EQUIPMENT

SKIN: Gloves: Impermeable type - nitrile rubber.

RESPIRATORY: None

PROTECTIVE CLOTHING: To prevent repeated or prolonged skin contact, wear impervious clothing.

WORK HYGIENIC PRACTICES: Availability of eyewash and safety shower station recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Clear odorless gas

VAPOR PRESSURE: 31 psig @ 70F

MATERIAL SAFETY DATA SHEET

Date Issued: 12/16/2011
MSDS No: LS1006
Date Revised: 08/14/2012
Revision No: 2

Ronson® Butane Fuel Refill

VAPOR DENSITY: 2.0068 (Air =1)
BOILING POINT: @ 1 ATM 10.90F
MELTING POINT: NA = Not Applicable
POUR POINT: NA = Not Applicable
SOLUBILITY IN WATER: Slight
EVAPORATION RATE: (Butyl Acetate = 1) NA = Not Applicable
SPECIFIC GRAVITY: (H₂O = 1) 0.5624
(VOC): 100.000 %

10. STABILITY AND REACTIVITY

STABILITY: Stable.
POLYMERIZATION: Will not occur
HAZARDOUS DECOMPOSITION PRODUCTS: None except asphyxiation by displacement.
INCOMPATIBLE MATERIALS: Reacts vigorously with oxidizing materials

11. TOXICOLOGICAL INFORMATION

ACUTE

INHALATION LC₅₀: 52 Vol % in Air

NOTES: Acute Inhalation of Isobutane:
LC₀ 32 Vol % in Air
LC₁₀₀ 65 Vol % in Air
Animal : Laboratory Rats

TERATOGENIC EFFECTS:

 Teratogenic Studies

Modified Ames Test

Isobutane not teratogenic under test conditions, six-hour exposure, followed by incubation for 42 additional Hours before scoring.

GENERAL COMMENTS:

 Caradic Arrhythmia due to Inhalation of Isobutane:

Concentration Threshold 10 + 20 Vol %

Animal : monkey, mice, dogs

Concentration to produce cardiac arrest - Not determined (cardiac arrest will occur with total exposure and oxygen deprivation.)

COMMENTS: Non toxic, but may displace oxygen in air.

12. ECOLOGICAL INFORMATION

COMMENTS: Not Available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose in accordance with local, state, and federal regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Butane

MATERIAL SAFETY DATA SHEET

Date Issued: 12/16/2011
 MSDS No: LS1006
 Date Revised: 08/14/2012
 Revision No: 2

Ronson® Butane Fuel Refill

PRIMARY HAZARD CLASS/DIVISION: Flammable Gas 2.1

UN/NA NUMBER: UN 1011

PLACARDS: Flammable Gas/1011

LABEL: FLAMMABLE GAS

OTHER SHIPPING INFORMATION: Shipping Containers: Cartons

VESSEL (IMO/IMDG)

SHIPPING NAME: Butane

UN/NA NUMBER: UN 1011

PRIMARY HAZARD CLASS/DIVISION: Flammable Gas 2.1

PLACARDS: Flammable Gas / 1011

LABEL: DOT / IMO Label

15. REGULATORY INFORMATION

16. OTHER INFORMATION

REASON FOR ISSUE: New MSDS Format

APPROVED BY: J. Hutchins **TITLE:** QA/RA Director

PREPARED BY: T. Swan


INFORMATION CONTACT: 1-800-999-3161

REVISION SUMMARY: This MSDS replaces the 08/14/2012 MSDS. Revised: Section 16: HMIS RATING (HEALTH, PHYSICAL HAZARD).

HMIS RATING

HEALTH	<input type="checkbox"/>	1
FLAMMABILITY	<input type="checkbox"/>	4
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input type="checkbox"/>	

NFPA CODES



MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.