

6/24/2024: File reviewed; more current MSDS/SDS not available. CAS

All Scribbles except Neon 731

AUG 14 2014
103-3400 thru 103-3755
103-4400 thru 103-4490

1404966



MATERIAL SAFETY DATA SHEET

Identity Duncan Scribbles SC 100, SC 200, SC300-316, [redacted] Res MSDS # 703

SECTION I

Manufacturer's Name Duncan Enterprises
Address 5673 E. Shields Ave. Fresno, CA 93727
Emergency Telephone Number (209) 445-1222
Telephone Number (209) 291-4444
Date Prepared August 1987 Revised January 1992
Prepared By Curt Sathre
HMIS Codes Health 0 Reactivity 0
Fire 1 Protective Equip. G (if spraying)

SECTION II
HAZARDOUS INGREDIENTS

Hazardous Components OSHA PEL ACGIH TLV CAS # %
none

Other Information
none

SECTION III
PHYSICAL DATA

Boiling Point, (DEG°F) 212°F Vapor Pressure, (MM HG.) n/a
Melting Point, (DEG°F) n/a Vapor Density (AIR=1) Less than 1 water
Specific Gravity (Water=1): 1.1 Water Solubility, % Insoluble
Appearance And Odor Opaque colored latex paint Freezing Point n/a
pH 8.0 - 9.0 Evaporation Rate (Butyl Acetate=1) Less than 1 water

103-3400a, thru 103-3755a
103-4400a, thru 103-4490a

MSDS 703

SECTION VII
PRECAUTIONS FOR SAFE HANDLING

Steps To Be Taken In Case Material Is Released Or Spilled

Clean up properly with paper towels and a wet sponge.

Waste Disposal Method

Put paper towels in trash and rinse out sponge. Follow Federal, State and Local regulations for disposal.

Precautions To Be Taken In Handling And Storing

Keep container sealed.

Other Precautions

n/a

SECTION VIII
CONTROL MEASURES

Respiratory Protection (Specify Type)

If spraying, do not inhale mist. Use respirator that is NIOSH approved for sprays and mists.

Ventilation

Local Exhaust

Recommended

Mechanical (General)

Recommended when spraying

Protective Gloves

no

Other Protective Clothing Or Equipment

None needed

Work/Hygienic Practices

Good hygiene practices should be followed.

Special

Use respirator when spraying

Other

none

Eye Protection

Safety glasses with side shields. Do not wear contact lenses.

SECTION IX
ADDITIONAL INFORMATION

CALIFORNIA Proposition 65

n/a



"Products bearing the Nontoxic Product Seal are certified in a program to toxicological evaluation by a nationally recognized toxicologist to contain no materials in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems. These products are certified to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4238. In addition, there is no physical hazard as defined within 29 CFR Part 1910.1200(c)."

DISCLAIMER -- Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Since conditions of use are beyond our control, we make no warranties, expressed or implied.

103-3400 B-THU 103375
103-4400 B-THU 103-4400

MSDS 703

SECTION IV
FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used) n/a Flammable Limits LEL n/a UEL n/a
Extinguishing Media Use appropriate techniques and media for surrounding fire.
Special Fire Fighting Procedures None.
Unusual Fire And Explosion Hazards Material can spatter above 212°F. Polymer film can burn.

SECTION V
REACTIVITY DATA

Stability Unstable: Stable: X
Conditions To Avoid n/a
Incompatibility (Materials To Avoid) n/a
Hazardous Decomposition or Byproducts n/a
Hazardous Polymerisation May Occur: Will Not Occur: X
Conditions To Avoid n/a

SECTION VI
HEALTH HAZARD DATA

Routes Of Entry Inhalation? no Skin? no Ingestion? no
Health Hazards (Acute and Chronic) None. Nontoxic
Carcinogenicity NTP? no IARC Monographs? no OSHA Regulated? no
Signs And Symptoms of Exposure n/a
Medical Conditions Generally Aggravated by Exposure Abrasive, can scratch eyes.
Emergency And First Aid Procedures Eye contact: Flush with water at least 15 minutes. Skin contact: Wash with soap and water.