		Page: 1
SAFETY DATA SHEET		Revision Date: 08/01/2019
		Print Date: 3/27/2023
		SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV614		Version: 1.4

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ Multi-Vehicle Multi-Purpose Red Grease
™ Trademark, Valvoline or its subsidiaries, registered in various countries

<p>Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825)</p> <p>SDS@valvoline.com</p>	<p>Emergency telephone number 1-800-VALVOLINE (1-800-825-8654)</p> <p>Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825)</p> <p>Product Information 1-800-TEAMVAL (1-800-832-6825)</p>
---	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
DIPHENYLAMINE	122-39-4	Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311	>=0.50 - < 1.00



SAFETY DATA SHEET

Revision Date: 08/01/2019

Print Date: 3/27/2023

SDS Number: R0172170

Version: 1.4

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV614

		Eye Irrit. 2A; H319	
		STOT RE 2; H373	

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
 If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
 Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO2)
 Dry chemical
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known



SAFETY DATA SHEET

Revision Date: 08/01/2019

Print Date: 3/27/2023

SDS Number: R0172170

Version: 1.4

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV614

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
 Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.

Conditions for safe storage : Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parameters /	Basis
------------	---------	---------------------	----------------------	-------



SAFETY DATA SHEET

Revision Date: 08/01/2019

Print Date: 3/27/2023

SDS Number: R0172170

Version: 1.4

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV614

		exposure)	Permissible concentration	
DIPHENYLAMINE	122-39-4	TWA	10 mg/m3	ACGIH
		TWA	10 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0
		PEL	10 mg/m3	CAL PEL

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
 Safety shoes
 Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : gel
- Colour : light brown
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : 640 °F / 338 °C
- Flash point : 491 °F / 255 °C

**SAFETY DATA SHEET**

Revision Date: 08/01/2019

Print Date: 3/27/2023

SDS Number: R0172170

Version: 1.4

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
VV614

Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	not determined
Relative vapour density	:	No data available
Relative density	:	0.95 (60.1 °F / 15.6 °C)
Density	:	0.898 g/cm ³ (68 °F / 20 °C)
Solubility(ies)		
Water solubility	:	negligible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Ignition temperature	:	> 599 °F / > 315 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm ² /s (104 °F / 40 °C)
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	Stable under recommended storage conditions.
Possibility of hazardous reactions	:	Product will not undergo hazardous polymerization.
Conditions to avoid	:	None known.

**SAFETY DATA SHEET**

Revision Date: 08/01/2019

Print Date: 3/27/2023

SDS Number: R0172170

Version: 1.4

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
VV614

Incompatible materials : None known.

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate (Rat): 3,019 mg/kg

Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate (Rabbit): 169,492 mg/kg
Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:**DIPHENYLAMINE:**

Acute oral toxicity : LD50 (Guinea pig): 300 mg/kg

Acute inhalation toxicity : Assessment: The component/mixture is classified as acute inhalation toxicity, category 3.

Acute dermal toxicity : Assessment: The component/mixture is classified as acute dermal toxicity, category 3.


Skin corrosion/irritation

Not classified based on available information.

Product:

Assessment : No skin irritation

Result : No skin irritation

	Page: 7
SAFETY DATA SHEET	Revision Date: 08/01/2019
	Print Date: 3/27/2023
	SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV614	Version: 1.4

Components:

DIPHENYLAMINE:

Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : No eye irritation

Assessment : No eye irritation

Remarks : Unlikely to cause eye irritation or injury.

Components:

DIPHENYLAMINE:

Result : Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

DIPHENYLAMINE:

Exposure routes : Ingestion

Target Organs : Kidney, Liver

Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

Revision Date: 08/01/2019

Print Date: 3/27/2023

SDS Number: R0172170

Version: 1.4

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 VV614

Product:

No aspiration toxicity classification

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Long-term (chronic) aquatic hazard : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Components:

DIPHENYLAMINE:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.27 - 0.36 mg/l
 Exposure time: 48 h
 Test Type: semi-static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): Estimated 2.17 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): Estimated 0.37 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Method: OECD Test Guideline 201

Ecotoxicology Assessment Short-term (acute) aquatic hazard : Acute aquatic toxicity Category 1; Very toxic to aquatic life.

Long-term (chronic) aquatic hazard : Chronic aquatic toxicity Category 1; Very toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

DIPHENYLAMINE:

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 26 %
 Exposure time: 28 d

**SAFETY DATA SHEET**

Revision Date: 08/01/2019

Print Date: 3/27/2023

SDS Number: R0172170

Version: 1.4

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
VV614

Method: OECD Test Guideline 301D

No data available

Bioaccumulative potential**Components:**

DIPHENYLAMINE:

Bioaccumulation

: Species: Pimephales promelas (fathead minnow)
Bioconcentration factor (BCF): 30
Exposure time: 32 d
Concentration: 0.0437 mg/l
Method: Flow through

No data available

Mobility in soil**Components:**

No data available

Other adverse effects

No data available

Product:Additional ecological
information

: An environmental hazard cannot be excluded in the event of
unprofessional handling or disposal., Harmful to aquatic life
with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

General advice

: Dispose of in accordance with all applicable local, state and
federal regulations.

The product should not be allowed to enter drains, water
courses or the soil.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste
handling site for recycling or disposal.


SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

		Page: 10
SAFETY DATA SHEET		Revision Date: 08/01/2019
		Print Date: 3/27/2023
		SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV614		Version: 1.4

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.


SARA 311/312 Hazards : No SARA Hazards

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : Not in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : Not in compliance with the inventory
- PICCS : Not in compliance with the inventory
- IECSC : Not in compliance with the inventory
- TCSI : Not in compliance with the inventory
- TSCA : On TSCA Inventory

		Page: 11
SAFETY DATA SHEET		Revision Date: 08/01/2019
		Print Date: 3/27/2023
		SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV614		Version: 1.4

TSCA list

No substances are subject to TSCA 12(b) export notification requirements.


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 08/01/2019

<p>NFPA:</p> <div style="text-align: center;"> <p>Flammability</p>  <p>Health Instability</p> <p>Special hazard.</p> </div>	<p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	0	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	0						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						


NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

- H301 Toxic if swallowed.
- H311 Toxic in contact with skin.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

		Page: 12
SAFETY DATA SHEET		Revision Date: 08/01/2019
		Print Date: 3/27/2023
		SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV614		Version: 1.4


The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency

	Page: 13
SAFETY DATA SHEET	Revision Date: 08/01/2019
	Print Date: 3/27/2023
	SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV614	Version: 1.4

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System