

7/16/2024: File reviewed, more current MSDS/SDS not available. CAS

00623-1006

SAFETY DATA SHEET

11/30/2020

SECTION I - IDENTIFICATION

Material Name
DICK BLICK ACRYLIC REMOVER
Company Information

For transportation emergencies only call: 608-968-6873
For health emergencies call the Poison Control Center: 1-800-222-1222

SECTION II - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.
Eye Irritation - Category 2
Flammable Liquid 2

GHS Label Elements**Symbol(s)**

Signal Word(s)
Danger

Hazard Statement(s)
Causes serious eye irritation
Highly flammable liquid and vapour

Precautionary Statement(s)

Prevention
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Keep cool. Ground and bond container and receiving equipment. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place.

Response
Get medical advice/attention. Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Rinse skin with water [or shower]. Take off immediately all contaminated clothing.

SECTION III - HAZARDOUS INGREDIENTS

Hazardous Ingredients	CAS/EC #	PEL/TLV (MG/M#)	Max % Weight	NTP	IARC
ISOPROPYL ALCOHOL	67-63-0	983.00	100.00000	N	N

SECTION IV - FIRST AID MEASURES

FIRST AID MEASURES: If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care. If swallowed, get prompt medical attention.

SECTION V - FIRE FIGHTING MEASURES

FLASH POINT (METHOD): 54 F AUTOIGNITION TEMPERATURE: N/A
 EXPLOSION LIMITS IN AIR (% BY VOLUME): NOT EXPLOSIVE
 EXTINGUISHING MEDIA: NO SPECIAL MEDIA REQUIRED
 FIRE FIGHTING PROCEDURES: NO SPECIAL FIRE FIGHTING PROCEDURES REQUIRED
 UNUSUAL FIRE & EXPLOSION HAZARDS: FLAMMABLE. HIGHLY FLAMMABLE

SECTION VI - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE A MATERIAL IS SPILLED: Clean up in accordance with all applicable regulations. Absorb spillage with non-combustible, absorbent material. For waste disposal, see Section XIII

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN DURING STORAGE AND HANDLING: Good industrial hygiene practice requires that exposure be maintained below the TLV. This is preferably achieved through the provision of adequate ventilation. When exposure cannot be adequately controlled in this way, personal respiratory protection should be employed.

SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION AND SPECIAL VENTILATION REQUIREMENTS: Use only with adequate ventilation.
 OTHER PROTECTIVE EQUIPMENT (GLOVES, GOGGLES, ETC): NONE REQUIRED
 WORK/HYGIENE PRACTICES: Keep away from eyes. Avoid ingestion.
 ENGINEERING CONTROLS: Do not store or use near heat or flame. KEEP OUT OF REACH OF CHILDREN.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: N/A MELTING POINT: N/A
 VAPOR PRESSURE: N/A FLASH POINT (METHOD): 54 F
 SPECIFIC VAPOR DENSITY (AIR=1): N/A SPECIFIC GRAVITY: N/A
 SOLUBILITY IN WATER: N/A REACTIVITY IN WATER: NON-REACTIVE

SECTION X - STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION PRODUCTS: N/A
 STABILITY: STABLE CONDITIONS TO AVOID: N/A
 INCOMPATIBILITY (MATERIALS TO AVOID): N/A
 HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide and smoke

SECTION XI - TOXICOLOGICAL INFORMATION

ACUTE EFFECTS ASSOCIATED WITH USE OF THIS MATERIAL: EYE IRRITANT. MAY BE HARMFUL IF SWALLOWED. CONTACT MAY RESULT IN REDNESS OR PAIN OF THE EYES.
The summated LD50 is 4500.0 mg/kg.

This product is not considered to be a known or suspected human carcinogen by NTP, IARC or OSHA (see section III)

SECTION XII - ECOLOGICAL INFORMATION

HARMFUL EFFECTS KNOWN OTHER THAN THOSE ASSOCIATED WITH SUSPENDED INERT SOLIDS IN WATER.

SECTION XIII - DISPOSAL CONSIDERATIONS

RCRA HAZARD CLASS (40 CFR 261): THIS PRODUCT IS NOT CLASSIFIED AS A HAZARDOUS WASTE.
WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION XIV - TRANSPORTATION INFORMATION

DOT:
UN-No: UN1219
Hazard class: 3
Packing Group: II

SECTION XV - REGULATORY INFORMATION

CONTENTS OF THIS SDS COMPLY WITH OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200

EPA SARA TITLE III CHEMICAL LISTINGS:
SECTION 302.4 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355):
NONE

SECTION 313 TOXIC CHEMICALS (40 CFR 372):
NONE

INTERNATIONAL REGULATIONS

CANADIAN WHMIS: THIS PRODUCT IS A CONTROLLED PRODUCT UNDER CANADA'S WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM. IT CONTAINS THE FOLLOWING TOXIC OR HIGHLY TOXIC MATERIALS:
ISOPROPYL ALCOHOL

Under CPSC's consumer product regulations (16CFR1500.3 and 150014), this product has the following required acute and chronic hazard labeling:

WARNING: FLAMMABLE. MAY BE HARMFUL IF SWALLOWED. EYE IRRITANT.
Contains: ISOPROPYL ALCOHOL

PRECAUTIONS: Keep away from eyes. Avoid ingestion. Do not store or use near heat or flame. Use only with adequate ventilation. **KEEP OUT OF REACH OF CHILDREN.**

FIRST AID TREATMENT: If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care. If swallowed, get prompt medical attention.

SECTION XVI - OTHER INFORMATION

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

LAST REVISION DATE: 11/30/2020

Prepared by Duke OEM Toxicology

BRAND NAMES

THIS SDS APPLIES TO THE FOLLOWING BRAND NAMES

Brand Name
DICK BLICK ACRYLIC REMOVER
