



# SAFETY DATA SHEET

## 1. Identification

<b>Product identifier</b>	<b>Mass Air Flow Sensor Cleaner</b>
<b>Other means of identification</b>	
<b>Product Code</b>	No. 05110 (Item# 1003729)
<b>Recommended use</b>	Mass air flow sensor cleaner
<b>Recommended restrictions</b>	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Manufactured or sold by:</b>	
<b>Company name</b>	CRC Industries, Inc.
<b>Address</b>	885 Louis Dr. Warminster, PA 18974 US
<b>Telephone</b>	
<b>General Information</b>	215-674-4300
<b>Technical Assistance</b>	800-521-3168
<b>Customer Service</b>	800-272-4620
<b>24-Hour Emergency (CHEMTREC)</b>	800-424-9300 (US)
<b>Website</b>	www.crcindustries.com

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
<b>Health hazards</b>	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2B
	Reproductive toxicity	Category 1A
	Specific target organ toxicity, single exposure	Category 1 (central nervous system, eyes)
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes eye irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. Causes damage to organs (central nervous system, eyes). Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

### Response

If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed: Call a poison center/doctor. Collect spillage.

### Storage

Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

### Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

### Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

### Supplemental information

None.

---

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
naphtha (petroleum), hydrotreated light		64742-49-0	50 - 60
2-methylpentane		107-83-5	20 - 30
carbon dioxide		124-38-9	5 - 10
n-hexane		110-54-3	3 - 5
methanol		67-56-1	2 - 4
n-pentane		109-66-0	1 - 3
2,2,4-trimethylpentane		540-84-1	< 1
2,2-dimethylbutane		75-83-2	< 1
2,3-dimethylbutane		79-29-8	< 1
3-methylpentane		96-14-0	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

---

## 4. First-aid measures

### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

### Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

### Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

### Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**General information** IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

---

## 5. Fire-fighting measures

**Suitable extinguishing media** Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical** Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**Fire-fighting equipment/instructions** In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

**General fire hazards** Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

---

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

**Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

---

## 7. Handling and storage

**Precautions for safe handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

**Conditions for safe storage, including any incompatibilities**

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

**8. Exposure controls/personal protection****Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
2,2,4-trimethylpentane (CAS 540-84-1)	PEL	2350 mg/m3
		500 ppm
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3
		5000 ppm
methanol (CAS 67-56-1)	PEL	260 mg/m3
		200 ppm
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	400 mg/m3
		100 ppm
n-hexane (CAS 110-54-3)	PEL	1800 mg/m3
		500 ppm
n-pentane (CAS 109-66-0)	PEL	2950 mg/m3
		1000 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
2,2-dimethylbutane (CAS 75-83-2)	STEL	1000 ppm
	TWA	500 ppm
2,3-dimethylbutane (CAS 79-29-8)	STEL	1000 ppm
	TWA	500 ppm
2-methylpentane (CAS 107-83-5)	STEL	1000 ppm
	TWA	500 ppm
3-methylpentane (CAS 96-14-0)	STEL	1000 ppm
	TWA	500 ppm
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
n-hexane (CAS 110-54-3)	TWA	50 ppm
n-pentane (CAS 109-66-0)	TWA	1000 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

<b>Components</b>	<b>Type</b>	<b>Value</b>
2,2,4-trimethylpentane (CAS 540-84-1)	Ceiling	1800 mg/m3 385 ppm
	TWA	350 mg/m3 75 ppm
	Ceiling	1800 mg/m3 510 ppm
2,2-dimethylbutane (CAS 75-83-2)	TWA	350 mg/m3 100 ppm
	Ceiling	1800 mg/m3 510 ppm
	TWA	350 mg/m3 100 ppm
2,3-dimethylbutane (CAS 79-29-8)	Ceiling	1800 mg/m3 510 ppm
	TWA	350 mg/m3 100 ppm
	Ceiling	1800 mg/m3 510 ppm
2-methylpentane (CAS 107-83-5)	TWA	350 mg/m3 100 ppm
	Ceiling	1800 mg/m3 510 ppm
	TWA	350 mg/m3 100 ppm
3-methylpentane (CAS 96-14-0)	Ceiling	1800 mg/m3 510 ppm
	TWA	350 mg/m3 100 ppm
	STEL	54000 mg/m3 30000 ppm
carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3 5000 ppm
	STEL	325 mg/m3 250 ppm
	TWA	260 mg/m3 200 ppm
methanol (CAS 67-56-1)	TWA	400 mg/m3 100 ppm
	TWA	180 mg/m3 50 ppm
	Ceiling	1800 mg/m3 610 ppm
n-pentane (CAS 109-66-0)	TWA	350 mg/m3 120 ppm

**Biological limit values**

**ACGIH Biological Exposure Indices**

<b>Components</b>	<b>Value</b>	<b>Determinant</b>	<b>Specimen</b>	<b>Sampling Time</b>
methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
n-hexane (CAS 110-54-3)	0.5 mg/l	2,5-Hexanedione, without hydrolysis	Urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines****US - California OELs: Skin designation**

methanol (CAS 67-56-1)  
n-hexane (CAS 110-54-3)

Can be absorbed through the skin.  
Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

methanol (CAS 67-56-1)

Skin designation applies.

**US - Tennessee OELs: Skin designation**

methanol (CAS 67-56-1)

Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

methanol (CAS 67-56-1)  
n-hexane (CAS 110-54-3)

Can be absorbed through the skin.  
Can be absorbed through the skin.

**US NIOSH Pocket Guide to Chemical Hazards: Skin designation**

methanol (CAS 67-56-1)

Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC). Viton/butyl.

**Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

---

**9. Physical and chemical properties****Appearance****Physical state**

Liquid.

**Form**

Aerosol.

**Color**

Colorless.

**Odor**

Alcoholic.

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point/freezing point**

-144 °F (-97.8 °C) estimated

**Initial boiling point and boiling range**

123 °F (50.6 °C) estimated

**Flash point**

< 0 °F (< -17.8 °C)

**Evaporation rate**

Very fast.

**Flammability (solid, gas)**

Not available.

### Upper/lower flammability or explosive limits

Flammability limit - lower (%) 0.9 % estimated

Flammability limit - upper (%) 36 % estimated

Vapor pressure 3215.5 hPa estimated

Vapor density > 1 (air = 1)

Relative density 0.7 estimated

### Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 489.2 °F (254 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Percent volatile 95 % estimated

---

## 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

**Possibility of hazardous reactions** No dangerous reaction known under conditions of normal use.

**Conditions to avoid** Heat, flames and sparks. Contact with incompatible materials.

**Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition products** Carbon oxides. Formaldehyde.

---

## 11. Toxicological information

### Information on likely routes of exposure

**Inhalation** May cause damage to organs by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

**Skin contact** Causes skin irritation.

**Eye contact** Causes eye irritation.

**Ingestion** Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Symptoms related to the physical, chemical and toxicological characteristics** Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain.

### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways.

Components	Species	Test Results
2,2,4-trimethylpentane (CAS 540-84-1)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	118 mg/l, 4 Hours
carbon dioxide (CAS 124-38-9)		
<b>Acute</b>		
<b>Inhalation</b>		
Gas		
LC50	Rat	470000 ppm, 30 minutes

Components	Species	Test Results
methanol (CAS 67-56-1)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	12800 mg/kg
<b>Oral</b>		
LD50	Rat	5628 mg/kg
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	61 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
n-hexane (CAS 110-54-3)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 1300 mg/kg
<b>Oral</b>		
LD50	Rat	15840 mg/kg
n-pentane (CAS 109-66-0)		
<b>Acute</b>		
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	364 mg/m3, 4 Hours
<b>Oral</b>		
LD50	Rat	> 2000 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Causes eye irritation.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	Not classifiable as to carcinogenicity to humans.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Not listed.		
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)</b>		
Not regulated.		
<b>US. National Toxicology Program (NTP) Report on Carcinogens</b>		
Not listed.		
<b>Reproductive toxicity</b>	May damage fertility or the unborn child.	
<b>Specific target organ toxicity - single exposure</b>	Causes damage to organs (central nervous system, eyes). May cause drowsiness and dizziness.	
<b>Specific target organ toxicity - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure.	
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.	
<b>Chronic effects</b>	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.	



---

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.  
**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

### Bioaccumulative potential

#### Partition coefficient n-octanol / water (log Kow)

2,2,4-trimethylpentane	5.18
2,2-dimethylbutane	3.82
2,3-dimethylbutane	3.42
2-methylpentane	3.74
3-methylpentane	3.6
methanol	-0.77
n-hexane	3.9
n-pentane	3.39

#### Bioconcentration factor (BCF)

naphtha (petroleum), hydrotreated light	10 - 25000
-----------------------------------------	------------

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

---

## 13. Disposal considerations

**Disposal instructions** If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Contents under pressure. Do not puncture, incinerate or crush. Dispose in accordance with all applicable regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## 14. Transport information

### DOT

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Special precautions for user</b>	Not available.
<b>Special provisions</b>	N82
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	None
<b>Packaging bulk</b>	None

### IATA


<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>ERG Code</b>	10L
<b>Special precautions for user</b>	Not available.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.

### IMDG


<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS, Limited Quantity

**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Packing group** Not applicable.  
**Environmental hazards**  
**Marine pollutant** No.  
**EmS** Not available.  
**Special precautions for user** Not available.

DOT; IMDG



IATA



---

## 15. Regulatory information

**US federal regulations** All components are on the U.S. EPA TSCA Inventory List.  
This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)**

Not regulated.

**US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance**

methanol (CAS 67-56-1)

n-hexane (CAS 110-54-3)

**CERCLA Hazardous Substance List (40 CFR 302.4)**

2,2,4-trimethylpentane (CAS 540-84-1) Listed.

methanol (CAS 67-56-1) Listed.

n-hexane (CAS 110-54-3) Listed.

n-pentane (CAS 109-66-0) Listed.

**CERCLA Hazardous Substances: Reportable quantity**

2,2,4-trimethylpentane (CAS 540-84-1) 1000 LBS

methanol (CAS 67-56-1) 5000 LBS

n-hexane (CAS 110-54-3) 5000 LBS

n-pentane (CAS 109-66-0) 100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

2,2,4-trimethylpentane (CAS 540-84-1)

methanol (CAS 67-56-1)  
n-hexane (CAS 110-54-3)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

n-pentane (CAS 109-66-0)

**Safe Drinking Water Act (SDWA)** Not regulated.

**Food and Drug Administration (FDA)** Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)  
Gas under pressure  
Acute toxicity (any route of exposure)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard  
Hazard not otherwise classified (HNOC)

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** Yes

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
methanol	67-56-1	2 - 4
n-hexane	110-54-3	3 - 5

**US state regulations**

**US. New Jersey Worker and Community Right-to-Know Act**

2,2,4-trimethylpentane (CAS 540-84-1)  
2,2-dimethylbutane (CAS 75-83-2)  
2,3-dimethylbutane (CAS 79-29-8)  
2-methylpentane (CAS 107-83-5)  
carbon dioxide (CAS 124-38-9)  
methanol (CAS 67-56-1)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-hexane (CAS 110-54-3)  
n-pentane (CAS 109-66-0)

**US. Massachusetts RTK - Substance List**

2,2,4-trimethylpentane (CAS 540-84-1)  
2,2-dimethylbutane (CAS 75-83-2)  
2,3-dimethylbutane (CAS 79-29-8)  
2-methylpentane (CAS 107-83-5)  
3-methylpentane (CAS 96-14-0)  
carbon dioxide (CAS 124-38-9)  
methanol (CAS 67-56-1)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-hexane (CAS 110-54-3)  
n-pentane (CAS 109-66-0)

**US. Pennsylvania Worker and Community Right-to-Know Law**

2,2,4-trimethylpentane (CAS 540-84-1)  
2,2-dimethylbutane (CAS 75-83-2)  
2,3-dimethylbutane (CAS 79-29-8)  
2-methylpentane (CAS 107-83-5)  
3-methylpentane (CAS 96-14-0)  
carbon dioxide (CAS 124-38-9)  
methanol (CAS 67-56-1)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-hexane (CAS 110-54-3)  
n-pentane (CAS 109-66-0)

**US. Rhode Island RTK**

2,2,4-trimethylpentane (CAS 540-84-1)

carbon dioxide (CAS 124-38-9)  
methanol (CAS 67-56-1)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-hexane (CAS 110-54-3)  
n-pentane (CAS 109-66-0)

### California Proposition 65



**WARNING:** Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

#### California Proposition 65 - CRT: Listed date/Developmental toxin

methanol (CAS 67-56-1) Listed: March 16, 2012

#### California Proposition 65 - CRT: Listed date/Male reproductive toxin

n-hexane (CAS 110-54-3) Listed: December 15, 2017

#### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2,2,4-trimethylpentane (CAS 540-84-1)  
methanol (CAS 67-56-1)  
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
n-hexane (CAS 110-54-3)  
n-pentane (CAS 109-66-0)

#### Volatile organic compounds (VOC) regulations

##### EPA

**VOC content (40 CFR 51.100(s))** 95 %

**Consumer products (40 CFR 59, Subpt. C)** Not regulated

##### State

**Consumer products** Not regulated

**VOC content (CA)** 95 %

**VOC content (OTC)** 95 %

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

---

## 16. Other information, including date of preparation or last revision

**Issue date** 06-30-2014  
**Revision date** 08-01-2018  
**Prepared by** Allison Yoon  
**Version #** 03  
**Further information** CRC # 1750769

**Disclaimer**

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

**Revision information**

This document has undergone significant changes and should be reviewed in its entirety.