

Issue date 19-Jul-2018

Revision date 06-Jul-2023

Revision Number 4

1. IDENTIFICATION

Product identification

Product identifier Drummond™ Remedy AC/Refrigeration Coil and Fin Cleaner
Other means of identification DA7040
Recommended use Cleaner
Restrictions on use For industrial use only

Supplier

Corporate Headquarters:
Drummond™, A Lawson Brand
Lawson Products, Inc.
8770 W. Bryn Mawr Ave., Suite 900
Chicago, IL 60631
(866) 837-9908

Canadian Distribution Center:
Lawson Canada
7315 Rapistan Court
Mississauga, ON L5N 5Z4
(800) 323-5922

24 Hour Emergency Phone Number (888) 426-4851 (Prosar)

Website www.lawsonproducts.com

Methylene Chloride notification No Information Available

2. HAZARD(S) IDENTIFICATION

Hazard Classification This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS 2015 and GHS Regulations.

| | |
|-----------------------------------|-------------|
| Serious eye damage/eye irritation | Category 2A |
| Skin sensitization | Category 1 |
| Flammable aerosols | Category 1 |

Symbol



Signal word DANGER

Hazard statements
H222 - Extremely flammable aerosol
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation

Precautionary statements

| | |
|--|--|
| Prevention | <p>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 - Do not spray on an open flame or other ignition source</p> <p>P251 - Pressurized container: Do not pierce or burn, even after use</p> <p>P261 - Avoid breathing dust/fume/gas/mist/vapors/spray</p> <p>P264 - Wash hands thoroughly after handling</p> <p>P272 - Contaminated work clothing should not be allowed out of the workplace</p> <p>P280 - Wear protective gloves/protective clothing and eye/face protection</p> |
| Response | |
| Eyes | <p>P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing</p> <p>P337 + P313 - If eye irritation persists: Get medical advice/attention</p> |
| Skin | <p>P302 + P352 - IF ON SKIN: Wash with plenty of water.</p> <p>P332 + P313 - If skin irritation occurs: Get medical advice/attention</p> <p>P363 - Wash contaminated clothing before reuse</p> |
| Storage | P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F |
| Disposal | P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable |
| Hazard(s) Not Otherwise Classified (HNOC) | None known. |
| Physical Hazards Not Otherwise Classified (PHNOC) | None known. |
| Unknown acute toxicity | None known. |

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition Mixture.

| Chemical name | CAS-No | Weight % |
|------------------------------|------------|----------|
| D-Limonene | 5989-27-5 | 2.5-10 |
| Propane | 74-98-6 | 1 - 2.5 |
| Butane | 106-97-8 | 1 - 2.5 |
| Alcohols, C9-11, ethoxylated | 68439-46-3 | 1-3 |

Chemical Additions Other components below reportable levels. 90 - 100 %

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Necessary first-aid measures

| | |
|----------------------------|--|
| General Information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. |
| Inhalation | IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician or Poison Control |

| | |
|---|---|
| | Center immediately. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If symptoms persist, call a physician. |
| Ingestion | In the unlikely even of swallowing contact a physician or poison control center. Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head so low so that stomach content doesn't get into the lungs. |
| Skin contact | Take off contaminated clothing and shoes immediately. Wash off immediately with soap and plenty of water. In case of eczema or other skin disorders, seek medical attention and take along these instructions. |
| Eye contact | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Seek medical attention if irritation persists. |
| Most important symptoms (acute) | dermatitis. Rash. May cause an allergic skin reaction. |
| Most important symptoms (over-exposure) | Not applicable. |
| Indication of any immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |

5. FIRE-FIGHTING MEASURES

| | |
|---|--|
| Suitable extinguishing media | In case of fire, use water spray (fog), foam, dry chemical or carbon dioxide. Foam. Small fires:. Dry chemical powder. Sand. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Full water jet. |
| Specific hazards | Contents under pressure. Pressurized container may explode when exposed to heat or flame. This product may become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on water surface. Material will float and may ignite on water surface. |
| Special protective equipment for fire-fighters | Firefighters must use standard protective equipment including flame retardent coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Wear suitable protective equipment. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. Cool containers exposed to flames with water until well after the fire is out. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes. Extremely Flammable Aerosol. |

6. ACCIDENTAL RELEASE MEASURES

| | |
|--|---|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary and unprotected personnel from entering the area. Keep people away from and upwind of spill/leak. Keep out of low areas. Remove all sources of ignition. Wear appropriate protective equipment and clothing during cleanup. Avoid breathing vapor or mist. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. Wear |
|--|---|

personal protective clothing and equipment, see section 8.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc) away from spilled material. This material is classified as a water pollutant under the Clean Water Act. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Stop leak if you can without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. For waste disposal, see section 13 of the SDS. This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. HANDLING AND STORAGE

Precautions for safe handling

Will ignite if exposed to intense heat or open air. Vapors may form explosive mixture with air. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, drill, grind, or weld near containers. Store and use away from heat, sparks, open flame or any other ignition source. All equipment used when handling the product must be grounded. Do not reuse containers. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. Wear appropriate personal protective equipment. Wash thoroughly after handling. Avoid release to the environment. Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 122 °F (50 °C). Do not puncture, incinerate, or crush. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid spark promoters. Ground/bond container and receiving equipment. These alone may be insufficient to remove static electricity. Refrigeration recommended. Keep away from incompatible materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

| Chemical name | OSHA PEL (TWA) | California - PELs | ACGIH OEL (TWA) | NIOSH - TWA |
|------------------------------|--|--|-----------------|--|
| D-Limonene | - | | | |
| Propane | 1000 ppm TWA 1800 mg/m ³ TWA | 1000 ppm PEL; 1800 mg/m ³ PEL | | 1000 ppm TWA 1800 mg/m ³ TWA 1000 ppm TWA 1800 mg/m ³ TWA |
| Butane | - | 800 ppm PEL; 1900 mg/m ³ PEL | | 800 ppm TWA 1900 mg/m ³ TWA 1000 ppm TWA 1800 mg/m ³ TWA |
| Alcohols, C9-11, ethoxylated | - | | | |

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Individual protection measures,

**such as personal protective
equipment**

- Eye protection** Face shield is recommended. Wear safety glasses with side shields or goggles.
- Skin and body protection** Wear appropriate chemical resistant gloves. Nitrile gloves are recommended. Wear appropriate chemical resistant clothing.
- Respiratory protection** If permissible levels are exceeded use NIOSH mechanical filter/organic vapor cartridge or an air-supplied respirator.
- Hygiene measures** When using, do not eat, drink or smoke. Avoid contact with skin, eyes and clothing. Keep away from food, drink and animal feeding stuffs. Handle in accordance with good industrial hygiene and safety practice. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

Canadian Province Occupational Exposure Limits

| Chemical name | AB | BC | MB | NB | NL | NS | ON | PE | QC | SK |
|---------------------------------|--|-----------------|----|---|----|----|----|----|--|---|
| D-Limonene | - | - | - | - | - | - | - | - | - | - |
| Propane | 1000 ppm TWA 1640 mg/m ³ TWA | 1000 ppm TWA | - | 1000 ppm TWA 1640 mg/m ³ TWA | - | - | - | - | 1000 ppm TWA 1800 mg/m ³ TWA 1000 ppm TWA 1640 mg/m ³ TWA | 1000 ppm TWA 1000 ppm TWA |
| Butane | 1000 ppm TWA 1640 mg/m ³ TWA | 1000 ppm TWA | - | 800 ppm TWA 1900 mg/m ³ TWA 1000 ppm TWA 1640 mg/m ³ TWA | - | - | - | - | 800 ppm TWA 1900 mg/m ³ TWA 1000 ppm TWA 1640 mg/m ³ TWA | 1000 ppm TWA 1000 ppm TWA 1000 ppm TWA |
| Alcohols, C9-11, ethoxylated | - | - | - | - | - | - | - | - | - | - |

9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state** Liquid Aerosol
- Odor** Not available
- Odor threshold** Not applicable
- pH** Not available
- Melting point/range °C** No data available
- Melting point/range °F** No data available
- Boiling point/range °C** 100 °C
- Boiling point/range °F** 212 °F
- Flash point °C** -104.4
- Flash point °F** -156.0

| | |
|--|-------------------------------|
| Flash point method used | estimated based on propellant |
| Evaporation rate | Not available |
| Flammability (Solid, Gas) | Not available |
| Lower explosion limit | 1.9 % |
| Upper explosion limit | 9.5% |
| Vapor pressure | No information available |
| Vapor density | Not available |
| Relative density | 0.976 |
| Solubility | Not available |
| Partition coefficient (n-octanol/water) | Not available |
| Autoignition temperature °C | Not available |
| Autoignition temperature °F | Not available |
| Decomposition temperature °C | Not available |
| Decomposition temperature °F | Not available |
| Viscosity | Not available |

10. STABILITY AND REACTIVITY

| | |
|---|--|
| Reactivity | The product is stable and not reactive under normal conditions of use, storage and transport. |
| Chemical stability | Risk of ignition. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Exposure to air. Heat, flames and sparks. Avoid temperatures exceeding the flash point. Avoid contact with incompatible materials. |
| Incompatible materials | Oxygen. |
| Hazardous decomposition products | None known based on information supplied. |

11. TOXICOLOGICAL INFORMATION

| | |
|---|---|
| Information on likely routes of exposure | Eyes. Dermal. |
| Symptoms | May cause an allergic skin reaction. Dermatitis. Rash. Direct contact with the eyes may cause temporary irritation. |
| Delayed and immediate effects as well as chronic effects from short and long-term exposure | Not applicable. |

Numerical measures of toxicity

| Chemical name | Inhalation LC50: | Dermal LD50: | Oral LD50: |
|------------------------------|-----------------------------------|--|--------------------|
| D-Limonene | - | = 5200 mg/kg Rat = 4400 mg/kg Rat = 5300 mg/kg Rat >5 g/kg Rabbit | 4400 mg/kg (Rat) |
| Propane | 658 mg/L (Rat) 4h | - | - |
| Butane | 30957 mg/m ³ (Rat) 4 h | - | - |
| Alcohols, C9-11, ethoxylated | - | > 2000 mg/kg (Rabbit) | 1400 mg/kg (Rat) |

ATEmix (dermal) Not available

ATEmix (oral) Not available

ATEmix (inhalation-gas) Not available

ATEmix (inhalation-vapor) Not available

ATEmix (inhalation-dust/mist) Not available

Carcinogenicity

| Chemical name | ACGIH OEL - Carcinogens | IARC | OSHA Carcinogens | NTP |
|------------------------------|-------------------------|---------------------|------------------|-----|
| D-Limonene | - | Group 2A Group 3 | Present | - |
| Propane | - | - | - | - |
| Butane | - | - | - | - |
| Alcohols, C9-11, ethoxylated | - | - | - | - |

Canadian Province carcinogenicity limits

| Chemical name | Alberta - Carcinogen | British Columbia - Carcinogen | Manitoba - Carcinogen | New Brunswick - Carcinogen | Nova Scotia - Carcinogen | Quebec - Carcinogen |
|------------------------------|----------------------|-------------------------------|-----------------------|----------------------------|--------------------------|---------------------|
| D-Limonene | - | - | - | - | - | - |
| Propane | - | - | - | - | - | - |
| Butane | - | - | - | - | - | - |
| Alcohols, C9-11, ethoxylated | - | - | - | - | - | - |

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

| Chemical name | Algae/aquatic plants | Fish LC50 |
|---------------|----------------------|---|
| D-Limonene | - | 0.619 - 0.796mg/L Pimephales promelas 96h = 35mg/L Oncorhynchus mykiss 96h |
| Propane | - | - |

| Chemical name | Algae/aquatic plants | Fish LC50 |
|------------------------------|----------------------|-----------|
| Butane | - | - |
| Alcohols, C9-11, ethoxylated | - | - |

Persistence and degradability Not available.

Bioaccumulation

| Chemical name | CAS-No | Partition coefficient (log Kow) | Bioconcentration factor (BCF) |
|--|------------|--|-------------------------------|
| D-Limonene 5989-27-5 | 5989-27-5 | 4.38 at 37 °C [OECD Guideline 117] (at pH 7.2, ECHA_API) | - |
| Propane 74-98-6 | 74-98-6 | 2.3 <=2.8 | - |
| Butane 106-97-8 | 106-97-8 | 2.31 at 20 °C (at pH 7, ECHA_API) <=2.8 | - |
| Alcohols, C9-11, ethoxylated 68439-46-3 | 68439-46-3 | - | - |

Mobility in soil Not available.

Other adverse effects No adverse affects expected

13. DISPOSAL CONSIDERATIONS

Disposal information Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate, or crush. The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with federal, state and local regulations.

Contaminated packaging Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its containers must be disposed of in a safe way. Empty containers should be taken for local recycling, recovery or waste disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. TRANSPORTATION INFORMATION

Shipping Descriptions

DOT

ID-No UN1950
 Proper shipping name Aerosols
 Hazard Class(es) 2.1
 Subsidiary Risk
 Packing group
 Special Provisions LTD QTY

TDG

ID-No UN1950
 Proper shipping name Aerosols
 Hazard Class(es) 2.1
 Packing group
 Special Provisions LTD QTY

IATA

ID-No UN1950
Proper shipping name Aerosols, flammable
Hazard Class(es) 2.1
Subsidiary Risk
Packing group
ERG Code 126
Special Provisions LTD QTY

IMDG/IMO

ID-No UN1950
Proper shipping name Aerosols
Hazard Class(es) 2.1
Packing group
EmS No F-D, S-U
Special Provisions LTD QTY

Marine Pollutants

| Chemical name | CAS-No | USDOT Marine Pollutant | Canada TDG Marine Pollutant | IMDG Marine Pollutant |
|------------------------------|------------|------------------------|-----------------------------|-----------------------|
| D-Limonene | 5989-27-5 | X | X | X |
| Propane | 74-98-6 | - | - | - |
| Butane | 106-97-8 | - | - | - |
| Alcohols, C9-11, ethoxylated | 68439-46-3 | - | - | - |

Special Precautions

Multi-modal shipping descriptions are provided for informational purposes and do not consider container size. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

15. REGULATORY INFORMATION

State regulations

U.S. state Right-to-Know regulations

| Chemical name | CAS-No | Massachusetts - RTK | New Jersey - RTK | Pennsylvania - RTK |
|------------------------------|------------|---------------------|------------------|--------------------|
| D-Limonene | 5989-27-5 | - | X | - |
| Propane | 74-98-6 | X | X | X |
| Butane | 106-97-8 | X | X | X |
| Alcohols, C9-11, ethoxylated | 68439-46-3 | - | - | - |

California Prop. 65

| Chemical name | CAS-No | California Prop. 65 |
|------------------------------|------------|---------------------|
| D-Limonene | 5989-27-5 | - |
| Propane | 74-98-6 | - |
| Butane | 106-97-8 | - |
| Alcohols, C9-11, ethoxylated | 68439-46-3 | - |

U.S. Federal Regulations

RCRA - D Series Wastes Waste codes should be assigned by the user based on the application for which the product was used

Methylene Chloride notification No Information Available

US EPA SARA 313

| Chemical name | CAS-No | CERCLA/SARA Hazardous Substances RQ | SARA 313 - Threshold Values |
|------------------------------|------------|--|-----------------------------|
| D-Limonene | 5989-27-5 | - | - |
| Propane | 74-98-6 | - | - |
| Butane | 106-97-8 | - | - |
| Alcohols, C9-11, ethoxylated | 68439-46-3 | - | - |

**US EPA SARA 311/312
hazardous categorization** Acute Health Hazard
Fire Hazard

TSCA and Canadian Inventories

| Chemical name | Inventory - United States - Section 8(b) Inventory (TSCA) | U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification | DSL | NDSL |
|------------------------------|---|--|-----|------|
| D-Limonene | X | - | X | - |
| Propane | X | - | X | - |
| Butane | X | - | X | X |
| Alcohols, C9-11, ethoxylated | X | - | X | - |

Legend X - Listed

16. OTHER INFORMATION

NFPA

Health Not available
Flammability Not available
Instability Not available

HMIS

Health Not available
Flammability Not available
Physical hazards Not available

Notice: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by Regulatory Affairs

Issue date 19-Jul-2018

Revision date 06-Jul-2023

Revision note

Key to abbreviations

ACGIH (American Conference of Governmental Industrial Hygienists)
ATE (Average Toxicity Estimate)
DSL/NDSL (Domestic Substance List/Non-Domestic Substance List)
HMIS (Hazardous Materials Identification System)
IARC (International Agency for Research on Cancer)
IATA (International Air Transport Association)
IMDG/IMO (International Maritime Dangerous Goods/International Maritime Organization)
NFPA (National Fire Protection Association)
NTP (National Toxicology Program)
OEL (Occupational Exposure Level)
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
PEL (Permissible Exposure Limit)
TSCA (Toxic Substance Control Act)
USEPA (United States Environmental Protection Agency)

Disclaimer

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

End of Safety Data Sheet