

4/23/2024: File reviewed, more current MSDS/SDS not available. CAS

1. Identification

Product identifier Liquid Wrench Silicone Spray

Other means of identification

SDS number M914
Part No. M914, M914/6, M914/4
Tariff code 3403.19.1000

Recommended use Lubricant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name RSC Chemical Solutions
Address 600 Radiator Road
 Indian Trail, NC 28079
 United States
Telephone Customer Service: (704) 821-7643
 Technical: (704) 684-1811
Website www.rscbrands.com
E-mail sds@rscbrands.com
Emergency phone number Emergency Telephone: (303) 623-5716
 Emergency Contact: RMPDC (877-740-5015)

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 2
Health hazards	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Germ cell mutagenicity	Category 1
	Carcinogenicity	Category 1A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
Environmental hazards	Aspiration hazard	Category 1
	Hazardous to the aquatic environment, acute hazard	Category 3
OSHA defined hazards	Hazardous to the aquatic environment, long-term hazard	Category 3
	Not classified.	

Label elements



Signal word Danger

Hazard statement Flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Combustible.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), Hydrotreated Light		64742-47-8	30.22
Naphtha (petroleum), Hydrotreated Heavy		64742-48-9	10 - < 20
Solvent Naphtha (petroleum), Medium Aliph.		64742-88-7	10 - < 20
Stoddard Solvent		8052-41-3	10 - < 20
Distillates (petroleum), Hydrotreated Heavy Naphthenic		64742-52-5	4.85
1000 cSt Silicone		63148-62-9	4.28
Carbon Dioxide		124-38-9	2.81
1,2,4-Trimethylbenzene		95-63-6	1 - < 3
BENZENE, DIMETHYL		1330-20-7	1 - < 3
NAPHTHALENE		91-20-3	1 - < 3
Nonane		111-84-2	1 - < 3
Trimethylbenzene		25551-13-7	1 - < 3
BENZENE		71-43-2	< 1
BENZENE, METHYL-		108-88-3	< 1
BENZENE,1-METHYLETHYL-		98-82-8	< 1
ETHYLBENZENE		100-41-4	< 1
HEXANE		110-54-3	< 1
Other components below reportable levels			< 1

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Diarrhea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Flammable aerosol. Combustible.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Keep combustibles (wood, paper, oil, etc.) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe the mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
--------------------------------------	---

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Components	Type	Value
BENZENE (CAS 71-43-2)	STEL	5 ppm
	TWA	1 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
BENZENE, DIMETHYL (CAS 1330-20-7)	PEL	435 mg/m3	
		100 ppm	
BENZENE, 1-METHYLETHYL- (CAS 98-82-8)	PEL	245 mg/m3	
		50 ppm	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	PEL	5000 ppm	Mist.
		5 mg/m3	
ETHYLBENZENE (CAS 100-41-4)	PEL	2000 mg/m3	
		500 ppm	
HEXANE (CAS 110-54-3)	PEL	435 mg/m3	
		100 ppm	
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)	PEL	1800 mg/m3	
		500 ppm	
NAPHTHALENE (CAS 91-20-3)	PEL	400 mg/m3	
		100 ppm	
Stoddard Solvent (CAS 8052-41-3)	PEL	50 mg/m3	
		10 ppm	
Stoddard Solvent (CAS 8052-41-3)	PEL	2900 mg/m3	
		500 ppm	

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
BENZENE (CAS 71-43-2)	Ceiling	25 ppm
	TWA	10 ppm
BENZENE, METHYL- (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	25 ppm	
BENZENE (CAS 71-43-2)	STEL	2.5 ppm	
	TWA	0.5 ppm	
BENZENE, DIMETHYL (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
BENZENE, METHYL- (CAS 108-88-3)	TWA	20 ppm	
BENZENE, 1-METHYLETHYL- (CAS 98-82-8)	TWA	50 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	TWA	5000 ppm	Inhalable fraction.
	TWA	5 mg/m3	
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm	
HEXANE (CAS 110-54-3)	TWA	50 ppm	
NAPHTHALENE (CAS 91-20-3)	TWA	10 ppm	
Nonane (CAS 111-84-2)	TWA	200 ppm	Non-aerosol.
Solvent Naphtha (petroleum), Medium Aliph. (CAS 64742-88-7)	TWA	200 mg/m3	
Stoddard Solvent (CAS 8052-41-3)	TWA	100 ppm	
Trimethylbenzene (CAS 25551-13-7)	TWA	25 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3	
		25 ppm	
BENZENE (CAS 71-43-2)	STEL	1 ppm	
	TWA	0.1 ppm	
	STEL	560 mg/m3	
BENZENE, METHYL- (CAS 108-88-3)	TWA	150 ppm	
		375 mg/m3	
		100 ppm	
BENZENE, 1-METHYLETHYL- (CAS 98-82-8)	TWA	245 mg/m3	
		50 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
	TWA	30000 ppm 9000 mg/m3	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	Ceiling	5000 ppm 1800 mg/m3	
	STEL	10 mg/m3	
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	100 mg/m3	Mist.
	STEL	545 mg/m3	
ETHYLBENZENE (CAS 100-41-4)	TWA	125 ppm	
		435 mg/m3	
HEXANE (CAS 110-54-3)	TWA	100 ppm	
		180 mg/m3	
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)	TWA	50 ppm	
		400 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
NAPHTHALENE (CAS 91-20-3)	STEL	100 ppm	
		75 mg/m3	
Nonane (CAS 111-84-2)	TWA	15 ppm	
		50 mg/m3	
Solvent Naphtha (petroleum), Medium Aliph. (CAS 64742-88-7)	TWA	10 ppm	
		1050 mg/m3	
Stoddard Solvent (CAS 8052-41-3)	Ceiling	200 ppm	
		1800 mg/m3	
	TWA	350 mg/m3	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
BENZENE (CAS 71-43-2)	25 µg/g	S-Phenylmercapturic acid	Creatinine in urine	*
BENZENE, DIMETHYL (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
BENZENE, METHYL- (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
HEXANE (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedion, without hydrolysis	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

BENZENE (CAS 71-43-2)	Can be absorbed through the skin.
BENZENE, METHYL- (CAS 108-88-3)	Can be absorbed through the skin.
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Can be absorbed through the skin.
HEXANE (CAS 110-54-3)	Can be absorbed through the skin.
NAPHTHALENE (CAS 91-20-3)	Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

BENZENE, METHYL- (CAS 108-88-3)	Skin designation applies.
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Skin designation applies.

US - Tennessee OELs: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Can be absorbed through the skin.
--------------------------------------	-----------------------------------

US ACGIH Threshold Limit Values: Skin designation

BENZENE (CAS 71-43-2)	Can be absorbed through the skin.
HEXANE (CAS 110-54-3)	Can be absorbed through the skin.
NAPHTHALENE (CAS 91-20-3)	Can be absorbed through the skin.
Solvent Naphtha (petroleum), Medium Aliph. (CAS 64742-88-7)	Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Can be absorbed through the skin.
--------------------------------------	-----------------------------------

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Can be absorbed through the skin.
--------------------------------------	-----------------------------------

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields, goggles or full facepiece.
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece. Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Clear. Liquid
Physical state	Liquid.
Form	Aerosol.
Color	Pale yellow
Odor	Petroleum
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-94 °F (-70 °C) estimated
Initial boiling point and boiling range	314.6 °F (157 °C) estimated
Flash point	117.0 °F (47.2 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.7 % estimated
Flammability limit - upper (%)	6 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.41 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	229 °F (109.44 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	6.80 lbs/gal
Explosive properties	Not explosive.

Flame extension	25 in
Flammability (flash back)	No
Flammability class	Combustible II estimated
Heat of combustion (NFPA 30B)	27.36 kJ/g estimated
Moisture	< 0.03 %
Oxidizing properties	Not oxidizing.
Percent volatile	7.89 % estimated
Refractive index	1.44
Specific gravity	0.82
VOC	58.5 % w/w

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Diarrhea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways. Harmful if inhaled. Narcotic effects.
-----------------------	---

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg
Inhalation		
LC50	Rat	> 2000 ppm, 48 Hours
Oral		
LD50	Rat	6 g/kg
BENZENE (CAS 71-43-2)		
Acute		
Inhalation		
LC50	Mouse	9980 ppm
	Rat	10000 ppm, 7 Hours
Oral		
LD50	Mouse	4700 mg/kg
	Rat	3306 mg/kg

Components	Species	Test Results
BENZENE, DIMETHYL (CAS 1330-20-7)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 43 g/kg
Inhalation		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours
Oral		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg
BENZENE, METHYL- (CAS 108-88-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	12124 mg/kg 14.1 ml/kg
Inhalation		
LC50	Mouse	5320 ppm, 8 Hours 400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours
Oral		
LD50	Rat	2.6 g/kg
BENZENE,1-METHYLETHYL- (CAS 98-82-8)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	2000 ppm, 7 Hours 24.7 mg/l, 2 Hours
	Rat	8000 ppm, 4 Hours
Oral		
LD50	Rat	1400 mg/kg
ETHYLBENZENE (CAS 100-41-4)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	17800 mg/kg
Oral		
LD50	Rat	3500 mg/kg
HEXANE (CAS 110-54-3)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	48000 ppm, 4 Hours
Oral		
LD50	Rat	28710 mg/kg
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)		
<u>Acute</u>		
Inhalation		
LC50	Rat	61 mg/l, 4 Hours
Oral		
LD50	Rat	> 25 ml/kg

Components	Species	Test Results
NAPHTHALENE (CAS 91-20-3)		
Acute		
Dermal		
LD50	Rabbit	> 2 g/kg
	Rat	> 20 g/kg
Oral		
LD50	Guinea pig	1200 mg/kg
	Rat	490 mg/kg
Nonane (CAS 111-84-2)		
Acute		
Inhalation		
LC50	Rat	3200 ppm, 4 Hours
Trimethylbenzene (CAS 25551-13-7)		
Acute		
Oral		
LD50	Rat	8970 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZENE (CAS 71-43-2)	1 Carcinogenic to humans.
BENZENE, DIMETHYL (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.
BENZENE, METHYL- (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	2B Possibly carcinogenic to humans.
ETHYLBENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.
NAPHTHALENE (CAS 91-20-3)	2B Possibly carcinogenic to humans.
Stoddard Solvent (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

BENZENE (CAS 71-43-2)	Cancer
-----------------------	--------

US. National Toxicology Program (NTP) Report on Carcinogens

BENZENE (CAS 71-43-2)	Known To Be Human Carcinogen.
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Reasonably Anticipated to be a Human Carcinogen.
NAPHTHALENE (CAS 91-20-3)	Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.

Specific target organ toxicity - single exposure May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 7.19 - 8.28 mg/l, 96 hours
1000 cSt Silicone (CAS 63148-62-9)		
Aquatic		
Fish	LC50	Channel catfish (<i>Ictalurus punctatus</i>) 2.36 - 4.15 mg/l, 96 hours
BENZENE (CAS 71-43-2)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 8.76 - 15.6 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) 7.2 - 11.7 mg/l, 96 hours
BENZENE, DIMETHYL (CAS 1330-20-7)		
Aquatic		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) 7.711 - 9.591 mg/l, 96 hours
BENZENE, METHYL- (CAS 108-88-3)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (<i>Oncorhynchus kisutch</i>) 8.11 mg/l, 96 hours
BENZENE,1-METHYLETHYL- (CAS 98-82-8)		
Aquatic		
Crustacea	EC50	Brine shrimp (<i>Artemia</i> sp.) 3.55 - 11.29 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) 2.7 mg/l, 96 hours
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) 2.9 mg/l, 96 hours
ETHYLBENZENE (CAS 100-41-4)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 7.5 - 11 mg/l, 96 hours
HEXANE (CAS 110-54-3)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 2.101 - 2.981 mg/l, 96 hours
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia pulex</i>) 2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) 8.8 mg/l, 96 hours
		8.8 mg/l, 96 hours
NAPHTHALENE (CAS 91-20-3)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Pink salmon (<i>Oncorhynchus gorbuscha</i>) 1.11 - 1.68 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

BENZENE 2.13

Partition coefficient n-octanol / water (log Kow)	
BENZENE, DIMETHYL	3.12 - 3.2
BENZENE, METHYL-	2.73
BENZENE, 1-METHYLETHYL-	3.66
ETHYLBENZENE	3.15
HEXANE	3.9
NAPHTHALENE	3.3
Nonane	5.46
Stoddard Solvent	3.16 - 7.15

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	Not available.
UN proper shipping name	Consumer Commodity
Transport hazard class(es)	
Class	ORM-D
Subsidiary risk	-
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	8, 146, 335, IB3, T4, TP1, TP29
Packaging exceptions	155
Packaging non bulk	203
Packaging bulk	241

IATA

UN number	UN1950
UN proper shipping name	Aerosol, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.


IMDG

UN number	UN1950
UN proper shipping name	Aerosols, MARINE POLLUTANT
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.
IATA; IMDG



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Nonane (CAS 111-84-2) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

BENZENE (CAS 71-43-2)	Listed.
BENZENE, DIMETHYL (CAS 1330-20-7)	Listed.
BENZENE, METHYL- (CAS 108-88-3)	Listed.
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Listed.
ETHYLBENZENE (CAS 100-41-4)	Listed.
HEXANE (CAS 110-54-3)	Listed.
NAPHTHALENE (CAS 91-20-3)	Listed.
Nonane (CAS 111-84-2)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

BENZENE (CAS 71-43-2)	Cancer
	Central nervous system
	Blood
	Aspiration
	Skin
	Eye
	respiratory tract irritation
	Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes
	Delayed Hazard - Yes
	Fire Hazard - Yes
	Pressure Hazard - No
	Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
1,2,4-Trimethylbenzene	95-63-6	1 - < 3
BENZENE, DIMETHYL	1330-20-7	1 - < 3
NAPHTHALENE	91-20-3	1 - < 3
BENZENE	71-43-2	< 1
BENZENE, METHYL-	108-88-3	< 1
BENZENE,1-METHYLETHYL-ETHYLBENZENE	98-82-8	< 1
ETHYLBENZENE	100-41-4	< 1
HEXANE	110-54-3	< 1

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

BENZENE (CAS 71-43-2)
 BENZENE, DIMETHYL (CAS 1330-20-7)
 BENZENE, METHYL- (CAS 108-88-3)
 BENZENE,1-METHYLETHYL- (CAS 98-82-8)
 ETHYLBENZENE (CAS 100-41-4)
 HEXANE (CAS 110-54-3)
 NAPHTHALENE (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

BENZENE, METHYL- (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

BENZENE, METHYL- (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

BENZENE, METHYL- (CAS 108-88-3) 594

US state regulations**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-Trimethylbenzene (CAS 95-63-6)
 BENZENE (CAS 71-43-2)
 BENZENE, DIMETHYL (CAS 1330-20-7)
 BENZENE, METHYL- (CAS 108-88-3)
 BENZENE,1-METHYLETHYL- (CAS 98-82-8)
 Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)
 Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)
 ETHYLBENZENE (CAS 100-41-4)
 HEXANE (CAS 110-54-3)
 Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)
 NAPHTHALENE (CAS 91-20-3)
 Solvent Naphtha (petroleum), Medium Aliph. (CAS 64742-88-7)
 Stoddard Solvent (CAS 8052-41-3)

US. Massachusetts RTK - Substance List

1,2,4-Trimethylbenzene (CAS 95-63-6)
 BENZENE (CAS 71-43-2)
 BENZENE, DIMETHYL (CAS 1330-20-7)
 BENZENE, METHYL- (CAS 108-88-3)
 BENZENE,1-METHYLETHYL- (CAS 98-82-8)
 Carbon Dioxide (CAS 124-38-9)
 Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)
ETHYLBENZENE (CAS 100-41-4)
HEXANE (CAS 110-54-3)
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)
NAPHTHALENE (CAS 91-20-3)
Nonane (CAS 111-84-2)
Solvent Naphtha (petroleum), Medium Aliph. (CAS 64742-88-7)
Stoddard Solvent (CAS 8052-41-3)
Trimethylbenzene (CAS 25551-13-7)

US. New Jersey Worker and Community Right-to-Know Act

1,2,4-Trimethylbenzene (CAS 95-63-6)
BENZENE (CAS 71-43-2)
BENZENE, DIMETHYL (CAS 1330-20-7)
BENZENE, METHYL- (CAS 108-88-3)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
Carbon Dioxide (CAS 124-38-9)
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)
ETHYLBENZENE (CAS 100-41-4)
HEXANE (CAS 110-54-3)
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)
NAPHTHALENE (CAS 91-20-3)
Nonane (CAS 111-84-2)
Solvent Naphtha (petroleum), Medium Aliph. (CAS 64742-88-7)
Stoddard Solvent (CAS 8052-41-3)
Trimethylbenzene (CAS 25551-13-7)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2,4-Trimethylbenzene (CAS 95-63-6)
BENZENE (CAS 71-43-2)
BENZENE, DIMETHYL (CAS 1330-20-7)
BENZENE, METHYL- (CAS 108-88-3)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
Carbon Dioxide (CAS 124-38-9)
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)
ETHYLBENZENE (CAS 100-41-4)
HEXANE (CAS 110-54-3)
NAPHTHALENE (CAS 91-20-3)
Nonane (CAS 111-84-2)
Solvent Naphtha (petroleum), Medium Aliph. (CAS 64742-88-7)
Stoddard Solvent (CAS 8052-41-3)
Trimethylbenzene (CAS 25551-13-7)

US. Rhode Island RTK

1,2,4-Trimethylbenzene (CAS 95-63-6)
BENZENE (CAS 71-43-2)
BENZENE, DIMETHYL (CAS 1330-20-7)
BENZENE, METHYL- (CAS 108-88-3)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
ETHYLBENZENE (CAS 100-41-4)
HEXANE (CAS 110-54-3)
NAPHTHALENE (CAS 91-20-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE (CAS 71-43-2)	Listed: February 27, 1987
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Listed: April 6, 2010
ETHYLBENZENE (CAS 100-41-4)	Listed: June 11, 2004
NAPHTHALENE (CAS 91-20-3)	Listed: April 19, 2002

US - California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE (CAS 71-43-2)	Listed: December 26, 1997
BENZENE, METHYL- (CAS 108-88-3)	Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

BENZENE (CAS 71-43-2)	Listed: December 26, 1997
-----------------------	---------------------------

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	06-01-2015
Revision date	09-12-2016
Version #	06
HMIS® ratings	Health: 3* Flammability: 4 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 3 Instability: 0

NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.