



# Safety Data Sheet (SDS)

Date Prepared/Revised: 8/25/23

Version no.: 05

Supersedes: (1/31/20)

## 1.) Identification of the Mixture and of the Company

Product identifier: **Zynolyte Speed E-namel**

Product name:

**Speed E-namel**

Z275 Semi-Gloss White	Z377 Flat White	Z471 Royal Blue	Z519 Burgundy
Z277 Semi-Gloss Black	Z387 Gloss Black	Z482 Almond	Z525 Kelly Green
Z297 Persimmon	Z397 Gloss White	Z487 Flat Black	Z813 Red
Z298 Orange	Z407 Gold	Z489 Light Gray	
Z307 Acrylic Clear	Z467 Lemon Yellow	Z506 Antique White	
Z308 Silver	Z468 Medium Gray	Z516 Purple	
Z317 Aluminum	Z469 Hunter Green	Z517 Rich Red	
Z357 Chocolate Brown	Z470 Bermuda Blue	Z518 Pink	

Relevant identified uses of the substance: Great for furniture, metal and wood railings, fences, bicycles, hobbies, crafts, plastic and metal garden accessories, cabinets, doors, patio items, wicker, tools masonry, bulkheads, and much more. Can be used indoors or outdoors.

Uses advised against: Poorly ventilated areas

CAS No:	<b>Not Applicable (mixture)</b>
EC No:	<b>Not Applicable (mixture)</b>
Index No:	<b>Not Applicable (mixture)</b>
Manufacturer/Supplier:	<b>Aervoe Industries Incorporated</b>
Street address/P.O. Box:	<b>1100 Mark Circle</b>
Country ID/Postcode/Place:	<b>Gardnerville, Nevada 89410</b>
Telephone number:	<b>1-775-782-0100</b>
e-mail:	<b>mailbox@aervoe.com</b>
National contact:	<b>Aervoe Industries Incorporated</b>
For Product Information:	<b>1-800-227-0196</b>
Emergency telephone number:	<b>1-800-424-9300 (CHEMTREC – 24 hrs)</b>

## 2. Hazards identification

### Classifications

Physical Hazards:           Aerosol - Category 1  
 Flam. Gas 1  
 Flam. Liq. 2  
 Flam. Liq. 3 \*311  
 Liquefied Gas

Health Hazards:           Carc. 1B  
 Muta. 1B  
 Eye Irrit. 2  
 Asp. Tox. 1  
 STOT SE3  
 Skin Irrit. 2



# Safety Data Sheet (SDS)

Date Prepared/Revised: 8/25/23

Version no.: 05 Supersedes: (1/31/20)

Environmental Hazards: Aquatic Tox 2

## Labeling

Signal Word: Danger

Hazard Statements:

- H220 – Extremely flammable gas.
- H222 – Extremely Flammable Aerosol
- H225 – Highly flammable liquid and vapour.
- H226 – Flammable liquid and vapour.
- H229 - Pressurized container: may burst if heated
- H304 – May be fatal if swallowed and enters airways.
- H315 – Causes skin irritation.
- H319 – Causes serious eye irritation.
- H336 – May cause drowsiness or dizziness.
- H340 – May cause genetic defects
- H350 – May cause cancer
- H411 – Toxic to aquatic life with long lasting effects.

Precautionary Statements:

- P101 - If medical advice is needed, have product container or label at hand
- P102 - Keep out of reach of children
- P103 - Read label before use
- P210 - Keep away from heat/sparks/open flames/hot surfaces - no smoking
- P211 - Do not spray on an open flame or other ignition source
- P251 - Pressurized container: Do not pierce or burn, even after use
- P261 - Avoid breathing dust/fume/gas/mist/vapours/spray
- P262 - Do not get in eyes, on skin, or on clothing
- P264 - Wash ... thoroughly after handling
- P280 - Wear protective gloves/eye protection/face protection
  
- P303+P361+P353 - If on skin or hair, remove/takeoff immediately all contaminated clothing. Rinse skin with water/shower.
- P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F
- P501 - Dispose of contents/container in accordance with local/regional/national/international regulation
- P251 - Pressurized container: Do not pierce or burn, even after use

Symbols/Pictograms:



## 3. Composition / Information on Ingredients

### Composition

Chemical	Synonyms	CAS Number	EINECS	Weight	Hazard Category	H-Code
----------	----------	------------	--------	--------	-----------------	--------



# Safety Data Sheet (SDS)

Date Prepared/Revised: 8/25/23

Version no.: 05 Supersedes: (1/31/20)

			Number	Percent		
Acetone	Propanone	67-64-1	200-662-2	15-40%	Flam. Liq. 2 Eye Irrit. 2 STOT SE 3	H225, H319, H336
Hydrocarbon Propellant	LPG	68476-86-8	270-705-8	15-40%	Liquefied Gas Flam. Gas 1	H220 H229
Aliphatic Petroleum Distillates	Solvent Naphtha	64742-89-8	265-192-2	10-30%	Flam Liq. 2 Skin Irr. 2 Asp. Tox. 1 STOT SE 3 Aquatic Tox. 2	H224 H304 H315 H336 H411
Dipropylene Glycol Methyl Ether	Glycol Ether DPM	34590-94-8	252-104-2	1-5%	N/AV	N/AV
Aliphatic Hydrocarbon	Hydrocarbon	64742-89-2	N/AV	1-5%	N/AV	N/AV
Z275,Z397, Z482,Z506 also contain:						
Aliphatic Hydrocarbon	Petroleum Distillate	8052-41-3	232-489-3	1-5%	Carc. 1B Muta. 1B Asp. Tox. 1	H350 H340 H304
Z307 contains:						
Hydrocarbon Propellant	LPG	68476-86-8	270-705-8	10-30%	Press. Gas Flam. Gas 1	H220 H229
Aliphatic Petroleum Distillates	Solvent Naphtha	64742-89-8	265-192-2	30-60%	Flam Liq. 2 Skin Irr. 2 Asp. Tox. 1 STOT SE 3 Aquatic Tox. 2	H224 H304 H315 H336 H411
n-Butyl Acetate	n-Butyl Ester	123-86-4	204-658-1	10-30%	Flam. Liq. 3 STOT SE 3	H226 H336
Acetone	Propanone	67-64-1	200-662-2	30-60%	Flam. Liq. 2 Eye Irrit. 2 STOT SE 3	H225, H319, H336
n-Methyl-2- Propanol Acetate	2-Methoxy-1- Methylethyl Acetate	108-65-6	203-603-9	1-5%	Flam. Liq. 3	H226
Z308 contains:						
Hydrocarbon Propellant	LPG	68476-86-8	270-705-8	30-60%	Press. Gas Flam. Gas 1	H220 H229
Aliphatic Petroleum Distillates	Solvent Naphtha	64742-89-8	265-192-2	30-60%	Flam Liq. 2 Skin Irr. 2 Asp. Tox. 1 STOT SE 3 Aquatic Tox. 2	H224 H304 H315 H336 H411
Z407 contains:						
Acetone	Propanone	67-64-1	200-662-2	30-60%	Flam. Liq. 2 Eye Irrit. 2	H225, H319, H336



# Safety Data Sheet (SDS)

Date Prepared/Revised: 8/25/23

Version no.: 05 Supersedes: (1/31/20)

					STOT SE 3	
Hydrocarbon Propellant	LPG	68476-86-8	270-705-8	10-30%	Press. Gas Flam. Gas 1	H220 H229
n-Butyl Acetate	n-Butyl Ester	123-86-4	204-658-1	10-30%	Flam. Liq. 3 STOT SE 3	H226 H336

## Other Product Information

Chemical Identity: Mixture

## 4.) First Aid Measures

<b>General Advice:</b>	If symptoms persist, always call a doctor.
<b>Inhalation First Aid:</b>	Remove victim to fresh air and provide oxygen if breathing is difficult. If not breathing, give artificial respiration, preferably mouth to mouth. Get medical attention immediately.
<b>Skin Contact First Aid:</b>	Wash with soap and water. Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse.
<b>Eye Contact First Aid:</b>	If contact with eyes, immediately flush eyes with plenty of water for at least 15 minutes, while holding eyelids open. Get medical attention immediately.
<b>Ingestion First Aid:</b>	If swallowed, wash out mouth with water provided the person is conscious. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
<b>Most Important Symptoms/Effects:</b>	Exposure may cause slight irritation to the skin, eyes, and respiratory tract. Excessive exposure may cause central nervous system effects.

## 5. Fire Fighting Measures

Flammable Properties:	Aerosol
Auto Ignition Temperature:	Not Available
Suitable extinguishing media:	Carbon dioxide, dry chemical, water spray.
Unsuitable extinguishing media:	None known
Special hazards arising from the substance or mixture:	None known
Hazardous combustion products:	Carbon dioxide, Carbon monoxide
Fire & Explosion Hazards:	Closed Containers may rupture due to the buildup of pressure from extreme temperatures.
Precautions for fire-fighters:	Use water spray to cool containers exposed to heat or fire to prevent pressure build up. In the event of a fire, wear full protective clothing and NIOSH- approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode.



# Safety Data Sheet (SDS)

Date Prepared/Revised: 8/25/23

Version no.: 05 Supersedes: (1/31/20)

## 6. Accidental Release Measures

### PERSONAL PRECAUTIONARY MEASURES:

- 1) Follow personal protective equipment recommendations found in section 8.
- 2) Maintain adequate ventilation.

### SPILL CLEAN-UP PROCEDURES:

- 1.) Evacuate unprotected personnel from the area.
- 2.) Remove sources of ignition if safe to do so.
- 3.) Pickup spilled materials using non-sparking tools and place in an appropriate container for disposal.
- 4.) Contain spill to prevent material from entering sewage or ground water systems.
- 5.) Always dispose of waste materials in accordance with all EU, National and Local Regulations.

## 7. Handling and Storage

### Handling:

Flammable Aerosol, use in a well ventilated area.  
 Do not use near sources of ignition.  
 Do not to eat, drink and smoke while working with this material.  
 Wash hands after use.

### Conditions for safe storage, including any incompatibilities:

Store out of direct sunlight.  
 Storage Temperature: 32° to 120°F (0° to 49°C).  
 No known incompatibilities.

## 8. Exposure Controls / Personal Protection

### Appropriate engineering controls:

Ensure adequate ventilation. A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits.  
 Keep away from sources of ignition.  
 Take precautionary measures against static discharge.

### Personal Protection:

Eye & face protection devices such as safety glasses, safety goggles or face shield are recommended.

### Skin protection

Wear the appropriate protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

### Respiratory protection:

Use only in an adequately ventilated area. For unknown vapor concentrations use a positive-pressure, pressure-demand, self-contained breathing apparatus (SCBA).

Hazardous Ingredient	CAS Number	ACGIH TLV (TWA)	ACGIH TLV (STEL)	OSHA PEL (TWA)	OSHA PEL (STEL)



# Safety Data Sheet (SDS)

Date Prepared/Revised: 8/25/23

Version no.: 05 Supersedes: (1/31/20)

Acetone	67-64-1	250PPM	500PPM	1000PPM	250PPM
Hydrocarbon Propellant	68476-86-8	N/A	N/A	N/A	N/A
Aliphatic Petroleum Distillates	64742-89-8	N/A	N/A	N/A	N/A
n-Butyl Acetate	123-86-4	50PPM	150PPM	150 ppm	50PPM
Aliphatic Hydrocarbon	8052-41-3	100PPM	N/A	500PPM	100PPM
Dipropylene Glycol Methyl Ether	34590-94-8	100PPM	150PPM	100PPM	100PPM
n-Methyl-2-Propanol Acetate	108-65-6	250PPM	500PPM	1000PPM	250PPM

**\*Values are based on the 2019 Guide to Occupational Exposure Values by ACGIH**

## 9. Information on Basic Physical and Chemical Properties

Appearance: Color varies by product	Odor: Ketone Odor
Odor Threshold: N/AV	pH: Not Applicable (solvent Base)
Melting Point: N/AV	Freezing Point: N/AV
Initial Boiling Point: N/AV	Boiling Point Range: N/AV
Flash Point: <0° F (-18° C)	Evaporation Rate: Faster than n-Butyl Acetate
Flammability Solid/Gas: Flammable gas	LEL: 0.7% UEL: 15%
Vapor Pressure: N/AV	Vapor Density: Heavier Than Air
Relative Density: N/AV	Solubility: Negligible
Partition Coefficient: n-octanol/ water: N/AV	Auto-ignition Temperature: N/AV
Decomposition Temperature: N/AV	Viscosity: N/AV
Explosive Properties: N/AV	Oxidizing Properties: N/AV

## 10. Stability & Reactivity

Possibility of hazardous reactions: Hazardous polymerization will not occur under normal conditions  
Chemical stability: Stable under normal conditions  
Conditions to avoid: Heat and ignition sources  
Incompatible materials: Strong Oxidizing Agents  
Hazardous decomposition products: Will not occur

## 11. Toxicological Information

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood

Routes of exposure: Eyes, skin, ingestion, and/or inhalation

Acute toxicological data: (Acetone) LD50: 5800 mg/kg (Rat-Oral)  
(Acetone) LC50: 21000 ppm/8 hr (Rat-Inha)

Eye irritation data: N/AV



# Safety Data Sheet (SDS)

Date Prepared/Revised: 8/25/23

Version no.: 05 Supersedes: (1/31/20)

Skin irritation/sensitization/absorption data: N/AV  
Reproductive toxicity data: N/AV

Mutagenicity data: Muta. 1B

Symptoms associated with physical contact: N/AV

Acute/chronic effects from short/long term exposure: Irritating to skin. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis. Not expected to be a skin sensitizer.

Known reportable carcinogens via the following agencies:

NTP: N/AV  
IARC: N/AV  
OSHA: TLV-A4

## 12. Ecological Information

Ecotoxicity: **No Data Available**  
Persistence and degradability: **No Data Available**  
Bioaccumulative potential: **No Data Available**  
Mobility in soil: **No Data Available**  
Results of PBT and vPvB assessment: **No Data Available**  
Other adverse effects: **No Data Available**

## 13. Disposal Considerations

**Waste Disposal:** Dispose of material in accordance with EU, national and local requirements. For proper disposal of used material, an assessment must be completed to determine the proper and permissible waste management options permitted under applicable rules, regulations and/or laws governing your location.  
**Product / Packaging disposal:** Dispose of packaging in accordance with federal, state and local requirements, regulations and/or laws governing your location.

## 14. Transportation Information

### US DOT

UN Number	Proper Shipping Name	Hazard Class	Packing Group	Marine Pollutant	Special Provisions
UN1950	Aerosols	2.1	Not Applicable	Not Applicable	Reference 49 CFR 172.101

### IMDG

UN Number	Proper Shipping Name	Hazard Class	Packing Group	Marine Pollutant	Special Provisions



# Safety Data Sheet (SDS)

Date Prepared/Revised: 8/25/23

Version no.: 05 Supersedes: (1/31/20)

UN1950	Aerosols	2.1	Not Applicable	Not Applicable	Reference IMDG code part 3
--------	----------	-----	----------------	----------------	----------------------------

## IATA:

UN Number	Proper Shipping Name	Hazard Class	Packing Group	Marine Pollutant	Special Provisions
UN1950	Aerosols, Flammable	2.1	Not Applicable	Not Applicable	Reference IATA Dangerous Goods Regulation

## 15. Regulatory Information

### Workplace classification:

This product is considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). The Occupational Safety and Health Administration's interpretation of the product's hazard to workers.

### SARA Title 3:

Section 311/312 Categorizations (40 CFR 372): This product is a hazardous chemical under 29 CFR 1910.1200, and is categorized as an immediate and delayed health, and flammability physical hazard. Superfund Amendment and Reauthorization Act (SARA) category. SARA requires reporting any spill of any hazardous substance.

**TSCA status:** All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

**WHMIS:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the (M)SDS contains all of the information required by the CPR.

**PROP 65 (CA):** WARNING: Cancer and Reproductive Harm – [www.P65Warnings.com](http://www.P65Warnings.com).

## 16. Other Information

This SDS has been completed in accordance with GHS Rev04 (2011): U.S OSHA, CMA, ANSI, Canadian WHMIS standards, and European Directives.

Date of Preparation/Revision: 8/25/23

Supersedes: 1/31/20

To the best of our knowledge, the information contained herein is believed to be accurate. However, the above data does not imply any guarantee or warranty of any kind, expressed or implied. The final determination of the suitability of any material is the sole responsibility of the user. All materials made present un-known hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards existing.