



Safety Data Sheet

Revision Date 15-Nov-2016

Version 11

Supersedes Date: 08-Nov-2016

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product code 059.CM25624.076
Product name TY25624AU AG & TURF GREEN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Aerosol, Paint

1.3. Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar (Australia) Corporation Pty. Ltd.
203 Power Street
Glendenning, New South Wales 2761

For further information, please contact

E-mail address sdshelpdesk@valspareurope.com

1.4. Emergency telephone number

Emergency Telephone Number 1-300-954-120

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aspiration toxicity	Category 1 - (H304)
Skin Corrosion/Irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Specific target organ toxicity (repeated exposure)	Category 1 - (H372)
Chronic Aquatic Toxicity	Category 3 - (H412)
Flammable aerosols	Category 2 - (H223)

Classification according to 67/548/EEC

Full text of R-phrases: see section 16

Hazard symbols

T - Toxic

N - Dangerous for the environment

R-code(s)

R10 - T;R48/23 - Xn;R65 - Xi;R36 - R66 - R67 - N;R50/53

2.2. Label Elements



Contains Solvent naphtha, petroleum, medium aliphatic, Solvent naphtha, petroleum, light aromatic, Solvent naphtha, petroleum, light aliphatic, Xylenes (o-, m-, p- isomers), Toluene, Stoddard solvent, Ethylbenzene, Naphtha, petroleum, hydrotreated heavy, Petroleum distillates, hydrotreated light, Naphtha, petroleum, hydrodesulfurized heavy

Signal word

DANGER

HAZARD STATEMENTS

H223 - Flammable aerosol

H229 - Pressurised container: May burst if heated

H372 - Causes damage to organs through prolonged or repeated exposure

H304 - May be fatal if swallowed and enters airways

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H315 - Causes skin irritation

H412 - Harmful to aquatic life with long lasting effects

EUH208 - May produce an allergic reaction

EUH066 - Repeated exposure may cause skin dryness or cracking

PRECAUTIONARY STATEMENTS - EU (§28, 1272/2008)

P260 - Do not breathe dust/fume/gas/mist/vapours/spray

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P331 - Do NOT induce vomiting

P273 - Avoid release to the environment

Labelling (67/548/EEC or 1999/45/EC)

Contains Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, 2-Butanone, oxime, Solvent naphtha, petroleum, medium aliphatic, Solvent naphtha, petroleum, light aliphatic, Solvent naphtha, petroleum, light aromatic



Hazard symbols

T - Toxic

N - Dangerous for the environment

R-phrases

R10 - Flammable
R65 - Harmful: may cause lung damage if swallowed
R36 - Irritating to eyes
R66 - Repeated exposure may cause skin dryness or cracking
R67 - Vapours may cause drowsiness and dizziness
R48/23 - Toxic: danger of serious damage to health by prolonged exposure through inhalation
R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

S phrases

S7 - Keep container tightly closed
S9 - Keep container in a well-ventilated place
S16 - Keep away from sources of ignition - No smoking
S33 - Take precautionary measures against static discharges

May produce an allergic reaction
Pressurized container: Do not pierce or burn, even after use
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
Do not spray on naked flames or any incandescent materials
Keep away from sources of ignition - No smoking
Keep out of the reach of children

2.3. Other Hazards

Harmful to aquatic life

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Acetone	67-64-1	25 - 50
Solvent naphtha, petroleum, medium aliphatic	64742-88-7	10 - 25
Solvent naphtha, petroleum, light aromatic	64742-95-6	3 - 5
Solvent naphtha, petroleum, light aliphatic	64742-89-8	1 - 3
Benzene, 1,2,4-trimethyl-	95-63-6	1 - 3
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 3
Ethyl 3-ethoxypropanoate	763-69-9	1 - 3
Toluene	108-88-3	0.3 - 1
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0.1 - 0.3
Zirconium ethyl hexoate	22464-99-9	0.1 - 0.3
2-Butanone, oxime	96-29-7	0.1 - 0.3

If this section is blank, there are no hazardous components per NOHSC guidelines.

Section 4: FIRST AID MEASURES**4.1. Description of first aid measures****General Advice**

IF exposed or concerned: Get medical advice/attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin contact

IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.

INHALATION

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

INGESTION

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitisation by skin contact. spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal. Keep product and empty container away from heat and sources of ignition.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal Precautions

Avoid breathing vapours or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak.

For emergency responders

Use personal protection recommended in Section 8.

6.2. Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Methods for Containment

Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labelled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

General hygiene considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorised personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Protect from sunlight. Store in a well-ventilated place.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical name	Australia	New Zealand	ACGIH TLV
Acetone 67-64-1	TWA: 500 ppm TWA: 1185 mg/m ³ STEL: 1000 ppm STEL: 2375 mg/m ³	TWA: 500 ppm TWA: 1185 mg/m ³ STEL: 1000 ppm STEL: 2375 mg/m ³	STEL: 500 ppm TWA: 250 ppm
Benzene, 1,2,4-trimethyl- 95-63-6	TWA: 25 ppm TWA: 123 mg/m ³	TWA: 25 ppm TWA: 123 mg/m ³	TWA: 25 ppm
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 80 ppm TWA: 350 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³	TWA: 50 ppm TWA: 217 mg/m ³	STEL: 150 ppm TWA: 100 ppm
Toluene 108-88-3	TWA: 50 ppm TWA: 191 mg/m ³ STEL: 150 ppm STEL: 574 mg/m ³ S*	TWA: 50 ppm TWA: 188 mg/m ³ S*	TWA: 20 ppm
Zirconium ethyl hexoate 22464-99-9	TWA: 5 mg/m ³ STEL: 10 mg/m ³	TWA: 5 mg/m ³ STEL: 10 mg/m ³	STEL: 10 mg/m ³ Zr TWA: 5 mg/m ³ Zr

Biological Limit Values:.

Chemical name	Australia	New Zealand
Acetone 67-64-1		50 mg/L urine end of shift Acetone
Xylenes (o-, m-, p- isomers) 1330-20-7		1.5 g/L urine end of shift Methylhippuric acid

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Personal Protective Equipment

Eye/Face Protection

Tight sealing safety goggles.

Skin and Body Protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Laminated PE/EVAL

No information available

Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water
Local authorities should be advised if significant spillages cannot be contained

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Aerosol
Appearance	No information available
Odour	Solvent
Colour	Green
Odour threshold	No information available
PH	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	No information available °C / °F
Flash Point	-73 °C / -99 °F
Method	
Evaporation Rate	No information available
Flammability (solid, gas)	No information available
Flammability limit in air	
Upper flammability limit:	No information available
Lower flammability limit	No information available
Vapour pressure	No information available
Vapour Density	No information available
Solubility(ies)	Not determined
Partition coefficient	No information available
Autoignition Temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive Properties	No information available
Oxidising Properties	No information available

9.2. Other information

Molecular Weight	No information available
------------------	--------------------------

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerisation

None under normal processing.

Possibility of hazardous reactions

None under normal processing.

10.4. Conditions to avoid

Heat, flames and sparks.

10.5. Incompatible materials

Strong oxidising agents.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide (CO₂).

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Information on Likely Routes of Exposure

Eye Contact

Causes serious eye irritation

Skin contact

CAUSES SKIN IRRITATION

INGESTION

May be fatal if swallowed and enters airways

INHALATION

May cause drowsiness or dizziness

Numerical Measures of Toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal)	86,954.00 Mg/kg
ATEmix (inhalation-dust/mist)	53.10 Mg/l
ATEmix (inhalation-vapour)	389.00 Mg/l

UNKNOWN ACUTE TOXICITY .0001% of the mixture consists of ingredient(s) of unknown toxicity.

Numerical Measures of Toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h
Solvent naphtha, petroleum, medium aliphatic	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Solvent naphtha, petroleum, light aromatic	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Solvent naphtha, petroleum, light aliphatic	-	= 3000 mg/kg (Rabbit)	-
Benzene, 1,2,4-trimethyl-	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Xylenes (o-, m-, p- isomers)	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Ethyl 3-ethoxypropanoate	= 5 g/kg (Rat)	= 10 mL/kg (Rabbit)	-
Toluene	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	= 2615 mg/kg (Rat)	-	-
Zirconium ethyl hexoate	-	-	-
2-Butanone, oxime	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4800 mg/m ³ (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin Corrosion/Irritation	CAUSES SKIN IRRITATION
Serious eye damage/eye irritation	Causes serious eye irritation
Skin Sensitisation	Not applicable
Respiratory Sensitisation	Not applicable
Germ Cell Mutagenicity	Not applicable
Carcinogenicity	Not applicable
Reproductive toxicity	Not applicable
Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure)	Causes damage to organs through prolonged or repeated exposure
Aspiration Hazard	Not applicable

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

Environmental Precautions Prevent product from entering drains.

Chemical name	Algae/aquatic plants	Fish	Crustacea
Acetone 67-64-1	-	6210 - 8120 mg/L Pimephales promelas 96h LC50 = 8300 mg/L Lepomis macrochirus 96h LC50 4.74 - 6.33 mL/L Oncorhynchus mykiss 96h LC50	12600 - 12700 mg/L Daphnia magna 48h EC50 10294 - 17704 mg/L Daphnia magna 48h EC50
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	= 450 mg/L Pseudokirchneriella subcapitata 96 h EC50	= 800 mg/L Pimephales promelas 96h LC50	> 100 mg/L Daphnia magna 48h EC50
Solvent naphtha, petroleum, light aromatic 64742-95-6	-	= 9.22 mg/L Oncorhynchus mykiss 96h LC50	= 6.14 mg/L Daphnia magna 48h EC50
Solvent naphtha, petroleum, light aliphatic 64742-89-8	= 4700 mg/L Pseudokirchneriella subcapitata 72 h EC50	-	-
Benzene, 1,2,4-trimethyl- 95-63-6	-	= 7.72 mg/L Pimephales promelas 96h LC50 7.19 - 8.28 mg/L Pimephales promelas 96h LC50	= 6.14 mg/L Daphnia magna 48h EC50

Xylenes (o-, m-, p- isomers) 1330-20-7	-	2.661 - 4.093 mg/L Oncorhynchus mykiss 96h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96h LC50 = 19 mg/L Lepomis macrochirus 96h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96h LC50 23.53 - 29.97 mg/L Pimephales promelas 96h LC50 = 780 mg/L Cyprinus carpio 96h LC50 > 780 mg/L Cyprinus carpio 96h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96h LC50 = 13.4 mg/L Pimephales promelas 96h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96h LC50	= 0.6 mg/L Gammarus lacustris 48h LC50 = 3.82 mg/L water flea 48h EC50
Ethyl 3-ethoxypropanoate 763-69-9	-	= 62 mg/L Pimephales promelas 96h LC50	= 970 mg/L Daphnia magna 48h EC50
Toluene 108-88-3	= 12.5 mg/L Pseudokirchneriella subcapitata 72 h EC50 > 433 mg/L Pseudokirchneriella subcapitata 96 h EC50	= 28.2 mg/L Poecilia reticulata 96h LC50 = 54 mg/L Oryzias latipes 96h LC50 15.22 - 19.05 mg/L Pimephales promelas 96h LC50 50.87 - 70.34 mg/L Poecilia reticulata 96h LC50 = 12.6 mg/L Pimephales promelas 96h LC50 14.1 - 17.16 mg/L Oncorhynchus mykiss 96h LC50 5.89 - 7.81 mg/L Oncorhynchus mykiss 96h LC50 11.0 - 15.0 mg/L Lepomis macrochirus 96h LC50 = 5.8 mg/L Oncorhynchus mykiss 96h LC50	5.46 - 9.83 mg/L Daphnia magna 48h EC50 = 11.5 mg/L Daphnia magna 48h EC50
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7	-	= 0.97 mg/L Lepomis macrochirus 96h LC50	= 20 mg/L Daphnia magna 24h EC50
Zirconium ethyl hexoate 22464-99-9	-	-	-
2-Butanone, oxime 96-29-7	= 83 mg/L Desmodosmus subspicatus 72 h EC50	320 - 1000 mg/L Leuciscus idus 96h LC50 = 760 mg/L Poecilia reticulata 96h LC50 777 - 914 mg/L Pimephales promelas 96h LC50	= 750 mg/L Daphnia magna 48h EC50

12.2. Persistence and degradability

No information available

12.3. Bioaccumulative potential

No information available

Chemical name	Partition Coefficient (n-octanol/water)
Acetone 67-64-1	-0.24
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	-
Solvent naphtha, petroleum, light aromatic 64742-95-6	-

Solvent naphtha, petroleum, light aliphatic 64742-89-8	-
Benzene, 1,2,4-trimethyl- 95-63-6	3.63
Xylenes (o-, m-, p- isomers) 1330-20-7	3.15
Ethyl 3-ethoxypropanoate 763-69-9	1.35
Toluene 108-88-3	2.65
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7	0.37
Zirconium ethyl hexoate 22464-99-9	-
2-Butanone, oxime 96-29-7	0.65

12.4. Mobility in soil

No information available

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.

Section 14: TRANSPORT INFORMATION

14.1 UN/ID no	IMDG UN1950	ADG UN1950	IATA UN1950
14.2 Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
14.3 Hazard class	2.1	2.1	2.1
14.4 Packing group			
14.5 Environmental hazard	Not applicable		
14.6 Special Provisions			
14.7 Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC CODE	EmS-No F-D, S-U		No information available

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations

Australia

See section 8 for national exposure control parameters

International Inventories

AICS - Australian Inventory of Chemical Substances

All components are listed or exempt from listing

NZIoC - New Zealand Inventory of Chemicals

All components are listed or exempt from listing

15.2. Chemical safety assessment

No information available

Section 16: OTHER INFORMATION

DBNZ Coatings Limited
6 Killarney Lane
Hamilton 3243
New Zealand
T: +64 7847 0933 F: +64 7847 0932
E: info@dbnz.co.nz
www.dbnzcoatings.co.nz

Prepared by Product Stewardship

Revision Date 15-Nov-2016

Revision note Not applicable.

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

End of Safety Data Sheet