

RAABE PAINT COMPANY, INC. -- AEROSOLS, PAINT - ACRYLIC ENAMEL -- 8010-00B180033

=====
Product Identification
=====

Product ID:AEROSOLS, PAINT – ACRYLIC ENAMEL

MSDS Date:07/25/1986

FSC:8010

NIIN:00B180033

MSDS Number: BKLXC

==== Responsible Party ====

Company Name:RAABE PAINT COMPANY, INC.

Address:4530 N. 124TH STREET

Box:25398

City:WAUWATOSA

State:WI

ZIP:53225

Country:US

Info Phone Num:414-466-7480

Emergency Phone Num:414-466-7480

CAGE:DO905

==== Contractor Identification ====

Company Name:RAABE CORPORATION THE PRECISION COLOR COMPANY

Address:N92 W14701 ANTHONY AVE.

Box:1090

City:MENOMONEE FALLS

State:WI

ZIP:53051-1630

Country:US

Phone:414-255-9500/800-966-7580

CAGE:0A3L4

Company Name:RAABE PAINT COMPANY, INC.

Address:4530 N. 124TH STREET

Box:25398

City:WAUWATOSA

State:WI

ZIP:53225

Country:US

Phone:414-466-7480

CAGE:DO905

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE

CAS:108-88-3

Fraction by Wt: <5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENE

CAS:1330-20-7

Fraction by Wt: 5-10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:NOT SPECIFIED

ACGIH TLV:100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

2/19/2024; File reviewed; more current MSDS/SDS not available. CAS

Ingred Name:N-BUTYL ACETATE
CAS:123-86-4
Fraction by Wt: <5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:NOT SPECIFIED
ACGIH TLV:150 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:DIACETONE ALCOHOL
CAS:123-42-2
Fraction by Wt: <5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:NOT SPECIFIED
ACGIH TLV:50 PPM

Ingred Name:ACETONE
CAS:67-64-1
Fraction by Wt: 35-40%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE
CAS:74-98-6
Fraction by Wt: 20-25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:NOT SPECIFIED
ACGIH TLV:1000 PPM

Ingred Name:ISOBUTANE
CAS:75-28-5
Fraction by Wt: <5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:NOT SPECIFIED
ACGIH TLV:800 PPM

Ingred Name:N-BUTANE
CAS:106-97-8
Fraction by Wt: 5-10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:NOT SPECIFIED
ACGIH TLV:NOT SPECIFIED

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:REPORTS HAVE SHOWN REPEATED AND
PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT
BRAIN AND NERVOUS SYSTEM DAMAGE.
Effects of Overexposure:HIGH CONCENTRATIONS OF INHALED VAPORS ARE
ANESTHETIC, WILL IRRITATE THE RESPIRATORY TRACT, AND CAUSE NERVOUS
SYSTEM DEPRESSION CHARACTERIZED BY DROWSINESS, LIGHTHEADEDNESS,
HEADACHES, DIZZINESS, STAGG ERING, CONFUSION, UNCONSCIOUSNESS, OR
COMA. PRIMARY IRRITANT TO SKIN AND EYE.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF
PRE-EXISTING RESPIRATORY DISEASES MAY BE AT INCREASED RISK FROM
EXPOSURE.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH IMMEDIATELY WITH WATER FOR 15 MIN., CALL PHYSICIAN IMMEDIATELY. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INHALATION: REMOVE FROM EXPOSURE TO FRESH AIR, A PPLY ARTIFICIAL RESPIRATION IF NECESSARY, ADMINISTER OXYGEN IF NECESSARY. CALL PHYSICIAN IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY!

=====
===== Fire Fighting Measures =====

Flash Point Method:TOC
Flash Point:<-25F,<-32C
Lower Limits:.9
Upper Limits:12.8
Extinguishing Media:NFPA CLASS B. EXTINGUISHERS (CARBON DIOXIDE, DRY CHEMICAL OR FOAM).
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT, INCLUDING SCBA, SHOULD BE USED. WATER SPRAY MAY BE INEFFECTIVE ON FIRE, BUT MAY BE USED TO COOL CONTAINERS.
Unusual Fire/Explosion Hazard:DO NOT USE OR STORE NEAR HEAT, SPARKS OR OPEN FLAME. DO NOT SMOKE, PUNCTURE, INCINERATE, CRUSH. DON'T STORE ABOVE 1230F. KEEP AWAY FROM CHILDREN!

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA OF SPILL AND ADJACENT LOW LYING AREAS. REMOVE WITH INERT ABSORBENT AND NON SPARKING TOOLS.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT TEMPERATURES ABOVE 120F. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. DO NOT PUNCTURE. KEEP OUT OF THE REACH OF CHILDREN!
Other Precautions:USE ONLY AROUND EXPOSITION PROOF EQUIPMENT. AVOID PROLONGED BREATHING OF VAPORS. AVOID CONTACT WITH SKIN. DO NOT TAKE INTERNALLY. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING CONTENTS M AY BE HARMFUL OR FATAL!

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A BUREAU OF MINES APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY DURING SPRAY APPLICATION.
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV BELOW ACCEPTABLE LIMIT.
Protective Gloves:USE TO PREVENT PROLONGED CONTACT
Eye Protection:USE CHEMICAL SAFETY GOGGLES/SPLASHPROOF.
Other Protective Equipment:WEAR INDUSTRIAL WORK CLOTHING. HAVE EMERGENCY EYE WASH AVAILABLE.
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
DO NOT STORE ABOVE 120F. KEEP AWAY FROM SOURCES OF HEAT SUCH AS SUNLIGHT, RADIATORS, STOVES, HOT WATER, OR ANY OTHER SOURCE OF HEAT THAT COULD CAUSE CONTAINER TO HEAT AND BURST.

===== Physical/Chemical Properties =====

HCC:V3
Boiling Pt:B.P. Text:<0F,<-18C
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:NEGLIGIBLE
Appearance and Odor:USUALLY HAS COLOR, SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES
OF IGNITION
Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE MADE IN ACCORDANCE WITH
APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.