

## Safety Data Sheet - Petroleum Gases, Liquefied

### Section 1. Chemical Product and Company Identification

**Product Name** Master Appliance Ultratane Butane Fuel (Petroleum Gases, Liquefied)

**Supplier** Master Appliance Corp  
 2420 18th St  
 Racine WI 53403 USA

**Date Prepared** 03/14/14

**Emergency Telephone** 1-800-535-5053 (Infotrac)

### Section 2. Hazards Identification

**Physical State** Gas (COLORLESS LIQUEFIED COMPRESS GAS).  
 Product is colorless, tasteless, odorless and highly flammable.

**Emergency Overview** WARNING!  
 FLAMMABLE GAS.  
 MAY CAUSE FLASH FIRE.  
 MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.  
 CONTENTS UNDER PRESSURE.

Keep away from heat, sparks and flame. Do not puncture or incinerate container.  
 May cause target organ damage, based on animal data.  
 Use only with adequate ventilation.  
 Keep container closed.

Contact with rapidly expanding gases can cause frostbite.

WHMIS	Personal Protection Equipment	TDG (Ground)
		

**Target Organs** May cause damage to the following organs: Central Nervous System (CNS).

**Route of Entry** Inhalation  
 Acute exposure may cause nausea, vomiting, coughing and pulmonary irritation.

**Potential Acute Health Effects**

**Eyes** Contact with rapidly expanding gas may cause burns or frostbite.

**Skin** Contact with rapidly expanding gas may cause burns or frostbite.

**Inhalation** Acts as a simple asphyxiant.

**Ingestion** Ingestion is not a normal route of exposure for gases.

**Potential Chronic Health Effects**

**Target Organs** May cause damage to the following organs: Central Nervous System (CNS)

**Medical Conditions** Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

**Aggravated By Over-Exposure**

See Toxicological Information (Section 11)

# Safety Data Sheet - Petroleum Gases, Liquefied

---

## Section 3. Composition, Information on Ingredients

---

(Specific Chemical Identity: Common Name(s))		OSHA PEL	ACGIH TLV
Isobutane	CAS 75-28-5	NE	1000 ppm
Propane	CAS 74-98-6	1000ppm	1000 ppm
Butane	CAS 106-97-8	800ppm	TWA: 1000 ppm 8 hour(s)

---

## Section 4. First Aid Measures

---

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

**Eye Contact** Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

**Skin Contact** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. To avoid the risk of static discharge and gas ignition, soak contaminated clothing thoroughly with water before removing it. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

**Frostbite** Try to warm up the frozen tissues and seek medical attention.

**Inhalation** Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

**Ingestion** As this product is gas, refer to the inhalation section.

---

## Section 5. Fire-Fighting Measures

---

**Flammability of Product** Flammable

**Auto-Ignition Temperature** 286.85°C (548.3°F)

**Flash Point** Closed Cup: -60.15°C (-76.3°F)

**Flammable Limits** Lower: 1.4% Upper: 9.5%

**Products of Combustion** Decomposition products may include the following materials:  
carbon dioxide and carbon monoxide

**Fire Hazards in the Presence of Various Substances** Extremely flammable in the presence of the following materials or conditions:  
open flames, sparks and static discharge and oxidizing materials

**Fire-Fighting Media and Instructions** In case of fire, use water spray (fog), foam or dry chemical.

In case of fire, allow gas to burn if flow cannot be shut off immediately. Apply water from a safe distance to cool container and protect surrounding area. If involved in fire, shut off flow immediately if it can be done without risk.

Contains gas under pressure. Flammable gas. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Avoid rocketing containers.

# Safety Data Sheet - Petroleum Gases, Liquefied

## Special Protective Equipment for Fire-Fighters

Fire-Fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Follow OSHA regulations [29 CFR\*1910.120(g)]. Emergency response to hazardous substances.

---

## Section 6. Accidental Release Measures

---

### Personal Precautions

Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (section 8). Shut off gas supply if this can be done safely. Isolate area until gas has dispersed.

### Environmental Precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Methods for Cleaning Up

Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Note: See section 1 for emergency contact information and section 13 for waste disposal.

---

## Section 7. Handling and Storage

---

### Handling

Use only with adequate ventilation. Use explosion-proof electrical (ventilating, lighting, and material handling) equipment. High pressure gas. Do not puncture or incinerate container. Keep container closed. Keep away from heat, sparks and flame. To avoid fire, eliminate ignition sources. Protect cylinders from physical damage; do not drag, roll, slide or drop. Use a suitable hand truck for cylinder removal.

### Storage

Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). Segregate from oxidizing materials. Cylinders should be stored upright with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52°C (125°F).

---

## Section 8. Exposure Controls/Personal Protection

---

### Engineering Controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor, or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Personal Protection

#### Eyes

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, or dusts.

#### Skin

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

# Safety Data Sheet - Petroleum Gases, Liquefied

**Hands** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Personal Protection in Case of a Large Spill** Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product.

## Product Name

Butane

**ACGIH TLV (United States, 3/2012).**

TWA: 1000 ppm 8 hour(s)

**NIOSH REL (United States, 1/2013).**

TWA: 1900 mg/m<sup>3</sup> 10 hour(s)

TWA: 800 ppm 10 hour(s)

**OSHA PEL 1989 (United States, 3/1989).**

TWA: 1900 mg/m<sup>3</sup> 10 hour(s)

TWA: 800 ppm 10 hour(s)

Consult local authorities for acceptable exposure limits.

---

## Section 9. Physical and Chemical Properties

---

<b>Molecular Weight</b>	58.14 g/mole
<b>Molecular Formula</b>	C4-H10
<b>Boiling/Condensation Point</b>	-0.6°C (30.9°F)
<b>Melting/Freezing Point</b>	-135.4°C (-211.7°F)
<b>Critical Temperature</b>	151.9°C (305.4°F)
<b>Vapor Pressure @ 70°F</b>	30 ± 2 (psig)
<b>Vapor Density</b>	2 (air = 1)
<b>Specific Volume (ft<sup>3</sup>/lb)</b>	6.435
<b>Gas Density (lb/ft<sup>3</sup>)</b>	0.1554

---

## Section 10. Stability and Reactivity

---

<b>Stability and Reactivity</b>	The product is stable.
<b>Incompatibility with Various Substances</b>	Extremely reactive or incompatible with the following materials: Oxidizing Materials
<b>Hazardous Decomposition Products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
<b>Hazardous Polymerization</b>	Under normal conditions of storage and use, hazardous polymerization will not occur.

---

## Section 11. Toxicological Information

---

### Toxicity Data

<b>Product/Ingredient Name</b>	<b>Result</b>	<b>Species</b>	<b>Dose</b>	<b>Exposure</b>
Butane	LC50 Inhalation Vapor	Rat	658000 mg/m3	4 hours

# Safety Data Sheet - Petroleum Gases, Liquefied

**Chronic Effects On Humans**                      May cause damage to the following organs: Central Nervous System (CNS).

**Other Toxic Effects On Humans**              No specific information is available in our database regarding the other toxic effects of this material to humans.

**Special Effects**

**Carcinogenic Effects**                              No known significant effects or critical hazards.

**Mutagenic Effects**                                 No known significant effects or critical hazards.

**Reproduction Toxicity**                         No known significant effects or critical hazards.

## Section 12. Ecological Information

**Aquatic Ecotoxicity**                              Not available

**Products of Degradation**                        Products of degradation: Carbon Oxides (CO, CO<sub>2</sub>) and water.

**Environmental Fate**                                Not available



**Environmental Hazards**                         No known significant effects or critical hazards.

**Toxicity to the Environment**                 Not available


## Section 13. Disposal Considerations

**Product removed from the cylinder must be disposed of in accordance with appropriate Federal, State, and Local regulation.**

## Section 14. Transport Information

Regulatory Information	UN Number	Proper Shipping Name	Class	Packing Group	Label	Additional Information
<b>DOT Classification</b>	UN1075	Petroleum Gases, Liquefied	2.1	Not Applicable (gas)		<p><b><u>Limited Quantity</u></b> Yes</p> <p><b><u>Packing Instruction</u></b>  <b>Passenger Aircraft</b>                      Quantity Limitation:                      Forbidden</p> <p><b>Cargo Aircraft</b>                      Quantity Limitation:                      150 kg</p> <p><b>Special Provisions</b>                      19, T50</p>
<b>TDG Classification</b>	UN1075	Petroleum Gases, Liquefied	2.1	Not Applicable (gas)		<p><b>Explosive Limit and Limited Quantity Index</b>                      0.125</p>

## Safety Data Sheet - Petroleum Gases, Liquefied

Regulatory Information	UN Number	Proper Shipping Name	Class	Packing Group	Label	Additional Information
<b>TDG Classification</b>						<b>ERAP Index</b> 3000  <b>Passenger Carrying Ship Index</b> Forbidden  <b>Passenger Carrying Road or Rail Index</b> Forbidden  <b>Special Provision</b> 29
<b>Mexico Classification</b>	UN1075	Petroleum Gases, Liquefied	2.1	Not Applicable (gas)		-

Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the products.

---

### Section 15. Regulatory Information

---

#### United States

##### US Federal Regulations

**TSCA 8(a) IUR:** Not determined  
**United States Inventory (TSCA 8b):** This material is listed or exempted.  
**SARA 302/304/311/312 Extremely Hazardous Substances:** No products were found.  
**SARA 302/304 Emergency Planning and Notification:** No products were found.  
**SARA 302/304/311/312 Hazardous Chemicals:** Butane  
**SARA 311/312 MSDS Distribution - Chemical Inventory - Hazard Identification:**  
 Butane: Fire hazard, Sudden release of pressure  
**Clean Water Act (CWA) 311:** No products were found.  
**Clean Air Act (CAA) 112 Regulated Flammable Substances:** Butane

##### State Regulations

**Connecticut Carcinogen Reporting:** This material is not listed.  
**Connecticut Hazardous Material Survey:** This material is not listed.  
**Florida Substances:** This material is not listed  
**Illinois Chemical Safety Act:** This material is not listed.  
**Illinois Toxic Substances Disclosure to Employee Act:** This material is not listed.  
**Louisiana Reporting:** This material is not listed.  
**Louisiana Spill:** This material is not listed.  
**Massachusetts Spill:** This material is not listed.  
**Massachusetts Substances:** This material is not listed.  
**Michigan Critical Material:** This material is not listed.  
**Minnesota Hazardous Substance:** This material is not listed.  
**New Jersey Hazardous Substances:** This material is not listed.  
**New Jersey Spill:** This material is not listed.  
**New Jersey Toxic Catastrophe Prevention Act:** This material is not listed.  
**New York Acutely Hazardous Substances:** This material is not listed.

# Safety Data Sheet - Petroleum Gases, Liquefied

**New York Toxic Chemical Release Reporting:** This material is not listed.

**Pennsylvania RTK Hazardous Substances:** This material is not listed.

**Rhode Island Hazardous Substances:** This material is not listed.

## Canada

### WHMIS (Canada)

Class A: Compressed gas.

Class B-1: Flammable gas.

**CEPA Toxic Substances:** This material is not listed.

**Canadian ARET:** This material is not listed.

**Canadian NPRI:** This material is not listed.

**Alberta Designated Substances:** This material is not listed.

**Ontario Designated Substances:** This material is not listed.

**Quebec Designated Substances:** This material is not listed.

## Section 16. Other Information

### United States

#### Label Requirements

FLAMMABLE GAS.

MAY CAUSE FLASH FIRE.

MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

CONTENTS UNDER PRESSURE.

### Canada

#### Label Requirements

Class A: Compressed Gas.

Class B-1: Flammable Gas.

### United States

#### Hazardous Material Information System

Health	*	1
Flammability		4
Physical Hazards		0

### National Fire Protection Association

Health	1
Flammability	4
Instability	0
Special	



### Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.